

The `automultiplechoice` package*

Alexis Bienvenüe
`paamc@passoire.fr`

January 21, 2021

Abstract

This package helps designing multiple choice exams ready for automated marking from papers scans.

Answers and questions are optionaly shuffled, creating different sheets for every student.

1 Introduction

The package `automultiplechoice` helps formatting multiple choice questionnaires with automated marking from papers scans in mind:

- The package can produce different copies of the question sheet for each student, optionaly shuffling answers and questions for each student.
- Markers can be printed on each sheet, so as to be able to analyse scans after examination. All the needed information about the position of the markers and the boxes to be checked by the students is given in an auxiliary file during L^AT_EX run.

See Auto Multiple Choice (AMC) software (<https://www.auto-multiple-choice.net/>) for an integration of this package, with user interface for automated marking.

2 Samples

We begin with several samples to see what can be done with the `automultiplechoice` package. All `automultiplechoice` commands and options will be detailed further.

For all these samples, two sets of questions are used: a group of geography questions, and a group of history questions. These are defined in a common L^AT_EX file named `questions.tex`:

```
\element{geography}{\begin{question}{Ghana}\text{What is the capital of Ghana?}\begin{choiceshoriz}\correctchoice{Accra}
```

*This document corresponds to version revision: r:b8156497 from AMC 1.5.0~rc1

```

\wrongchoice{Addis Abeba}
\wrongchoice{Ankara}
\wrongchoice{Apia}
\end{choiceshoriz}
\end{question}
}

\element{geography}{
\begin{question}{Thailand}
What is the capital of Thailand?
\begin{choiceshoriz}
\correctchoice{Bangkok}
\wrongchoice{Banjul}
\wrongchoice{Beijing}
\wrongchoice{Beirut}
\wrongchoice{Berlin}
\end{choiceshoriz}
\end{question}
}

\element{geography}{
\begin{question}{Egypt}
What is the capital of Egypt?
\begin{choices}
\correctchoice{Cairo}
\wrongchoice{Caracas}
\wrongchoice{Cayenne}
\wrongchoice{Chisinau}
\wrongchoice{Conakry}
\end{choices}
\end{question}
}

\element{geography}{
\begin{question}{Ireland}
What is the capital of Ireland?
\begin{multicols}{3}
\begin{choices}
\correctchoice{Dublin}
\wrongchoice{Dili}
\wrongchoice{Djibouti}
\wrongchoice{Doha}
\wrongchoice{Dakar}
\wrongchoice{Dhaka}
\end{choices}
\end{multicols}
}

```

```

        \end{question}

    }

\element{history}{
\begin{questionmult}{1901}
    Which of the following events are taking place during the year
    1901?
\begin{choices}
    \correctchoice{Funeral of Queen Victoria in London}
    \correctchoice{Official end of the Caste War of Yucat\'an}
    \wrongchoice{King George of Greece becomes absolute monarch of Crete}
    \wrongchoice{The first line of the Paris M\'etro is opened}
\end{choices}
\end{questionmult}
}

\element{history}{
\begin{questionmult}{1850}
    Which of the following events are taking place during the year
    1850?
\begin{choices}
    \correctchoice{American Express is founded by Henry Wells \& William Fargo}
    \wrongchoice{Napoleon Bonaparte crosses the Alps and invades Italy}
    \wrongchoice{Kwang-su becomes emperor of China}
    \wrongchoice{First horse-drawn omnibuses established in London}
\end{choices}
\end{questionmult}
}

\element{history}{
\begin{questionmult}{1971}
    Which of the following events are taking place during the year
    1971?
\begin{choices}
    \correctchoice{Apollo 14 lands on the Moon}
    \correctchoice{The Soviet Union launches Salyut 1}
    \correctchoice{Death of Louis Armstrong}
    \wrongchoice{The first commercial Concorde flight takes off}
\end{choices}
\end{questionmult}
}

```

We will ask automultiplechoice package to include two geography questions and two history questions at random for each student, shuffling questions and answers, with the following code:

```
\cleargroup{all}
\shufflegroup{geography}
```

```
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}
```

You can read these commands as “clear group `all`, shuffle questions inside group `geography` and copy the first two to group `all`, do the same for group `history`, shuffle the four questions copied into `all` and print them”.

2.1 Standard layout

A set of 30 students sheets can be produced from the following L^AT_EX source named `sample-amc.tex`:

```
\documentclass{article}
\usepackage{automultiplechoice}
\usepackage{multicol}
\begin{document}

\input{questions.tex}

\onecopy{30}{}

\noindent{\bf AMC} \hfill SAMPLE TEST

\vspace{3ex}
```

For this test, package `\sf automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\tt nowatermark` option.

Commands from `\sf automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

```
\vspace{3ex}

\cleargroup{all}

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

}
```

```
\end{document}
```

producing a 30-pages document (every page has number 1), from which we show the first pages on page 8.

Note that “DRAFT” indications can be cancelled using option `nowatermark` , or using AMC software.

You can see on each page markers that can be used for automated completed answer sheets scans analysis:

- Four circles ● are printed in the corners, to be able to analyse any rotation or scaling of the scans.
- Binary boxes are printed in the header area, so as to be able to read student sheet number and page number. On page 2 for example, you can see that these binary boxes are coding 2/1/59:



Here, 2 is the student sheet number, 1 is the page number for this student, and 59 is a checking value that can be used for checking correct identification from a scan.

If you also use `calibration` option , `automultiplechoice` will produce a `.xy` file with informations about the exact position in the page of all the markers, and all the boxes. This option is automatically set by AMC software, which then use the information in the `.xy` file for automated marking.

2.2 Separate answer sheet

In some situations, you may need a separate answer sheet:

- this makes cheating even more difficult;
- this can reduce the number of pages to scan.

This is done using `separateanswersheet` option of `automultiplechoice` package. You also have to use commands `\AMCformBegin` to indicate the beginning of this separate answer sheet (usually after a `\clearpage` or `\AMCcleardoublepage` command), and `\AMCform` to insert the form to be completed by the students, as in the following example (`sample-separate.tex`):

```
\documentclass{article}
\usepackage[separateanswersheet]{automultiplechoice}
\usepackage{multicol}
\begin{document}

\input{questions.tex}

\onecopy{30}{
```

```

\noindent{\bf AMC} \hfill SAMPLE TEST}

\vspace{3ex}

For this test, package {\sf automultiplechoice} is used with {\tt
separateanswersheet} option, so that all answers are to be filled on
a separate sheet by students. Page markers are printed in view of an
automated marking from papers scans. DRAFT indications can be
cancelled using {\tt nowatermark} option.

Commands from {\sf automultiplechoice} are used to print, for each
student, two geography questions and two history questions, at
random. Questions and answers are shuffled.

\vspace{3ex}

\cleargroup{all}

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

\clearpage

\AMCformBegin

This is the answer sheet: all answers are to be ticked on this page to
be taken into account.

\vspace{2ex}

\AMCform

}

\end{document}

```

First pages of the result are shown on page 9. There are now 2 pages per student: the first with questions, and the second for answers. Only the second will be completed by the students, and scanned for analysis.

2.3 Without markers

With the `nopage` option , package `automultiplechoice` does not include any page markers for scan processing. I'm afraid you can't use any automated marking software with this layout, but you can

still use answer sheet and corrected answer sheet (option `indivanswers`, added here) for a manual marking...

The L^AT_EX source `sample-plain.tex` that only differs from `sample-amc.tex` by its options passed to `automultiplechoice`:

```
\usepackage[nopage,indivanswers]{automultiplechoice}
```

produces a 30-pages document, from which we show the first pages on page 10.

First pages from L^AT_EX source detailed in section 2.1 – see sample-amc.pdf

<p>AMC</p> <p style="text-align: right;">+1/1/60*</p> <p>SAMPLE TEST</p> <p>For this test, package <code>automultiplechoice</code> is used without any option. Page markers are printed in view of an automated marking from paper scans. DRAFT indications can be canceled using <code>no水印</code> option.</p> <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1971?</p> <ul style="list-style-type: none"> <input type="checkbox"/> The Soviet Union launches Salyut 1 <input type="checkbox"/> The first commercial Concorde flight takes off <input type="checkbox"/> Apollo 14 lands on the Moon <input checked="" type="checkbox"/> Apollo 14 lands on the Moon <p>Question 2 What is the capital of Egypt?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Cayenne <input type="checkbox"/> Caracas <input type="checkbox"/> Cairo <input type="checkbox"/> Conakry <input type="checkbox"/> Dakar <p>Question 3 Which of the following events are taking place during the year 1850?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input type="checkbox"/> First horse-drawn omnibus established in London <input type="checkbox"/> American Express is founded by Henry Wells & William Fargo <input type="checkbox"/> Kwang-on becomes emperor of China <p>Question 4 What is the capital of Ghana?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Accra <input checked="" type="checkbox"/> Addis Abeba <input type="checkbox"/> Ankara <input type="checkbox"/> Apia <p style="text-align: center;"><i>For your examination, preferably print documents compiled from auto-multiple-choice.</i></p>	<p>AMC</p> <p style="text-align: right;">+2/1/59*</p> <p>SAMPLE TEST</p> <p>For this test, package <code>automultiplechoice</code> is used without any option. Page markers are printed in view of an automated marking from paper scans. DRAFT indications can be canceled using <code>no水印</code> option.</p> <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1901?</p> <ul style="list-style-type: none"> <input type="checkbox"/> The first line of the Paris Metro is opened <input type="checkbox"/> Official end of the Caste War of Yucatan <input type="checkbox"/> King George of Greece becomes absolute monarch of Crete <input type="checkbox"/> Funeral of Queen Victoria in London <p>Question 2 What is the capital of Ireland?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Djibouti <input type="checkbox"/> Dublin <input type="checkbox"/> Doha <input type="checkbox"/> Dili <p>Question 3 What is the capital of Ghana?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Apia <input type="checkbox"/> Accra <input checked="" type="checkbox"/> Addis Abeba <input type="checkbox"/> Ankara <p>Question 4 Which of the following events are taking place during the year 1850?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input type="checkbox"/> First horse-drawn omnibus established in London <input type="checkbox"/> American Express is founded by Henry Wells & William Fargo <input type="checkbox"/> Kwang-on becomes emperor of China <p style="text-align: center;"><i>For your examination, preferably print documents compiled from auto-multiple-choice.</i></p>
<p>AMC</p> <p style="text-align: right;">+3/1/58*</p> <p>SAMPLE TEST</p> <p>For this test, package <code>automultiplechoice</code> is used without any option. Page markers are printed in view of an automated marking from paper scans. DRAFT indications can be canceled using <code>no水印</code> option.</p> <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1971?</p> <ul style="list-style-type: none"> <input type="checkbox"/> The first commercial Concorde flight takes off <input type="checkbox"/> Apollo 14 lands on the Moon <input type="checkbox"/> The Soviet Union launches Salyut 1 <input checked="" type="checkbox"/> Apollo 14 lands on the Moon <p>Question 2 Which of the following events are taking place during the year 1850?</p> <ul style="list-style-type: none"> <input type="checkbox"/> First horse-drawn omnibus established in London <input type="checkbox"/> Kwang-on becomes emperor of China <input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input type="checkbox"/> American Express is founded by Henry Wells & William Fargo <p>Question 3 What is the capital of Ireland?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Daka <input type="checkbox"/> Dili <input type="checkbox"/> Dakar <input type="checkbox"/> Djibouti <p>Question 4 What is the capital of Thailand?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Beijing <input type="checkbox"/> Banjul <input type="checkbox"/> Bangkok <input type="checkbox"/> Beirut <input type="checkbox"/> Berlin <p style="text-align: center;"><i>For your examination, preferably print documents compiled from auto-multiple-choice.</i></p>	<p>AMC</p> <p style="text-align: right;">+4/1/57*</p> <p>SAMPLE TEST</p> <p>For this test, package <code>automultiplechoice</code> is used without any option. Page markers are printed in view of an automated marking from paper scans. DRAFT indications can be canceled using <code>no水印</code> option.</p> <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1971?</p> <ul style="list-style-type: none"> <input type="checkbox"/> The Soviet Union launches Salyut 1 <input type="checkbox"/> Apollo 14 lands on the Moon <input type="checkbox"/> Death of Louis Armstrong <input type="checkbox"/> The first commercial Concorde flight takes off <p>Question 2 What is the capital of Egypt?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Caracas <input type="checkbox"/> Cayenne <input type="checkbox"/> Cairo <input type="checkbox"/> Conakry <input type="checkbox"/> Dakar <p>Question 3 Which of the following events are taking place during the year 1850?</p> <ul style="list-style-type: none"> <input type="checkbox"/> American Express is founded by Henry Wells & William Fargo <input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input type="checkbox"/> First horse-drawn omnibus established in London <input type="checkbox"/> Kwang-on becomes emperor of China <p>Question 4 What is the capital of Ireland?</p> <ul style="list-style-type: none"> <input type="checkbox"/> Djibouti <input type="checkbox"/> Dili <input type="checkbox"/> Doha <input type="checkbox"/> Dublin <p style="text-align: center;"><i>For your examination, preferably print documents compiled from auto-multiple-choice.</i></p>

First pages from L^AT_EX source detailed in section 2.2 – see sample-separate.pdf

<p>AMC</p> <p style="text-align: center;">SAMPLE TEST</p> <p>For this test, package <code>automultiplechoice</code> is used with <code>separatenosheet</code> option, so all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from paper scans. DRAFT indications can be cancelled using <code>nowatermark</code> option.</p> <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1971?</p> <p><input type="checkbox"/> The Soviet Union launches Salyut 1 <input type="checkbox"/> The first commercial Concorde flight takes off <input type="checkbox"/> Death of Louis Armstrong <input type="checkbox"/> Apollo 14 lands on the Moon</p> <p>Question 2 What is the capital of Egypt?</p> <p><input type="checkbox"/> Cayenne <input type="checkbox"/> Caracas <input type="checkbox"/> Cairo <input type="checkbox"/> Conakry <input type="checkbox"/> Chisinau</p> <p>Question 3 Which of the following events are taking place during the year 1850?</p> <p><input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input type="checkbox"/> First horse-drawn omnibuses established in London <input type="checkbox"/> American Express is founded by Henry Wells & William Fargo <input type="checkbox"/> Kuang-kuo becomes emperor of China</p> <p>Question 4 What is the capital of Ghana?</p> <p><input checked="" type="checkbox"/> Accra <input type="checkbox"/> Addis Ababa <input type="checkbox"/> Aukara <input type="checkbox"/> Apia</p> <p style="text-align: center;">For your examination, preferably print documents compiled from auto-multiple-choice.</p>	<p style="text-align: center;">+1/1/60+</p>  <p>This is the answer sheet: all answers are to be ticked on this page to be taken into account.</p> <p>Question 1: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> Question 2: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> Question 3: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> Question 4: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/></p> <p style="text-align: center;">+1/2/59+</p>  <p style="text-align: center;">DRAFT</p> <p style="text-align: center;">For your examination, preferably print documents compiled from auto-multiple-choice.</p>
<p>AMC</p> <p style="text-align: center;">SAMPLE TEST</p> <p>For this test, package <code>automultiplechoice</code> is used with <code>separatenosheet</code> option, so all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from paper scans. DRAFT indications can be cancelled using <code>nowatermark</code> option.</p> <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1901?</p> <p><input type="checkbox"/> The first line of the Paris Metro is opened <input type="checkbox"/> Official end of the Caste War of Yucatán <input type="checkbox"/> King George of Greece becomes absolute monarch of Crete <input type="checkbox"/> Funeral of Queen Victoria in London</p> <p>Question 2 What is the capital of Ireland?</p> <p><input type="checkbox"/> Djibouti <input type="checkbox"/> Dhaka <input type="checkbox"/> Dublin <input type="checkbox"/> Dakar</p> <p>Question 3 What is the capital of Ghana?</p> <p><input type="checkbox"/> Apia <input checked="" type="checkbox"/> Accra <input type="checkbox"/> Addis Ababa <input type="checkbox"/> Aukara</p> <p>Question 4 Which of the following events are taking place during the year 1860?</p> <p><input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input type="checkbox"/> First horse-drawn omnibuses established in London <input type="checkbox"/> American Express is founded by Henry Wells & William Fargo <input type="checkbox"/> Kuang-kuo becomes emperor of China</p> <p style="text-align: center;">For your examination, preferably print documents compiled from auto-multiple-choice.</p>	<p style="text-align: center;">+2/1/58+</p>  <p>This is the answer sheet: all answers are to be ticked on this page to be taken into account.</p> <p>Question 1: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> Question 2: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> Question 3: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> Question 4: <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/></p> <p style="text-align: center;">+2/2/57+</p>  <p style="text-align: center;">DRAFT</p> <p style="text-align: center;">For your examination, preferably print documents compiled from auto-multiple-choice.</p>

First pages from L^AT_EX source detailed in section 2.3 – see sample-plain.pdf

<p>AMC</p> <p>For this test, package <code>automultiplechoice</code> is used with the following options:</p> <ul style="list-style-type: none"> <code>\nospage</code>, so that no page markers are printed: nothing is planned for future automated marking from papers scans. <code>\indivanswers</code>, so that correct answers are indicated (this is the correct answer sheet). Without this option, you get the question sheet). <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1971?</p> <p><input checked="" type="checkbox"/> The Soviet Union launches Salyut 1 <input type="checkbox"/> The first commercial Concorde flight takes off <input checked="" type="checkbox"/> Death of Louis Armstrong <input type="checkbox"/> Apollo 14 lands on the Moon</p> <p>Question 2 What is the capital of Egypt?</p> <p><input type="checkbox"/> Cayenne <input type="checkbox"/> Caracas <input checked="" type="checkbox"/> Cairo <input type="checkbox"/> Conakry <input type="checkbox"/> Chisinau</p> <p>Question 3 Which of the following events are taking place during the year 1850?</p> <p><input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input type="checkbox"/> First horse-drawn omnibuses established in London <input checked="" type="checkbox"/> American Express is founded by Henry Wells & William Fargo <input type="checkbox"/> Kwang-su becomes emperor of China</p> <p>Question 4 What is the capital of Ghana?</p> <p><input checked="" type="checkbox"/> Accra <input type="checkbox"/> Addis Ababa <input type="checkbox"/> Ankara <input type="checkbox"/> Apia</p>	<p>SAMPLE TEST</p> <p>For this test, package <code>automultiplechoice</code> is used with the following options:</p> <ul style="list-style-type: none"> <code>\nospage</code>, so that no page markers are printed: nothing is planned for future automated marking from papers scans. <code>\indivanswers</code>, so that correct answers are indicated (this is the correct answer sheet). Without this option, you get the question sheet). <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1901?</p> <p><input type="checkbox"/> The first line of the Paris Métro is opened <input checked="" type="checkbox"/> Official end of the Caste War of Yucatán <input type="checkbox"/> King George of Greece becomes absolute monarch of Crete <input type="checkbox"/> Funeral of Queen Victoria in London</p> <p>Question 2 What is the capital of Ireland?</p> <p><input type="checkbox"/> Djibouti <input type="checkbox"/> Dhaka <input type="checkbox"/> Doha <input checked="" type="checkbox"/> Dublin <input type="checkbox"/> Dili <input type="checkbox"/> Dukar</p> <p>Question 3 What is the capital of Ghana?</p> <p><input type="checkbox"/> Apia <input checked="" type="checkbox"/> Accra <input type="checkbox"/> Addis Ababa <input type="checkbox"/> Ankara</p> <p>Question 4 Which of the following events are taking place during the year 1850?</p> <p><input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input type="checkbox"/> First horse-drawn omnibuses established in London <input checked="" type="checkbox"/> American Express is founded by Henry Wells & William Fargo <input type="checkbox"/> Kwang-su becomes emperor of China</p>
1	1
<p>AMC</p> <p>For this test, package <code>automultiplechoice</code> is used with the following options:</p> <ul style="list-style-type: none"> <code>\nospage</code>, so that no page markers are printed: nothing is planned for future automated marking from papers scans. <code>\indivanswers</code>, so that correct answers are indicated (this is the correct answer sheet). Without this option, you get the question sheet). <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1971?</p> <p><input type="checkbox"/> The first commercial Concorde flight takes off <input checked="" type="checkbox"/> Apollo 14 lands on the Moon <input checked="" type="checkbox"/> The Soviet Union launches Salyut 1 <input type="checkbox"/> Death of Louis Armstrong</p> <p>Question 2 Which of the following events are taking place during the year 1850?</p> <p><input type="checkbox"/> First horse-drawn omnibuses established in London <input type="checkbox"/> Kwang-su becomes emperor of China <input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input checked="" type="checkbox"/> American Express is founded by Henry Wells & William Fargo</p> <p>Question 3 What is the capital of Ireland?</p> <p><input type="checkbox"/> Dhaka <input type="checkbox"/> Doha <input type="checkbox"/> Dakar <input type="checkbox"/> Dili <input checked="" type="checkbox"/> Dublin <input type="checkbox"/> Djibouti</p> <p>Question 4 What is the capital of Thailand?</p> <p><input type="checkbox"/> Beijing <input type="checkbox"/> Basjul <input checked="" type="checkbox"/> Bangkok <input type="checkbox"/> Beirut <input type="checkbox"/> Berlin</p>	<p>SAMPLE TEST</p> <p>For this test, package <code>automultiplechoice</code> is used with the following options:</p> <ul style="list-style-type: none"> <code>\nospage</code>, so that no page markers are printed: nothing is planned for future automated marking from papers scans. <code>\indivanswers</code>, so that correct answers are indicated (this is the correct answer sheet). Without this option, you get the question sheet). <p>Commands from <code>automultiplechoice</code> are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.</p> <p>Question 1 Which of the following events are taking place during the year 1971?</p> <p><input checked="" type="checkbox"/> The Soviet Union launches Salyut 1 <input type="checkbox"/> Apollo 14 lands on the Moon <input checked="" type="checkbox"/> Death of Louis Armstrong <input type="checkbox"/> The first commercial Concorde flight takes off</p> <p>Question 2 What is the capital of Egypt?</p> <p><input type="checkbox"/> Caracas <input type="checkbox"/> Cayenne <input type="checkbox"/> Cairo <input type="checkbox"/> Conakry <input type="checkbox"/> Chisinau</p> <p>Question 3 Which of the following events are taking place during the year 1850?</p> <p><input checked="" type="checkbox"/> American Express is founded by Henry Wells & William Fargo <input type="checkbox"/> Napoleon Bonaparte crosses the Alps and invades Italy <input type="checkbox"/> First horse-drawn omnibuses established in London <input type="checkbox"/> Kwang-su becomes emperor of China</p> <p>Question 4 What is the capital of Ireland?</p> <p><input type="checkbox"/> Djibouti <input type="checkbox"/> Doha <input type="checkbox"/> Dakar <input type="checkbox"/> Dili <input type="checkbox"/> Dublin</p>
1	1

3 Usage

3.1 Package options

The following options are available for package `automultiplechoice`:

`noshuffle` cancels answers shuffling for all questions.

`noshufflegroups` cancels groups shuffling.

`answers` produces a common corrected answers sheet.

`indivanswers` shows the boxes that corresponds to correct choices on the question sheet.

`box` includes every question in a L^AT_EX box, so that they can't be cutted on two different pages.

`asbox` does the same for questions in the separate answer sheet.

`separateanswersheet` asks for a separate answer sheet (see section 2.2 for an example). Commands `\AMCformBegin` and `\AMCform` must be used to describe the separate answer sheet (see section 3.6).

`digits` puts digits instead of letters in the boxes, when `separateanswersheet` (or `insidebox`) is used.

`outsidebox` prints boxes labels outside the boxes on the answersheet when `separateanswersheet` is set.

`init` initializes the random generator from time. *This option is only for testing: don't use it for a real exam!*

`completetmulti` adds an answer "None of these answers are correct." at the end of each multiple question (question with no, one or several correct answers), so as to make the difference between "I don't know" and "I think none of the answers are correct".

`insidebox` puts a letter (or a digit if `digits` option is used) inside the boxes, even if `separateanswersheet` is not used. The `insidebox` option is implicitly called when using `separateanswersheet`: no need to call it then.

`calibration` asks for logging positions of boxes and markers in the `.xy` file. Without this option, a L^AT_EX run updates the document but not the `.xy` file.

`nowatermark` cancels the "DRAFT" indications above pages.

`catalog` is used for formatting a catalog of questions, not an exam. Then the question identifiers will be printed.

`keys` defines the way the question identifiers will be printed on the catalog file. With `keys=next` (the default), the question identifiers will be printed next to the questions numbers. With `keys=line`, the question identifiers will be printed on one line before the question text, so that the question will look close to the final result on the exam copies.

`francais` asks for french localisation.

`lang=XX` asks for localisation in XX language. At present, only CA (Catalan), DE (German), ES (Spanish), FR (French), IT (Italian), JA (Japanese), NO (Norwegian) and NL (Dutch) are available.

`plain` cancels `environ` and `etex` automatic loading. The default behaviour is to load `environ` and `etex` packages if available, as they improve `automultiplechoice`. This is not done when `plain` option is set.

`nopage` cancels markers print and page layout definition (see sample in section 2.3).

`automarks`, when used with `separateanswersheet`, cancels markers print on the subject page (they are only shown on the answer sheet pages).

`postcorrect` tells that correct answers won't be given in the LaTeX source. The teacher will fill one answer sheet for AMC to analyse the scan and set correct answers from it.

`fullgroups` cancels the use of the optional parameter of `\insertgroup` and `\copygroup`, so that each group is always fully inserted and fully copied.

`storebox` asks to use `\storebox` instead of `\savebox` to handle ovals (when using oval shape). The package `storebox` will be loaded.

`pdfform` use this option to produce PDF forms. The PDF sheet won't be printed, but filled by each student with a PDF reader. The completed PDF will then be sent to the teacher, and given to AMC for data capture.

See also section 3.8 for a french version of some of these options.

3.2 Questions and answers

We make a difference between two kind of multiple choice questions:

- **Simple questions:** there is one and only one correct choices among the proposed choices, *and this is announced to the student*. Thus, the student is asked to check one answer if he thinks this is the good one, and to check none if he has no idea.
- **Multiple questions:** there can be zero, one or several correct choices among the proposed choices. This is also announced to the student (using the `\multiSymbol` sign, with default ♣), so that the student is asked to check all the boxes corresponding to correct choices, and to let unchecked all boxes corresponding to wrong choices.

`question` Simple questions are enclosed in a `{question}{(id)}` environment, and multiple questions are `questionmult` enclosed in a `{questionmult}{(id)}` environment. These environments contain the question text, and the proposed choices inside a `choices`-like environment (see next). The `(id)` argument is a question identifier. Each question must have a unique identifier, different from the other questions identifiers.

```
\begin{question}{everest}
What is the elevation of Mount Everest?
\begin{choices}
\correctchoice{8,848\,m}
\wrongchoice{8,253\,m}
\wrongchoice{8,810\,m}
\end{choices}
\end{question}
```

```
\begin{questionmult}{americas}
Which countries are in the Americas?
\begin{choices}
\correctchoice{Guatemala}
\correctchoice{Canada}
\wrongchoice{Switzerland}
\wrongchoice{Cambodia}
\end{choices}
\end{questionmult}
```

`\AMCcompleteMulti`
`\MCnoCompleteMulti`

For multiple questions, it is sometimes useful to make the difference between a student who thinks that none of the choices are correct, and a student who did not answer the question. The use of package option `completemulti` can be used in this case: it adds a choice to all multiple questions. Commands `\AMCcompleteMulti` and `\MCnoCompleteMulti` can also be used to change this behaviour for a single question.

```
\begin{questionmult}{americas}
\AMCcompleteMulti
Which countries are in the Americas?
\begin{choices}
\correctchoice{Guatemala}
\correctchoice{Canada}
\wrongchoice{Switzerland}
\wrongchoice{Cambodia}
\end{choices}
\end{questionmult}
```

`choices`
`choiceshoriz`
`choicescustom`

Question 1 ♣ What is the elevation of Mount Everest?

- 8,253 m
- 8,810 m
- 8,848 m

Question 2 ♣ Which countries are in the Americas?

- Cambodia
- Guatemala
- Canada
- Switzerland

Question 1 ♣ Which countries are in the Americas?

- Guatemala
- Cambodia
- Canada
- Switzerland
- None of these answers are correct.*

Depending on the formatting style for answers, one can choose one of the following ones:

- Environment `choices` is usually chosen for long answers:

```
\begin{questionmult}{latex}
    What are the possible uses of latex?
\begin{choices}
    \correctchoice{Natural rubber is
        the most important product
        obtained from latex.}
    \correctchoice{Latex from the chicle
        and jelutong trees is used in
        chewing gum.}
    \wrongchoice{Latex is used as a fuel
        for some space launch vehicles.}
\end{choices}
\end{questionmult}
```

- environment `choiceshoriz` is chosen for short answers:

```
\begin{question}{insect}
    From those animals, which
    is an insect?
\begin{choiceshoriz}
    \correctchoice{Ant}
    \wrongchoice{Horse}
    \wrongchoice{Turtle}
\end{choiceshoriz}
\end{question}
```

- environment `choicescustom` is provided to customize answers formatting. See 3.9.3 for details.

`\correctchoice`
`\wrongchoice`

As you have seen in these examples, the `choices`-like environments contain `\correctchoice{<text>}` and `\wrongchoice{<text>}` commands, with the text of the proposed choice as argument.

3.3 Scoring

`\scoring`
`\scoringDefaultM`
`\scoringDefaultS`
`\QuestionIndicative`

Scoring strategies can be given in the L^AT_EX source. They don't have any impact on the question sheet: they are only transmitted to the analysis software through the `.amc` file. See AMC documentation to write proper commands for your needs. `\scoring{<score>}` can be used inside a `question` or `questionmult` environment to describe the scoring strategy for the question, or after a `\correctchoice` or `\wrongchoice` command to describe score associated to a particular choice. `\scoringDefaultM{<score>}` and `\scoringDefaultS{<score>}` define default scoring strategies for multiple and simple questions. `\QuestionIndicative` tags a question that is not taken into account to compute the mark – for example, it can be used for a question about the way students have enjoyed the course.

3.4 Groups of questions

Several commands are available that allows shuffling questions for each question sheet. They handle groups of questions. These groups will usually contain questions, but can be made of any L^AT_EX

Question 1 ♣ What are the possible uses of latex?

- Latex is used as a fuel for some space launch vehicles.
- Latex from the chicle and jelutong trees is used in chewing gum.
- Natural rubber is the most important product obtained from latex.

Question 1 From those animals, which is an insect?

- Horse
- Ant
- Turtle

content.

The command `\element{<groupname>}{<content>}` adds element with content `<content>` to the group named `<groupname>`. The command `\shufflegroup{<groupname>}` shuffles elements of group named `<groupname>`. The command `\insertgroup[<n>]{<groupname>}` inserts elements of group `<groupname>` one after one. If optional parameter `<n>` is given, only the first `<n>` elements of the group are inserted in the document. The command `\insertgroupfrom[<n>]{<groupname>}{<i>}` does the same, starting from element at index `<i>` (the first element has index 0).

As an example without questions in groups elements, consider the following code:

```
\element{serie}{ one}
\element{serie}{ two}
\element{serie}{ three}
\element{serie}{ four}
\element{serie}{ five}
Numbers:\insertgroup{serie}.
```

Three numbers from the second (index=1) one:\insertgroupfrom[3]{serie}{1}.

```
\shufflegroup{serie}
Two of them:\insertgroup[2]{serie}.
```

which produces:

Numbers: one two three four five.
Three numbers from the second (index=1) one: two three four.
Two of them: two four.

The command `\cleargroup{<groupname>}` clears all the elements of group `<groupname>`, making an empty group. The command `\copygroup[<n>]{<from>}{<to>}` copies the elements of group `<from>` to group `<to>` – if optional parameter `<n>` is given, only the `<n>` first elements are copied. The command `\copygroupfrom[<n>]{<from>}{<to>}{<i>}` does the same, starting from element at index `<i>` (the first element has index 0).

As an example again without questions, consider the following code:

```
\element{digits}{ 1}\element{digits}{ 2}\element{digits}{ 3}
\element{digits}{ 4}\element{digits}{ 5}\element{digits}{ 6}
\element{digits}{ 7}\element{digits}{ 8}\element{digits}{ 9}
\element{letters}{ A}\element{letters}{ B}\element{letters}{ C}
\element{letters}{ D}\element{letters}{ E}\element{letters}{ F}

\shufflegroup{letters}
\cleargroup{mixed}
\copygroupfrom[3]{digits}{mixed}{1}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits from 2 to 4 and two letters:\insertgroup{mixed}.

\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
```

```
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.
```

```
\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.
```

which produces:

Three digits from 2 to 4 and two letters: A 2 3 F 4.
 Three digits and two letters: 2 8 4 E D.
 Three digits and two letters: 4 E 2 5 A.

You can find an example involving questions in section 2.

3.5 Students identification

There are two ways to associate students to their sheets.

- Always add to one page of each copy some place for the student to write down his name. If you want AMC software to be able to cut the scan around this area to present it to you and ask you to read the written name (this is called manual association), you must use the `\namefield{\langle descr\rangle}` command. The `\langle descr\rangle` argument contains the L^AT_EX code used to format the name field on the page. For example:

<pre>\namefield{\fbox{ \begin{minipage}{15em} Name and surname:\vspace*{3ex}\par \noindent\dotfill\vspace{2mm} \end{minipage} }}</pre>	Name and surname:
--	-------------------------------------

You can see that the `\namefield` command has no effect on the produced document. In fact, its only purpose is to log in the `.xy` file information about the position of the name field on the page, to be used by the software analysing the scans.

- For automated student identification, if for example students have a 6-digits student number, you can ask them to code it somewhere on the question sheet. This can be done using the `\AMCcodeGridInt[\langle opts\rangle]{\langle key\rangle}{\langle ndigits\rangle}` command, where `\langle key\rangle` is the key identifier, that can be used to retrieve coded student numbers from the scans, and `\langle ndigits\rangle` is the number of digits for numbers to be coded.

```
\AMCcodeGridInt{student}{6}
```

	<input type="text"/>					
	0	0	0	0	0	0
	1	1	1	1	1	1
	2	2	2	2	2	2
	3	3	3	3	3	3
	4	4	4	4	4	4
	5	5	5	5	5	5
	6	6	6	6	6	6
	7	7	7	7	7	7
	8	8	8	8	8	8
	9	9	9	9	9	9

For smaller number of digits, the “horizontal” form can be preferred:

\AMCcodeGridInt[h]{student}{3}		<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9
		<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9
		<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9

3.6 Separate answer sheet

\AMCformBegin
 \AMCform
 MCcleardoublepage

To produce separate answer sheets as seen in section 2.2,

1. use the `separateanswersheet` package option.
2. use the `\AMCformBegin` command at the beginning of the answer sheet description. This command usually follows a command to get a new page. This command can be the classical `\clearpage` for single-sided question sheets, or the `\AMCcleardoublepage` command, that go to the next odd numbered page, so that the answer sheet is on a separate sheet even when printing in duplex mode.
3. use the `\AMCform` command to insert all boxes for all questions.

See section 2.2 for an example.

3.7 Random computation questions

One can use the L^AT_EX package `fp` to make random computation questions, as can be seen in the following example (don’t forget to load package `fp`):

<pre>\begin{question}{simplesum} \FPeval\VQa{trunc(1+random*8,0)} \FPeval\VQb{trunc(4+random*5,0)} \FPeval\VQsum{clip(\VQa+\VQb)} \FPeval\VQnoA{clip(\VQa+\VQb-1)} \FPeval\VQnoB{clip(\VQa*\VQb)} \FPeval\VQnoC{clip(\VQa-\VQb)} How much are \VQa{} plus \VQb{?} \begin{choiceshoriz} \correctchoice{\VQsum} \wrongchoice{\VQnoA} \wrongchoice{\VQnoB} \wrongchoice{\VQnoC} \end{choiceshoriz} \end{question}</pre>	Question 1 How much are 2 plus 8? <input type="checkbox"/> 9 <input checked="" type="checkbox"/> 10 <input type="checkbox"/> 16 <input type="checkbox"/> -6
--	---

In this example, `\VQa` and `\VQb` are used to store two random integers (the first between 1 and 8, and the second between 4 and 8). Then `\VQsum` stores the sum of these two integers, and `\VQnoA`, `\VQnoB` and `\VQnoC` are other values that will be used as distractors in the multiple choice question.

\AMCIntervals
In some cases, command `\AMCIntervals{<x>}{<x0>}{<x1>}{<delta>}` from `automultiplechoice` can be useful. It adds a sequence of choices made of intervals $[x_i, x_i + \delta[$ of length `<delta>` covering the interval $[<x0>, <x1>[$, using `\correctchoice` when `<x>` lies in the interval, and `\wrongchoice` otherwise.

```

\begin{question}{inf-expo-indep}
\FPeval\VQa{trunc(2 + random * 4,0)}
\FPeval\VQb{trunc(6 + random * 5,0)}
\FPeval\VQr{\VQa/(VQa+VQb)}
Let $X$ and $Y$ be two independent random variables, following exponential laws with respective parameters $\VQa{}$ and $\VQb{}$. In which interval lies the probability $\text{P}[X < Y]$?
\begin{multicols}{5}
\begin{reponses}[o]
\AMCIntervals{\VQr}{0}{1}{0.1}
\end{reponses}
\end{multicols}
\end{question}

```

Question 1

Let X and Y be two independent random variables, following exponential laws with respective parameters 5 and 8. In which interval lies the probability $P[X < Y]$?

- | | | | | |
|-------------------------------------|--|-------------------------------------|-------------------------------------|-------------------------------------|
| <input type="checkbox"/> [0, 0.1[| <input type="checkbox"/> [0.2, 0.3[| <input type="checkbox"/> [0.4, 0.5[| <input type="checkbox"/> [0.6, 0.7[| <input type="checkbox"/> [0.8, 0.9[|
| <input type="checkbox"/> [0.1, 0.2[| <input checked="" type="checkbox"/> [0.3, 0.4[| <input type="checkbox"/> [0.5, 0.6[| <input type="checkbox"/> [0.7, 0.8[| <input type="checkbox"/> [0.9, 1[|

`AMCnumericChoices`

One can also use the `\AMCnumericChoices` command to ask the student to enter a numerical value as his answer, as in the following example:

```

\begin{questionmultx}{sqrt}
\FPeval\VQa{trunc(5+random*15,0)}
\FPeval\VQs{\VQa^0.5}

```

Compute $\sqrt{\VQa}$ and round it with two digits after period.

```

\AMCnumericChoices{\VQs}{digits=3,decimals=2,sign=true,
borderwidth=0pt,backgroundcol=lightgray,approx=5}
\end{questionmultx}

```

Question 2

Compute $\sqrt{11}$ and round it up to two digits after period.

<input type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/> 6 <input type="checkbox"/> 7 <input type="checkbox"/> 8 <input type="checkbox"/> 9 .	<input type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/> 6 <input type="checkbox"/> 7 <input type="checkbox"/> 8 <input type="checkbox"/> 9
<input checked="" type="checkbox"/> +	<input type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/> 6 <input type="checkbox"/> 7 <input type="checkbox"/> 8 <input type="checkbox"/> 9
<input type="checkbox"/> -	<input type="checkbox"/> 0 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/> 6 <input type="checkbox"/> 7 <input type="checkbox"/> 8 <input type="checkbox"/> 9

Note the use of `questionmultx` environment: we need this question to be *multiple* as several boxes has to be ticked, but we can't say that *several answers are correct*, so we don't show the ♣.

Available options that can be used in the second argument of the `\AMCnumericChoices` command are the following ($\langle bool \rangle$ can be `true` or `false`, and $\langle color \rangle$ must be a color known by the `xcolor` package):

`digits=⟨num⟩` gives the number of digits to request (defaults to 3).

`decimals=⟨num⟩` gives the number of digits after period to request (defaults to 0). Note that when `decimals` is positive, the LaTeX package `fp` must be loaded.

`base=⟨num⟩` gives the base for digits and decimals (defaults to 10).

`significant=⟨bool⟩` if `true`, the numbers to code are the first *significant* digits from the first argument of `\AMCnumericChoices`. For example, the right answer to `\AMCnumericChoices{56945.23}{digits=2,significant=true}` is 57.

`exponent=⟨num⟩` gives the number of digits for the exponent, when requesting to enter the result in scientific notation.

`nozero=⟨bool⟩` if `true`, the choice 0 is removed for all digits. May be useful when `\AMCnumericChoices` is used to get a small (< 10) positive value.

`sign=⟨bool⟩` requests (or not) a signed value (default to `true`).

`exposign=⟨bool⟩` requests (or not) a signed value of the exponent (default to `true`).

`strict=⟨bool⟩` if `true`, a box has to be ticked for every digit and for the sign. If `false`, if some digits has no ticked box, they will be set to zero. Defaults to `false`.

`vertical=⟨bool⟩` if `true`, each digit is represented on one raw. If `false` (default), each digit is represented on one line.

`expovertical=⟨bool⟩` if `true`, the mantissa is above the exponent. If `false` (default), the mantissa is beside the exponent.

`reverse=⟨bool⟩` if `true`, place higher values of the digits on the top in vertical mode (defaults to `true`).

`vhead=⟨bool⟩` if `true`, in vertical mode, a header is placed over all digits rows, made using the command `\AMCtextVHead` that is originally defined as `\def\AMCtextVHead#1{\emph{b#1}}`. This default value is useful to number the binary digits. Default value is `false`.

`hspcse=⟨space⟩` sets the horizontal space between boxes (defaults to `.5em`).

`vspcse=⟨space⟩` sets the certycal space between boxes (defaults to `1ex`).

`borderwidth=⟨space⟩` sets the width of the frame around all the boxes (defaults to `1mm`).

`bordercol=⟨color⟩` sets the color of the frame (defaults to `lightgray`).

`backgroundcol=⟨color⟩` sets the background color (defaults to `white`).

`Tsign=⟨text⟩` sets the text to print at the top of the boxes to set the sign (Can also be redefined by `\def\AMCtextSign{⟨text⟩}`, and defaults to be empty).

`Tpoint=<text>` sets the text for the period. Can also be redefined by `\def\AMCdecimalPoint{<text>}`, and defaults to `\raisebox{1ex}{\bf .}`.

`Texponent=<text>` sets the text before the exponent. Can also be redefined by `\def\AMCexponent{<text>}`, and defaults to `$\times^{<text>}`.

`scoring=<bool>` if `true`, a scoring strategy is given to AMC for this question. Defaults to `true`.

`scoreexact=<num>` gives the score for an exact answer (defaults to 2).

`exact=<num>` sets the maximal distance to the correct integer value (value without the decimal point) for an answer to be said *exact* and be rewarded to `scoreexact` points (defaults to 0).

`scoreapprox=<num>` gives the score for an approximative answer (defaults to 1).

`approx=<num>` sets the maximal distance to the correct integer value (value without the decimal point) for an answer to be said *approximative* and be rewarded to `scoreapprox` points (defaults to 0).

`scorewrong=<num>` gives the score for a wrong answer (defaults to 0).

`keepas=<name>` keeps the value entered by the student in variable `{<name>}`, for future use with `alsocorrect` in another question.

`alsocorrect=<expression>` gives another acceptable answer, that can be based on the values entered by the student in the previous questions.

The text added at the end of the questions using `\AMCnumericChoices` when not in the separate answer sheet (and when a separate answer sheet is requested by the `separateanswersheet` package option) can also be set redefining the `\AMCnTextGoto` command, as:

```
\def\AMCnTextGoto{\par{\bf\emph{Please code the answer on  
the separate answer sheet.}}}
```

3.8 French command names

For backward compatibility, some of `automultiplechoice` commands, environments and package option have their French counterpart. You can always use either the English command or the French equivalent. See table 1 for details.

3.9 Customisation

3.9.1 Boxes

`\AMCboxStyle` The command `\AMCboxStyle{<style>}` can be used to specify the shape, color and dimensions of the boxes to be ticked. The argument `<style>` is a coma-separated list of `<key>=<value>` pairs, with the following possible `<key>`s:

`shape` for the shape to be used: either `square` or `oval`. Note that if `oval` is used, the L^AT_EX package `tikz` must be loaded.

`width` for the width of the boxes.

type	English	French
command environment	\namefield choices	\champnom reponses
environment	choiceshoriz	reponseshoriz
environment	choicescustom	reponsesperso
command	\correctchoice	\bonne
command	\wrongchoice	\mauvaise
command	\lastchoices	\alafin
command	\AMCIntervals	\choixIntervalles
command	\scoring	\bareme
command	\scoringDefaultM	\baremeDefautM
command	\scoringDefaultS	\baremeDefautS
command environment	\onecopy examcopy	\exemplaire copieexamen
command	\shufflegroup	\melange groupe
command	\insertgroup	\restituegroupe
command	\AMCform	\formulaire
command	\AMCformBegin	\AMCdebutFormulaire
option	noshuffle	ordre
option	answers	correc
option	indivanswers	correcindiv
option	box	bloc
option	separateanswersheet	ensemble
option	digits	chiffres

Table 1: French equivalent commands

`height` for the height of the boxes.

`size` for the size of the boxes (sets `width` and `height`).

`down` for the length the boxes are to be moved down.

`rule` for the rule width.

`outsidesep` for the distance between the box and the letter when printed outside the box.

`color` for the color (only the box that are to be filled by the students and will be used for data capture). Use something that will be understood by the `xcolor` package.

Default values are `\AMCboxStyle{shape=square,size=2.5ex,down=.4ex,rule=.5pt,outsidesep=.1em,color=black}`

Setting the box color allows to print the boxes with some color that won't disturb too much the data capture (for example red, but some light grey can also be considered).

```
\AMCboxStyle{shape=oval,color=red}
\begin{question}{sum} $2+2=\{\}$
\begin{choiceshoriz}[o]
    \wrongchoice{1}\correctchoice{4}\wrongchoice{10}
\end{choiceshoriz}
```

Question 1	2 + 2 =
Ⓐ	1
Ⓑ	4
Ⓒ	10

```
\end{question}
```

3.9.2 Codes

One may adapt the codes rendering from `\AMCcodeGrid` to one's needs modifying the following lengths:

- `\AMCcodeHspace` is the amount of horizontal space between two columns of digits,
- `\AMCcodeVspace` is the amount of vertical space between two rows of digits,

Default values are `\AMCcodeHspace=.5em \AMCcodeVspace=.5em`

3.9.3 Answers

Environment `choicescustom` will make use of the three commands `\AMCbeginAnswer` (before the first answer), `\AMCendAnswer` (after the last answer) and `\AMCanswer{\langle box\rangle}{\langle text\rangle}` (for each answer) to format the answers. Redefining them properly, some different answers formatting can be achieved. However, this does not seem to work with non-trivial settings...

<pre>\begin{question}{add} \def\AMCbeginAnswer{\$\Big(\$} \def\AMCendAnswer{\$\Big)\$} \def\AMCanswer#1#2{\#1 \ #2\hfill} 2+2= \begin{choicescustom} \correctchoice{4} \wrongchoice{2} \wrongchoice{3} \end{choicescustom} \end{question}</pre>	Question 1 $2+2=$ <input type="checkbox"/> 4 <input type="checkbox"/> 3 <input type="checkbox"/> 2 <input type="checkbox"/>
---	--

4 Implementation

This package uses the following other packages:

```

1 \RequirePackage{xcolor} % \fcolorbox to fill (or not) a box
2 \RequirePackage{fancyhdr} % \pagestyle{empty}
3 \RequirePackage{bophook} % \AtBeginPage
4 \RequirePackage{xkeyval} % \setkeys
5 \RequirePackage{rotating} % \rotatebox
6 \RequirePackage{fancybox} % \boxput
7 \RequirePackage{expl3}
8 \RequirePackage{csvsimple}
9 \RequirePackage{environ}
10 \% \end{macrocode}
11 %
12 \% First, we read the options that can be given by AMC through the
13 \% |jobname-config.tex| file:
14 \% \begin{macrocode}
```

```

15 \InputIfFileExists{\jobname-config.tex}%
16 {\message{Loading configuration file...^^J}}{}}

\AMC@amclog Informations about questions and choices will be logged to a file with extension amc, to be parsed
\AMCmessage later. Macro \AMC@amclog writes to this file.

17 \newwrite\AMC@logfile
18 \immediate\openout\AMC@logfile=\jobname.amc
19 \def\AMC@amclog#1{\immediate\write\AMC@logfile{#1}}
20 \def\AMCmessage#1{\AMC@amclog{AUTOQCM[#1]^^J}}

```

`\AMC@LR` Colours management can be faulty in right-to-left mode: in these situations, we will make use of `\LR` from package `bidi` to get back to left-to-right mode. `\AMC@LR` is `\LR` if `bidi` is loaded.

```

21 \AtBeginDocument{@ifpackageloaded{bidi}{%
22   \PackageInfo{automultiplechoice}{Package bidi loaded: using LR for boxes.}%
23   \let\AMC@LR=\LR}%
24 \let\AMC@LR=\relax}%

```

4.1 Variables

Counters and boolean variables defined here are internal and should not be modified by the user.

The package defines the following counters:

```

\AMCload@counter number of choices already loaded for current question.

\AMCid@quest current question ID number (see section 4.7).

\AMCid@etud current student sheet number.

\AMCid@etudstart starting student sheet number of the current oncopy bloc.

\AMCid@check current page checking number.

\AMCid@etudfin last student sheet number for the exam.

\AMCnum@copies number of exam sheets to produce.

```

It also defines the following switches:

```

\ifAMC@ordre if choices are never to be shuffled.

\ifAMC@shuffleG if groups shuffling is allowed.

\ifAMC@fullGroups if groups are always fully inserted by \insertgroup and fully copied by
\copygroup, irrespective to the optional parameter.

\ifAMC@correchead if some correction header is to be printed at the beginning.

\ifAMC@affichekeys if questions keys are to be printed.

\ifAMC@keysline if questions keys should be printed on a single line before the question text.

\ifAMC@correc if correct choices are to be checked on the produced document.

```

\ifAMC@qbloc if questions are to be included in L^AT_EX boxes (so that they can't be splitted on two different pages).

\ifAMC@asqbloc if questions are to be included in L^AT_EX boxes in the answer sheet (so that they can't be splitted on two different pages).

\ifAMC@rbloc if answers are to be included in L^AT_EX boxes (so that they can't be splitted on two different columns for example).

\ifAMC@textPos if questions and answers positions are to be logged.

\ifAMC@extractOnly if the PDF is only built to extract questions and answers images.

\ifAMCcomplete@multi if a choice "None of these answers are correct." is to be added to every multiple question.

\ifAMCquestionNumber if AMC should step up the question number for each new question.

\ifAMC@calibration if this L^AT_EX run is used to get page layouts.

\ifAMC@plain if automultiplechoice won't try to load useful packages (`etex`, `environ`) that extend automultiplechoice capabilities.

\ifAMCune@bonne if there is at least one correct answer for the current question.

\ifAMCtype@multi if the current question is a multiple question.

\ifAMC@watermark if the document is a draft, not to be used for exam.

\ifAMC@ensemble if answers are to be given on a separate answers sheet.

\ifAMC@inside@box if a letter or digit is to be printed inside all boxes.

\ifAMC@inside@digit if digits are to be written inside boxes instead of letters (when using a separate answer sheet for example).

\ifAMC@outside@box if labels for boxes are to be printed outside the box on the answer sheet.

\ifAMCformulaire@dedans is true for questions inside separate answer sheet.

\ifAMC@zoneformulaire is true for codes (made by \AMCcodeGrid) inside separate answer sheet.

\ifAMC@pagelayout is true if the AMC page layout, with signs for scan analysis, is to be used.

\ifAMC@postcorrect corresponds to the use of the `postcorrect` package option.

\ifAMC@automarks corresponds to the use of the `automarks` package option.

\ifAMC@invisible is true if the DVI/PDF output is not important (used for example for scoring strategy extraction).

\ifAMC@pdfform is true if the output is a PDF form. This PDF will not be printed but will be filled by the students with a PDF reader and sent back to the teacher.

```

25 \newcount\AMCload@counter
26 \newcount\AMCid@quest\AMCid@quest=-1
27 \newcount\AMCid@check
28 \newcount\AMCid@etud\AMCid@etud=0
29 \newcount\AMCid@etudstart\AMCid@etudstart=0
30 \newcount\AMCid@etudfin
31 \newcount\AMCnum@copies

32 \newif\ifAMC@ordre\AMC@ordrefalse
33 \newif\ifAMC@shuffleG\AMC@shuffleGtrue
34 \newif\ifAMC@fullGroups\AMC@fullGroupsfalse
35 \newif\ifAMC@correchead\AMC@correcheadfalse
36 \newif\ifAMC@affichekeys\AMC@affichekeysfalse
37 \newif\ifAMC@keysline\AMC@keyslinefalse
38 \newif\ifAMC@correc\AMC@correcfalse
39 \newif\ifAMC@textPos\AMC@textPosfalse
40 \newif\ifAMC@extractOnly\AMC@extractOnlyfalse
41 \newif\ifAMC@qbloc\AMC@qblocfalse
42 \newif\ifAMC@asqbloc\AMC@asqblocfalse
43 \newif\ifAMC@rbloc\AMC@rblocfalse
44 \newif\ifAMCcomplete@multi\AMCcomplete@multifalse
45 \newif\ifAMCquestionNumber\AMCquestionNumbertrue
46 \newif\ifAMC@calibration\AMC@calibrationfalse
47 \newif\ifAMC@catalog\AMC@catalogfalse
48 \newif\ifAMC@plain\AMC@plainfalse
49 \newif\ifAMCune@bonne
50 \newif\ifAMCtype@multi
51 \newif\ifAMC@watermark\AMC@watermarktrue
52 \newif\ifAMC@inside@box\AMC@inside@boxfalse
53 \newif\ifAMC@outside@box\AMC@outside@boxfalse
54 \newif\ifAMC@ensemble\AMC@ensemblefalse
55 \newif\ifAMC@inside@digit\AMC@inside@digitfalse
56 \newif\ifAMCformulaire@dedans\AMCformulaire@dedansfalse
57 \newif\ifAMC@zoneformulaire
58 \newif\ifAMC@pagelayout\AMC@pagelayouttrue
59 \newif\ifAMC@postcorrect\AMC@postcorrectfalse
60 \newif\ifAMC@automarks\AMC@automarksfalse
61 \newif\ifAMC@invisible\AMC@invisiblefalse
62 \newif\ifAMC@pdfform\AMC@pdfformfalse
63 \let\AMCcompleteMulti=\AMCcomplete@multittrue
64 \let\AMCnoCompleteMulti=\AMCcomplete@multifalse

```

\AMCid@name The package also defines command \AMCid@name to be the current question identifier key.
65 \def\AMCid@name{}

4.2 Dimensions

\AMCformVSpace The following dimensions can be modified by the user to adjust questions formatting:
\AMCformHSpace \AMCformVSpace is the amount of vertical space between two questions in a separate answer sheet.
\AMCinterIrep
\AMCinterBrep

`\AMCformHSpace` is the amount of horizontal space between two answers boxes in a separate answer sheet.

`\AMCinterIrep` is the amount of vertical space to be added between two answers.

`\AMCinterBrep` is the amount of vertical space between two boxed answers (see `\AMCboxedAnswers` and `\ifAMC@rbloc`).

`\AMCinterIquest` is the amount of vertical space left after a question, in standard mode (without package option `box`).

`\AMCinterBquest` is the amount of vertical space left after a question, in 'boxed' mode (with package option `box`).

`\AMCpost0quest` is the amount of vertical space left after an open question.

```
66 \newdimen\AMCformVSpace\AMCformVSpace=1.2ex
67 \newdimen\AMCformHSpace\AMCformHSpace=.3em
68 \newdimen\AMCinterIrep\AMCinterIrep=\z@
69 \newdimen\AMCinterBrep\AMCinterBrep=.5ex
70 \newdimen\AMCinterIquest\AMCinterIquest=\z@
71 \newdimen\AMCinterBquest\AMCinterBquest=3ex
72 \newdimen\AMCpost0quest\AMCpost0quest=7mm
```

4.3 Human readable sheet ID position

`\AMCidsPosition` The position of the human readable sheet ID, near the corresponding binary boxes, is set with the `\AMCidsPosition` command, in the form `\AMCidsPosition{pos=<position>, width=<width>, height=<height>}`, where `<position>` is one of `side` (default), `top` and `none`, `<width>` is the width of the box enclosing the ID (default value is `4cm`), and `<height>` is the height of the box enclosing the ID (default value is `3ex`).

```
73 \newif\ifAMCids@top
74 \newif\ifAMCids@side
75 \newdimen\AMCids@width
76 \newdimen\AMCids@height
77 \define@choicekey*{\AMCids}{pos}[\AMCidsVar\AMCidsVarN]{none,top,side}{%
78   \ifcase\AMCidsVarN\relax
79     \AMCids@topfalse\AMCids@sidefalse
80   \or
81     \AMCids@toptrue\AMCids@sidefalse
82   \or
83     \AMCids@topfalse\AMCids@sidetrue
84   \fi
85 }
86 \define@key{\AMCids}{width}{\AMCids@width=#1}
87 \define@key{\AMCids}{height}{\AMCids@height=#1}
88 \def\AMCidsPosition#1{\setkeys{\AMCids}{#1}}
89 \AMCidsPosition{pos=side,width=4cm,height=3ex}
```

4.4 Localisation

In this section, some localised strings or commands are defined, for English, French and Spanish languages.

\AMCtext To modify these texts, you can use command \AMCtext. For example, \AMCtext{draft}{<text>} sets the text to be printed behind each page of a draft exam.

```
90 \def\AMCtext#1#2{\expandafter\def\csname AMC@loc@#1\endcsname{#2}}
91 \def\AMClocalized#1{\csname AMC@loc@#1\endcsname}
```

4.4.1 English

Text indicating draft exams:

```
92 \def\AMC@loc@draft{DRAFT}
```

Message at page bottom when compiled out of AMC gui:

```
93 \def\AMC@loc@message{For your examination, preferably print
94   documents compiled from auto-multiple-choice.}
```

Announcing a question in a separate sheet (parameter #1 is the question number):

```
95 \def\AMC@loc@qf#1{\textbf{Question #1:}}
```

Announcing a question (parameter #1 is the question number and parameter #2 can be the multiple choice symbol, or be empty):

```
96 \def\AMC@loc@q#1#2{\textbf{Question #1} #2}
```

Headers for corrected version and catalog:

```
97 \def\AMC@loc@corrected{Corrected}
98 \def\AMC@loc@catalog{Catalog}
```

Localization text for Explanation

```
99 \def\AMC@loc@explain{\textit{\textbf{Explanation:}}}
```

Last choice added at the end for multiple questions when option completemulti is used:

```
100 \def\AMC@loc@none{None of these answers are correct.}
```

Word for 'question', singular and plural forms:

```
101 \def\AMC@loc@question{question}
102 \def\AMC@loc@questions{questions}
```

Default text to write in the students' name box:

```
103 \def\AMC@loc@namesurname{Name and surname:}
```

4.4.2 Catalan

Catalan localisation is called with option lang=CA.

```
104 \def\AMC@loc@CA{
105   \def\AMC@loc@draft{PROJECTE}
106   \def\AMC@loc@message{Pel vostre examen, imprimiu preferiblement
107     els documents compilats amb l'ajuda de auto-multiple-choice.}
108   \def\AMC@loc@qf#1{\textbf{Pregunta ##1 :}}
109   \def\AMC@loc@q##1##2{\textbf{Pregunta ##1} ##2}
110   \def\AMC@loc@corrected{Correcció}
```

```

111 \def\AMC@loc@catalog{Cat`aleg}
112 \def\AMC@loc@explain{\textit{\textbf{Explicaci\'o : }}}
```

```
113 \def\AMC@loc@none{Cap de les respistes \'es correcte.}
```

```
114 \def\AMC@loc@question{pregunta}
```

```
115 \def\AMC@loc@questions{preguntes}
```

```
116 \def\AMC@loc@namesurname{Nom i cognoms:}
```

```
117 }
```

4.4.3 Dutch

Dutch localisation is called with option `lang=NL`.

```

118 \def\AMC@loc@NL{
119   \def\AMC@loc@draft{Ontwerp}
120   \def\AMC@loc@message{Gebruik bij uw proefwerk bij voorkeur die
121     documenten welke door auto-multiple-choice zijn aangemaakt.}
122   \def\AMC@loc@qf##1{\textbf{Vraag ##1 :}}
123   \def\AMC@loc@q##1##2{\textbf{Vraag ##1} ##2}
124   \def\AMC@loc@corrected{Correctie}
125   \def\AMC@loc@catalog{Catalogus}
126   \def\AMC@loc@none{Geen van de antwoorden is juist.}
127   \def\AMC@loc@question{vraag}
128   \def\AMC@loc@questions{vragen}
129   \def\AMC@loc@namesurname{Achternaam en voornaam:}
130 }
```

4.4.4 French

French localisation is called with option `francais`, or `lang=FR`.

```

131 \def\AMC@loc@FR{
132   \def\AMC@loc@draft{PROJET}
133   \def\AMC@loc@message{Pour votre examen, imprimez de pr\'ef\'erence
134     les documents compil\'es \'a l'aide de auto-multiple-choice.}
135   \def\AMC@loc@qf##1{\textbf{Question ##1 :}}
136   \def\AMC@loc@q##1##2{\textbf{Question ##1} ##2}
137   \def\AMC@loc@corrected{Correction}
138   \def\AMC@loc@catalog{Catalogue}
139   \def\AMC@loc@explain{\textit{\textbf{Explication : }}}
```

```
140   \def\AMC@loc@none{Aucune de ces r\'eponses n'est correcte.}
```

```
141   \def\AMC@loc@question{question}
```

```
142   \def\AMC@loc@questions{questions}
```

```
143   \def\AMC@loc@namesurname{Nom et pr\'énom :}
```

```
144 }
```

4.4.5 German

German localisation is called with option `lang=DE`.

```

145 \def\AMC@loc@DE{
146   \def\AMC@loc@draft{ENTWURF}
147   \def\AMC@loc@message{Benutzen Sie f\"ur Ihre Pr\"ufung bevorzugt Dokumente die mit
```

```

148     auto-multiple-choice erstellt wurden.}
149 \def\AMC@loc@qf##1{\textbf{Frage ##1 :}}
150 \def\AMC@loc@q##1##2{\textbf{Frage ##1} ##2}
151 \def\AMC@loc@corrected{Korrektur}
152 \def\AMC@loc@catalog{Katalog}
153 \def\AMC@loc@explain{\textit{\textbf{Erkl\"arung :}}}}
154 \def\AMC@loc@none{Keine dieser Antworten ist korrekt.}
155 \def\AMC@loc@question{Frage}
156 \def\AMC@loc@questions{Fragen}
157 \def\AMC@loc@namesurname{Vor- und Nachname:}
158 }

```

4.4.6 Italian

Italian localisation is called with option `lang=IT`.

```

159 \def\AMC@loc@IT{
160   \def\AMC@loc@draft{BOZZA}
161   \def\AMC@loc@message{Per l'esame, \`e preferibile stampare i documenti
162     a partire da auto-multiple-choice.}
163   \def\AMC@loc@qf##1{\textbf{Domanda ##1 :}}
164   \def\AMC@loc@q##1##2{\textbf{Domanda ##1} ##2}
165   \def\AMC@loc@corrected{Correzione}
166   \def\AMC@loc@catalog{Catalogo}
167   \def\AMC@loc@none{Nessuna risposta \`e giusta.}
168   \def\AMC@loc@question{domanda}
169   \def\AMC@loc@questions{domande}
170   \def\AMC@loc@namesurname{Nome e cognome:}
171 }

```

4.4.7 Norwegian

Norwegian localisation is called with option `lang=NO`.

```

172 \def\AMC@loc@NO{
173   \def\AMC@loc@draft{UTKAST}
174   \def\AMC@loc@message{Det anbefales {\aa} skrive ut dokumentet
175     for gjennomgang \ direkt fra auto-multiple-choice.}
176   \def\AMC@loc@qf##1{\textbf{Oppgave ##1 :}}
177   \def\AMC@loc@q##1##2{\textbf{Oppgave ##1} ##2}
178   \def\AMC@loc@corrected{Rettet}
179   \def\AMC@loc@catalog{Katalog}
180   \def\AMC@loc@none{Ingen svar er riktige.}
181   \def\AMC@loc@question{oppgave}
182   \def\AMC@loc@questions{oppgave}
183   \def\AMC@loc@namesurname{Etternavn og fornavn:}
184 }

```

4.4.8 Portuguese

Portuguese localisation is called with option `lang=PT`.

```
185 \def\AMC@loc@PT{  
186   \def\AMC@loc@draft{RASCUNHO}  
187   \def\AMC@loc@message{Para o seu exame, use preferencialmente documentos compilados do auto-multiple-choice}  
188   \def\AMC@loc@qf##1{\textbf{Quest\~ao ##1:}}  
189   \def\AMC@loc@q##1##2{\textbf{Quest\~ao ##1} ##2}  
190   \def\AMC@loc@corrected{Corrigido}  
191   \def\AMC@loc@catalog{Cat\'alogo}  
192   \def\AMC@loc@explain{\textit{\textbf{Justifique: }}}  
193   \def\AMC@loc@none{Nenhuma das respostas apresentadas est\'a correta.}  
194   \def\AMC@loc@question{Quest\~ao}  
195   \def\AMC@loc@questions{Quest\~oes}  
196   \def\AMC@loc@namesurname{Nome e apelido:}  
197 }
```

4.4.9 Spanish

Spanish localisation is called with option lang=ES.

```
198 \def\AMC@loc@ES{  
199   \def\AMC@loc@draft{BORRADOR}  
200   \def\AMC@loc@message{Para revisi\'on, preferentemente imprimir documentos compilados  
201     desde auto-multiple-choice.}  
202   \def\AMC@loc@qf##1{\textbf{Pregunta ##1 :}}  
203   \def\AMC@loc@q##1##2{\textbf{Pregunta ##1} ##2}  
204   \def\AMC@loc@corrected{Correcci\'on}  
205   \def\AMC@loc@catalog{Cat\'alogo}  
206   \def\AMC@loc@none{Ninguna de estas preguntas son correctas.}  
207   \def\AMC@loc@question{pregunta}  
208   \def\AMC@loc@questions{preguntas}  
209   \def\AMC@loc@namesurname{Nombre y apellidos:}  
210 }
```

4.4.10 Japanese

Japanese localisation is called with option `lang=JA`. It includes UTF8 encoded Japanese characters which are shown as ◊ here (look at the `.sty` file to see them).

4.4.11 Other languages

Other languages can be integrated to `automultiplechoice` package upon request to the author.

4.5 Interaction with other packages

4.5.1 cleveref

For references to questions:

```
223 \AtBeginDocument{\@ifpackageloaded{cleveref}{%
224     \message{AMC/cleveref integration loaded^^J}%
225     \crefalias{AMCquestionaff}{question}%
226     \crefname{question}{\AMC@loc@question}{\AMC@loc@questions}%
227 }{}%
```

4.6 Random

4.6.1 Random pseudo-generator

The package uses the pseudo-random bit generator from *TuGBoat* 1994, vol 15:1:

```
228 \ifx\AMC@SR\undefined\newcount\AMC@SR\fi
229 \providecommand\AMC@SRconst{2097152}
230 \providecommand\AMC@SRset[1]{\global\AMC@SR#1 \ignorespaces}
231 \providecommand\AMC@SRadvance{%
232     \begingroup%
233     \ifnum\AMC@SR<\AMC@SRconst\relax\AMC@SR@count\z@\else\AMC@SR@count\@ne\fi%
234     \ifodd\AMC@SR\advance\AMC@SR@count\@ne\fi%
235     \global\divide\AMC@SR\@tw@%
236     \ifodd\AMC@SR@count\global\advance\AMC@SR\AMC@SRconst\relax\fi%
237     \endgroup}
238 \providecommand\AMC@SRbit{\AMC@SRadvance\ifodd\AMC@SR1\else0\fi}
239 \providecommand\AMC@SRtest[2]{\AMC@SRadvance%
240     \ifodd\AMC@SR#2\else#1\fi\ignorespaces}
241 \providecommand\AMC@SRvalue{\number\AMC@SR}
```

\AMCrandomseed The seed of this generator is set to 1515, but another value can be given using the command `\AMCrandomseed{<seed>}`.

```
242 \AMC@SRset{1515}
243 \def\AMCrandomseed#1{\AMC@SRset{#1}}
```

4.6.2 Uniform random deviates

\AMC@SRnextByte This generator is used to build first a 20-bit uniform integer generator (macro `\AMC@SRnextByte`). Then, using modulo, a (nearly) uniform generator on $\{0, \dots, n-1\}$ is built: command `\AMC@SRmax{n}` puts in `\AMC@SR@count` the random deviate.

```
244 \newcount\AMC@SR@count
245 \def\AMC@SR@time{\AMC@SRset{\time}}
246 \newcount\AMC@SRnum
247 \def\AMC@SRnextByte{\AMC@SRnum=\z@%
248     \AMC@SR@count=20%
```

```

249 \loop\multiply\AMC@SRnum\tw@%
250   \AMC@SRtest{\advance\AMC@SRnum\@ne}{\@ne}%
251 \ifnum\AMC@SR@count>\@ne\advance\AMC@SR@count\m@ne\repeat%
252 }
253 \newcommand\AMC@SRmax[1]{\AMC@SRnextByte%
254   \AMC@SR@count=\AMC@SRnum%
255   \divide\AMC@SR@count by #1\relax%
256   \multiply\AMC@SR@count by #1\relax%
257   \advance\AMC@SRnum by -\AMC@SR@count%
258 }

```

4.6.3 Tokens shuffling

`\AMCsw@p` The package defines the macro `\AMCsw@p` to swap the values of two token registers given as parameters.

`\AMC@shuffletoks` After defining n token registers `\foo@i`, `\foo@ii`, `\foo@iii`, `\foo@iv` and so on, you can shuffle them using `\AMC@shuffletoks[⟨a⟩]{⟨n⟩}{⟨foo⟩}`. With optional argument `⟨a⟩`, registers are shuffled from number `⟨a⟩` to `⟨n⟩` (default value for `⟨a⟩` is 1).

```

259 \newcount\AMC@sti
260 \newcount\AMC@stil
261 \newtoks\AMCsw@p@%
262 \newcommand\AMCsw@p[2]{%
263   \global\AMCsw@p@=#1%
264   \global#1=#2%
265   \global#2=\AMCsw@p@}
266 \newcommand{\AMC@shuffletoks}[3][\@ne]{%
267   \AMC@sti=#2\relax%
268   \AMC@stil=#2\relax%
269   \advance\AMC@stil\@ne%
270   \advance\AMC@stil -#1\relax%
271   \@whilenum\AMC@sti>#1\do{%
272     \AMC@SRmax{\AMC@stil}\advance\AMC@SRnum #1\relax%
273     \AMCsw@p{\csname #3\romannumeral\AMC@SRnum\endcsname}%
274       {\csname #3\romannumeral\AMC@sti\endcsname}%
275     \advance\AMC@sti\m@ne\relax%
276     \advance\AMC@stil\m@ne\relax%
277   }%

```

4.7 Keys numbering

`\AMC@unnumero` This package allocates a unique integer ID to each question key from the questionnaire. The counter `\AMC@numerotation` keeps track of the number of keys which already had an ID. Command `\AMC@definitnumero{ n }{key}` allocates ID n to the key `key`. Command `\AMC@prepare{key}` looks if an ID had already been associated to `key`, and, if not, makes a new ID allocation for `key`. Command `\AMC@unnumero{key}` returns the ID associated with `key` (creating one if necessary). Command `\AMC@affecte{key}{{cnt}}` give to counter `\cnt` the value of the ID associated to `key` (creating one if necessary).

```

278 \newcount\AMC@numerotation\AMC@numerotation=\z@%
279 \def\AMC@definitnumero#1#2{\AMC@amclog{AUTOQCM[NUM=#1=#2] ^~ J}}%

```

```

280 \expandafter\global\expandafter\def\csname AMC@numtab@#2\endcsname{#1}%
281 \def\AMC@prepare#1{\expandafter\ifx\csname AMC@numtab@#1\endcsname\relax%
282 \global\advance\AMC@numerotation\@ne%
283 \expandafter\AMC@definitnumero\expandafter{\the\AMC@numerotation}{#1}\fi}%
284 \def\AMC@unnumero#1{\AMC@prepare{#1}\csname AMC@numtab@#1\endcsname}%
285 \def\AMC@affecte#1#2{\AMC@prepare{#1}\global#2=\csname AMC@numtab@#1\endcsname}%

```

4.8 Boxes

4.8.1 Character logging

\AMC@logchar The command `\AMC@logchar{<char>}{{<key>}}` logs the character written in the box referenced as `<key>` in the .cs file. This is used in catalog mode, to get understandable references to answers from the statistics tables of the ODS export.

```

286 \def\AMC@logchar#1#2{%
287 \protected@write\AMC@CSFILE{}{%
288 \string\answer{%
289 {\the\AMCid@etud/\thepage:#2}%
290 {#1}}%
291 }%

```

4.8.2 Position logging

\AMC@tracebox \AMC@pagepos Command `\AMC@tracebox{<trace>}{{<key>}}{{<content>}}` makes a L^AT_EX box around `<content>`, and, if `<trace>` is not empty, logs to the .xy file informations to be able to compute exact location of this box on the page, attached to the box identification `<key>`.

Command `\AMC@pagepos` logs page and page size informations at the beginning of each page.

```

292 \def\AMC@shapename@{\ifAMC@invisible none\else\AMC@shapename\fi}%
293 \def\AMC@tracepos#1#2{%
294 \ifAMC@calibration\ifx\empty\empty\empty\else%
295 \pdfsavepos\protected@write\AMC@XYFILE{}{%
296 \string\tracepos{%
297 {\the\AMCid@etud/\thepage:#2}%
298 {\noexpand\number\pdflastxpos sp}%
299 {\noexpand\number\pdflastypos sp}%
300 {\AMC@shapename}}%
301 \fi\fi}%
302 \def\AMC@traceposx#1#2{%
303 \ifAMC@calibration\ifx\empty\empty\empty\else%
304 \pdfsavepos\protected@write\AMC@XYFILE{}{%
305 \string\tracepos{%
306 {\the\AMCid@etud/\thepage:#2}%
307 {\noexpand\number\pdflastxpos sp}%
308 {0sp}%
309 {\AMC@shapename}}%
310 \fi\fi}%
311 \def\AMC@traceposy#1#2{%
312 \ifAMC@calibration\ifx\empty\empty\empty\else%
313 \pdfsavepos\protected@write\AMC@XYFILE{}{%

```

```

314   \string\tracepos%
315   {\the\AMC@etud/\thepage:#2}%
316   {0sp}%
317   {\noexpand\number\pdflastypos sp}%
318   {\AMC@shapename}}%
319 \fi\fi}
320 \newcommand\AMC@tracebox[3]{%
321   \vbox{\AMC@traceposy{#1}{#2}%
322     \hbox{\AMC@traceposx{#1}{#2}\#3\AMC@traceposx{#1}{#2}}}%
323   \AMC@traceposy{#1}{#2}}%
324 \def\AMC@pagepos{%
325   \ifAMC@calibration\protected@write\AMC@XYFILE{}{%
326     \string\page%
327     {\the\AMC@etud/\thepage/\the\AMC@check}%
328     {\the\paperwidth}{\the\paperheight}}\fi}

```

\AMCdontScan The commands `\AMCdontScan` and `\AMCdontAnnotate` write into the `.xy` file instructions related to the current question.

```

329 \newcommand{\AMCdontScan}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\dontscan{\the\AMC@etud,\thepage}}%
330 \newcommand{\AMCdontAnnotate}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\dontannotate{\the\AMC@etud,\thepage}}%
331 %

```

\AMC@tracechar The macro `\AMC@tracechar{<char>}{<unused>}{<trace>}{<key>}` is used to log (for further processing with AMC), into to `.xy` file, the character used to identify the box.

```

332 \newcommand\AMC@tracechar[4]{%
333   \ifAMC@calibration\ifx\@empty#3\@empty\else%
334     \protected@write\AMC@XYFILE{}{%
335       \string\boxchar{\the\AMC@etud/\thepage:#4}{#1}}%
336     }%
337   \fi\fi%
338 }

```

amcxyfile The following lines defines an environment to use a particular file for positions outputs. This is used mainly for documentation or testing.

```

339 \newwrite\AMC@XYspecial
340 \newwrite\AMC@tmpXY
341 \newenvironment{amcxyfile}[1]{%
342   \openout\AMC@XYspecial#1%
343   \let\AMC@tmpXY=\AMC@XYFILE%
344   \let\AMC@XYFILE=\AMC@XYspecial%
345 }{\let\AMC@XYFILE=\AMC@tmpXY\closeout\AMC@XYspecial}

```

\namefield The `\namefield{<name field content>}` is a simple call to `\AMC@tracebox`:

```

346 \newcommand{\namefield}[1]{\AMC@tracebox{1}{nom}{#1}}

```

It is used to enclose the page region where students are to write their names, so as to retrieve it easily from the scans.

\namefielddots The command \namefielddots can be used to fill a line with dots (printed sheets) or use a text field in PDF forms:

```
347 \newcommand{\namefielddots}{%
348   \noindent%
349   \ifAMC@pdfform%
350     \hspace*{\fill}%
351     \TextField[name={\the\AMCid@etud:namefield},width=.95\linewidth,bordercolor=0 0 0]{}
352     \hspace*{\fill}%
353   \else%
354     \dotfill%
355   \fi%
356 }
```

As an example,

```
\namefield{\fbox{%
\begin{minipage}{5cm}
Name:

\vspace{.5cm}
\namefielddots
\vspace{2mm}
\end{minipage}}}
```

produces the following box:

and outputs information about the position of the box in the .xy file, as seen in section 5.1.

4.8.3 Boxes to be checked by students

\AMC@answerBox@ There are two styles for boxes to be checked by the students. The first one is an empty box, printed beside the answer. The second is a box with a character in it. It is mainly used when answers are to be given on a separate answer sheet.

These boxes can be drawn using command \AMC@answerBox@{<char>}{{<answer>}}{<trace>}{<key>}: <char> is the character to print inside the box, <trace> is non-empty if you want to log the box position in the .xy file, <key> is the box identification, and <answer> is an answer to be written in the box (or \AMC@checkbox for filling the box).

Depending on the required shape for the boxes, the corresponding

```
\AMC@shape@xxx{<char>}{{<answer>}}{<trace>}{<key>}
```

command is used.

- \AMC@answerBox@{K}{}{1}{test} produce the box K, writing the lines in the .xy file shown in section 5.2.

- `\AMC@answerBox@{K}{\AMC@checkbox}{}{}` produces 
- `\AMC@answerBox@{}{8}{}{}` produces 
- `\AMC@answerBox@{K}{8}{1}{testb}` produces  with `\AMCboxStyle{shape=oval,color=red}`

```

357 \def\AMC@checkbox{}
358 \let\AMC@new@savebox=\newsavebox
359 \let\AMC@save@box=\savebox
360 \let\AMC@use@box=\usebox
361 \newif\ifAMC@draw@cross

```

The `\AMC@smashcentered{<text>}` command shows the `<text>` centered at point.

```

362 \newbox\AMC@smashbox
363 \newdimen\AMC@smashboxheight
364 \newcommand{\AMC@smashcentered}[1]{%
365   \setbox\AMC@smashbox\hbox{\#1}%
366   \AMC@smashboxheight=\ht\AMC@smashbox%
367   \advance\AMC@smashboxheight by \dp\AMC@smashbox%
368   \vfuzz=\AMC@smashboxheight\hfuzz=\wd\AMC@smashbox%
369   \hspace*{-.5\wd\AMC@smashbox}\hbox to .5\wd\AMC@smashbox{%
370     \vbox to \Opt{%
371       \vspace*{-.5\AMC@smashboxheight}\vbox to .5\AMC@smashboxheight{%
372         \box\AMC@smashbox}}}}%
373 }

```

`\AMC@setcolors@{<trace>}-{<answer>}` sets colours `\AMC@boxcolor@` and `\AMC@fillcolor@` according to its arguments. It also sets the `\ifAMC@draw@cross` switch if AMC should draw a cross instead of filling the box.

```

374 \newcommand\AMC@setcolors@[2]{%
375   \def\AMC@boxcolor@{\AMC@boxcolor}%
376   \ifx\empty#1\empty \def\AMC@boxcolor@{black}\fi%
377   \ifAMC@correc\def\AMC@boxcolor@{black}\fi%
378   \def\AMC@fillcolor@{\ifx #2\AMC@checkbox{%
379     \AMC@boxcolor@\else white\fi}%
380   \AMC@draw@crossfalse%
381   \ifKV@AMCdim@cross\ifx #2\AMC@checkbox{%
382     \AMC@draw@crosstrue\fi\fi%
383 }%
384 \newcommand\AMC@answerBox@[4]{%
385   \ifAMC@catalog%
386     \AMC@logchar{\#1}{\#4}%
387   \fi%
388   \AMC@LR{\hspace{\Opt{%
389     \lower\AMC@boxeddown\hbox{\csname \AMC@shape@\AMC@shapename@\endcsname%
390     {\AMCchoiceLabelFormat{\#1}{\#2}{\#3}{\#4}}}}}}%
391 }%
392 \newcommand\AMC@shapeprepare@square{}%
393 \newcommand\AMC@shape@square[4]{%
394   \fboxsep=\z@\fboxrule=\AMC@boxedrule%
395   \AMC@setcolors@{\#3}{\#2}%

```

```

396 \ifKV@AMCdim@cross\def\AMC@fillcolor@{white}\fi%
397 \fcolorbox{\AMC@boxcolor@}{\AMC@fillcolor@}%
398 {%
399   \boxput*(0,0){%
400     \ifAMC@draw@cross\AMC@crosschar\fi%
401   }{%
402     \vbox to \AMC@boxedheight{%
403       \AMC@tracepos{#3}{#4}%
404       \vfill%
405       \hbox to \AMC@boxedwidth{\hfill%
406         \AMC@smashcentered{\textcolor{\AMC@boxcolor@}{#1}}%
407         \AMC@smashcentered{#2}%
408         \hfill}\vfill}%
409     \AMC@tracepos{#3}{#4}%
410   }%
411 \AMC@makeovalbox{\langle trace\rangle}{\langle answer\rangle}{\langle box\rangle} prepares an oval frame in the LATEX box box.%
412 \newcommand\AMC@makeovalbox[3]{%
413   \AMC@setcolors@{#1}{#2}%
414   \ifKV@AMCdim@cross\def\AMC@fillcolor@{white}\fi%
415   \AMC@save@box{#3}{%
416     \begin{tikzpicture}%
417       \useasboundingbox (-0.5\AMC@boxedwidth-0.5\AMC@boxedrule,0.5\AMC@boxedheight+0.5\AMC@boxedrule) rectangle (0.5\AMC@boxedwidth+0.5\AMC@boxedrule,-0.5\AMC@boxedheight-0.5\AMC@boxedrule);%
418       \draw[\AMC@boxcolor@,fill=\AMC@fillcolor@,line width=\AMC@boxedrule,rounded corners=\AMC@oval@radius] (-0.5\AMC@boxedwidth,0.5\AMC@boxedheight) rectangle (0.5\AMC@boxedwidth,-0.5\AMC@boxedheight);%
419       \ifAMC@draw@cross%
420         \draw[\AMC@boxcolor@,line width=\AMC@crossrule] (-0.5\AMC@boxedwidth,0.5\AMC@boxedheight) -- (0.5\AMC@boxedwidth,-0.5\AMC@boxedheight) (0.5\AMC@boxedwidth,0.5\AMC@boxedheight) -- (-0.5\AMC@boxedwidth,-0.5\AMC@boxedheight);%
421       \fi%
422     \end{tikzpicture}%
423   }%
424 \newcommand\AMC@shapeprepare@oval{%
425   \ifx\AMC@ovalbox@R\undefined\else%
426     \AMC@makeovalbox{1}{}{\AMC@ovalbox@R}%
427     \AMC@makeovalbox{1}{\AMC@checkbox}{\AMC@ovalbox@RF}%
428     \AMC@makeovalbox{}{\AMC@checkbox}{\AMC@ovalbox@O}%
429     \AMC@makeovalbox{}{\AMC@checkbox}{\AMC@ovalbox@F}%
430   \fi%
431 }%
432 \newcommand\AMC@shape@oval[4]{%
433   \AMC@setcolors@{#3}{#2}%
434   \AMC@tracebox{#3}{#4}{\boxput*(0,0){%
435     \AMC@smashcentered{\textcolor{\AMC@boxcolor@}{#1}}%
436     \AMC@smashcentered{#2}%
437   }{%
438     \ifx\empty#3\empty%
439       \AMC@use@box{\AMC@ovalbox@F}%
440     \ifx #2\AMC@checkbox%
441       \AMC@use@box{\AMC@ovalbox@O}%
442     \else%
443       \AMC@use@box{\AMC@ovalbox@RF}%
444     \fi%
445   }}%
446 }%

```

```

445      \else%
446          \AMC@use@box{\AMC@ovalbox@}%
447      \fi%
448 \else%
449     \ifx #2\AMC@checkbox%
450         \AMC@use@box{\AMC@ovalbox@RF}%
451     \else%
452         \AMC@use@box{\AMC@ovalbox@R}%
453     \fi%
454     \fi%
455 \}%
456 }
457 \newcommand\AMC@shapeprepare@form{}%
458 \newcommand\AMC@shape@form@base[5]{%
459   \ifx #2\AMC@checkbox%
460     \def\AMC@shape@form@ticked{true}%
461   \else%
462     \def\AMC@shape@form@ticked{false}%
463   \fi%
464   \AMC@tracebox{#3}{#4}{%
465     \CheckBox[checked=\AMC@shape@form@ticked,%
466               checkboxsymbol=\ding{110},name={#5},%
467               bordercolor=0 0 0,%
468               width=\AMC@boxedwidth,height=\AMC@boxedheight]{}{}%
469   }%
470 }
471 \newcommand\AMC@shape@form[4]{%
472   \AMC@shape@form@base{#1}{#2}{#3}{#4}{\the\AMCid@etud:#4}%
473 }
474 \newcommand\AMC@shapeprepare@none{}%
475 \newcommand\AMC@shape@none[4]{ #1 }

```

`\AMC@answerBox` Command `\AMC@answerBox` is the same as `\AMC@answerBox@`, but if `<char>` is empty, it is replaced by an arabic or alphabetical counter, depending on the use of the `digits` package option.

To use another way to label the choices boxes, the user can redefine the `\AMCchoiceLabel` macro, which takes as argument the name of the counter used to number the choices. One can for example use `\def\AMCchoiceLabel#1{\alph{#1}}` to ask for lowercase letters.

To write these labels with another font, size, or so, the user can redefine the `\AMCchoiceLabelFormat` macro, which takes as argument the label. One can for example get sans serif bold labels with `\def\AMCchoiceLabelFormat#1{\textsf{\textsf{#1}}}`.

```

476 \def\AMCchoiceLabel#1{%
477   \ifAMC@inside@digit\arabic{#1}%
478   \else\Alpha{#1}\fi%
479 }
480 \def\AMCchoiceLabelFormat#1{%
481   \newcounter{AMC@ncase}%
482   \setcounter{AMC@ncase}{0}%
483   \newcommand\AMC@answerBox[4]{%
484     \AMC@answerBox@\ifx\empty#1\empty%
485       \AMCchoiceLabel{AMC@ncase}%

```

```
486 \else #1\fi}{#2}{#3}{#4}}
```

\AMCboxStyle The dimensions of these box are managed by `\AMCboxDimensions{<sizes>}`, where `<sizes>` is a comma separated list of `<name>=<dimension>` constructs. Here, `<name>` can be `size` for the box size, `rule` for the box rule width, `down` for moving the box down, `color` for the box color and `outsidesep` for the distance between the box and the letter (when outside the box).

The `<color>` value given to `color` is a color that should be defined for the `xcolor` package. This color is used only in the case the box will be used for data capture: it is not used on the corrected answer sheet (`answers` or `indivanswers` package option), and not used on the subject part of an exam with a separate answer sheet (`separateanswersheet` package option).

The `\AMCboxColor{<color>}` command is defined as an alias to `\AMCboxStyle{color=<color>}`, and `\AMCboxDimensions` as an alias to `\AMCboxStyle`, for backward compatibility.

```
487 \newlength\AMC@boxedrule
488 \newlength\AMC@crossrule
489 \newlength\AMC@boxeddown
490 \newlength\AMC@boxedwidth
491 \newlength\AMC@boxedheight
492 \newlength\AMC@oval@radius
493 \newlength\AMC@outside@sep
494 \define@choicekey{AMCdim}{shape}{square,oval,form,none}{\def\AMC@shapename{#1}}
495 \define@key{AMCdim}{size}{\AMC@boxedwidth=#1\AMC@boxedheight=#1}
496 \define@key{AMCdim}{height}{\AMC@boxedheight=#1}
497 \define@key{AMCdim}{width}{\AMC@boxedwidth=#1}
498 \define@key{AMCdim}{rule}{\AMC@boxedrule=#1}
499 \define@key{AMCdim}{outsidesep}{\AMC@outside@sep=#1}
500 \define@key{AMCdim}{down}{\AMC@boxeddown=#1}
501 \define@key{AMCdim}{color}{\def\AMC@boxcolor{#1}}
502 \define@boolkey{AMCdim}{cross}[false]{}
503 \define@key{AMCdim}{crosschar}{[\textbf{\textsf{X}}]}{\def\AMC@crosschar{#1}}
504 \define@key{AMCdim}{crossrule}{[1.5pt]}{\AMC@crossrule=#1}
505 \def\AMC@shapeprepare{\csname AMC@shapeprepare@\AMC@shapename@\endcsname}
506 \def\AMCboxStyle#1{%
507   \setkeys{AMCdim}{#1}%
508   \ifnum\AMC@boxedwidth<\AMC@boxedheight%
509     \AMC@oval@radius=\AMC@boxedwidth\divide\AMC@oval@radius\tw@%
510   \else%
511     \AMC@oval@radius=\AMC@boxedheight\divide\AMC@oval@radius\tw@%
512   \fi%
513   \AMC@shapeprepare%
514 }
515 \AMCboxStyle{shape=square,size=2.5ex,down=.4ex,rule=.5pt,outsidesep=.1em,color=black,cross,crosschar,crossru
516 \newcommand\AMCboxColor[1]{\AMCboxStyle{color=#1}}
517 \let\AMCboxDimensions=\AMCboxStyle
```

\AMCboxOutsideLetter Command `\AMC@box{<char>}{<answer>}` prints a box with character `<char>` inside, showing answer `<answer>` (`\AMC@checkbox` to get a filled box), using global variables to identify the box (question and choice).

It calls `\AMC@formBox@{<char>}{<answer>}{<trace>}{<key>}` to actually render the box.

\AMC@formBox Command `\AMC@formBox` simply sets the first argument when empty before calling `\AMC@formBox@`.

The command `\AMCboxOutsideLetter{<box>}{<char>}` is called to print the box *and* the character `<char>` outside (and next to) it. The character is formatted using `\AMCoutsideLabelFormat` first: if you need bold characters, redefine it with `\def\AMCoutsideLabelFormat#1{\textbf{#1}}`. `\AMC@keyBox@` is used instead of `\AMCformBox@` when the text that corresponds to the answer is the letter/character inside the box itself (see `\AMCcodeGrid` and `\AMCnumericChoices`.

```

518 \def\AMCoutsideLabelFormat#1{%
519 \newcommand\AMCboxOutsideLetter[2]{#1\nobreak\hspace{.1em}\AMCoutsideLabelFormat{#2}}%
520 \newif\ifAMC@printformoutside@%
521 \newcommand\ifAMC@printformoutside@{%
522   \AMC@printformoutside@false%
523   \ifAMC@ensemble\ifAMC@outside@box%
524     \ifAMCformulaire@dedans\AMC@printformoutside@true\fi%
525     \ifAMC@zoneformulaire\AMC@printformoutside@true\fi%
526   \fi\fi%
527   \ifAMC@printformoutside@%
528 }
529 \newcommand\AMC@formBox@[4]{%
530   \ifAMC@printformoutside% letter to be written outside the box
531     \AMCboxOutsideLetter{\AMC@answerBox@{}{#2}{#3}{#4}}{#1}%
532   \else%
533     \AMC@answerBox@{#1}{#2}{#3}{#4}%
534   \fi%
535   \AMC@tracechar{#1}{#2}{#3}{#4}%
536 }
537 \newif\ifAMC@printkeyoutside@%
538 \newcommand\ifAMC@printkeyoutside@{%
539   \AMC@printkeyoutside@false%
540   \ifAMC@ensemble%
541     \ifAMC@outside@box\AMC@printkeyoutside@true\fi%
542   \else%
543     \ifAMC@inside@box\else\AMC@printkeyoutside@true\fi%
544   \fi%
545   \ifAMC@printkeyoutside@%
546 }
547 \newcommand\AMC@keyBox@[4]{%
548   \ifAMC@printkeyoutside%
549     \AMCboxOutsideLetter{\AMC@answerBox@{}{#2}{#3}{#4}}{#1}%
550   \else%
551     \AMC@answerBox@{#1}{#2}{#3}{#4}%
552   \fi%
553   \AMC@tracechar{#1}{#2}{#3}{#4}%
554 }
555 \newcommand\AMC@formBox[4]{%
556   \AMC@formBox@\{\ifx\empty\empty\empty\empty%
557     \AMCchoiceLabel{\AMC@ncase}%
558     \else #1\fi\}{#2}{#3}{#4}%
559 }
560 \newcommand{\AMC@box}[2]{%
561   \ifAMC@ensemble%
562     \ifAMC@zoneformulaire% for codes inside form sheet

```

```

563     \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
564 \else%
565     \ifAMCformulaire@dedans% for answer boxes inside form sheet
566         \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
567     \else% outside form sheet: not to be read during data capture
568         \AMC@formBox{#1}{#2}{1}{casequestion:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
569 \fi\fi%
570 \else% no separate sheet for answers: always read
571     \ifAMC@inside@box%
572         \AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
573     \else%
574         \AMC@formBox@{}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
575     \fi%
576 \fi%
577 }

```

4.8.4 Scoring zones

\AMCscoreZone The source file can define zones that will be used to print scores when annotating the completed answer sheets. The command \AMCscoreZone{\langle zone \rangle} logs these zones positions on the page.

```

578 \newif\ifAMCsz@logged\AMCsz@loggedfalse
579 \newcommand{\AMCscoreZone}[1]{%
580     \ifAMC@ensemble%
581         \ifAMCformulaire@dedans%
582             \AMC@tracebox{1}{score::\the\AMCid@quest,-1}{#1}%
583         \else%
584             \AMC@tracebox{1}{scorequestion::\the\AMCid@quest,-1}{#1}%
585         \fi%
586     \else%
587         \AMC@tracebox{1}{score::\the\AMCid@quest,-1}{#1}%
588     \fi%
589     \ifAMCsz@logged\else%
590         \AMC@amclog{AUTOQCM[VAR:scorezones=1]^^J}%
591         \global\AMCsz@loggedtrue%
592     \fi%
593 }

```

4.8.5 Binary boxes

The package prints on each page some boxes that code (like binary digits) student sheet number, page number and a check number, so as to be read easily from scans after exam.

\AMCid@checkmax The check number is just decreased each page. Its maximum value is \AMCid@checkmax. The number of binary digits used to print student sheet number, page and check number are \AMC@NCBetud, \AMC@NCBpage and \AMC@NCBcheck. The number of the first page is \AMC@premierecopie.
\AMC@NCBetud
\AMC@NCBpage
\AMC@NCBcheck The length of zone reserved for binary boxes is \AMC@CBtaille.

```

594 \def\AMCid@checkmax{60}
595 \def\AMC@NCBetud{12}
596 \def\AMC@NCBpage{6}

```

```

597 \def\AMC@NCBcheck{6}
598 \newlength{\AMC@CBtaille}\setlength{\AMC@CBtaille}{5cm}
599 \def\AMC@premierecopie{1}

```

\AMC@binaryBoxes Command \AMC@binaryBoxes[*ndigits*]{*n*} prints *ndigits* boxes to represent number *n* in its binary form. \AMCbin@one and \AMCbin@zero print individual digit-boxes.

For example, \AMC@binaryBoxes[12]{367} shows $367 = 000101101111_2$ using 12 boxes:



```

600 \newtoks\AMCbin@sequence
601 \newcount\AMCbin@number
602 \newcount\AMCbin@ndigits
603 \newcount\AMCbin@id
604 \newcount\AMCbin@digit
605 \def\AMCbin@one{\advance\AMCbin@digit\@ne%
606   \AMC@answerBox@{}{\AMC@checkbox}{1}{chiffre:\the\AMCbin@id,\the\AMCbin@digit}}
607 \def\AMCbin@zero{\advance\AMCbin@digit\@ne%
608   \AMC@answerBox@{}{\AMC@checkbox}{1}{chiffre:\the\AMCbin@id,\the\AMCbin@digit}}
609 \def\AMCbin@begin#1{\AMCbin@id=#1\AMCbin@digit=\z@}
610 \newcommand{\AMC@binaryBoxes}[2][1]{%
611 {\AMCboxDimensions{shape=square,size=.32cm,down=0pt,rule=.2pt,cross=false}\AMCbin@sequence={}\AMCbin@number=%
612 \AMCbin@ndigits=\z@%
613 \loop%
614 \ifnum\AMCbin@number>\z@%
615 \advance\AMCbin@ndigits\@ne%
616 \ifodd\AMCbin@number\AMCbin@sequence=\expandafter{\expandafter\AMCbin@one\the\AMCbin@sequence}%
617 \else\AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\fi%
618 \divide\AMCbin@number\tw@%
619 \repeat%
620 \loop\relax%
621 \ifnum\AMCbin@ndigits<#1\advance\AMCbin@ndigits\@ne%
622 \AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\repeat%
623 \the\AMCbin@sequence%
624 \ifnum\AMCbin@ndigits>#1\PackageError{automultiplechoice}{Too low AMC@NCB value (got #1 but needs \the\AMCbin@ndigits)}{%
625 }%

```

4.9 Checking Environment

\AMCcurrentenv Sets the current environment as document.

```
626 \def\AMCcurrentenv{document}
```

\AMCif@env Checks for the current environment.

```

627 \def\AMCif@env#1{%
628   \def\AMC@tempenv{\#1}%
629   \ifx\AMC@tempenv\AMCcurrentenv
630     \expandafter\@firstoftwo
631   \else
632     \expandafter\@secondoftwo
633   \fi
634 }

```

4.10 Handling groups of questions

The package allows to handle groups of questions, so as to be able to shuffle them before printing them to the sheets.

```
\nouveaugroupe  Command \nouveaugroupe{\langle group-name\rangle}{\langle n\rangle} creates a new (empty) group with name \langle group-name\rangle (argument \langle n\rangle is present only for compatibility reasons and is ignored). Command \element{\langle group-name\rangle}{\langle text\rangle} adds to group \langle group-name\rangle a new element that contains \langle text\rangle. \langle text\rangle can be a question environment, ore two successive questions to be kept together, or anything else. Calling command \nouveaugroupe is not compulsory, as \element calls it if necessary.
635 \newcount\AMCtok@k
636 \newcount\AMCtok@max
637 \newcount\AMCtok@size
638 \newcommand{\nouveaugroupe}[2]{%
639   \expandafter\ifx\csname #1@k\endcsname\relax%
640     \expandafter\newcount\csname #1@k\endcsname%
641     \expandafter\newcount\csname AMC#1@j\endcsname%
642     \csname #1@k\endcsname=\z@\relax%
643     \csname AMC#1@j\endcsname=\z@\relax%
644     \setgroupmode{\#1}{\AMCdefault@groupmode}%
645   \fi%
646 }
647 \newcommand\AMC@prepare@element[1]{%
648   \nouveaugroupe{\#1}{}}%
649   \global\advance\csname #1@k\endcsname@ne\relax%
650   \AMCtok@k=\csname #1@k\endcsname%
651   \expandafter\ifx\csname #1@\romannumerals\AMCtok@k\endcsname\relax%
652     \expandafter\newtoks\csname #1@\romannumerals\AMCtok@k\endcsname\fi%
653 }
654 \newcommand{\element}[2]{%
655   \AMC@prepare@element{\#1}%
656   \global\csname #1@\romannumerals\AMCtok@k\endcsname=\#2}%
657 }
```

\setgroupmode Command \setgroupmode{\langle group-name\rangle}{\langle mode\rangle} sets the group mode to \langle mode\rangle for group \langle group-name\rangle. This mode setup the behaviour of \insertgroup and \copygroup for this group:

1. With mode **fixed**, group's elements will be taken from the beginning.
2. With mode **cyclic**, the elements will be taken from the group following the last call group's use, recycling if necessary.
3. Mode **withreplacement** is the same as **fixed**, but the group is shuffled before each use.
4. Mode **withoutreplacement** is like **cyclic**, adding some shuffling when comming back to the beginning of the group.

The command \setdefaultgroupmode{\langle mode\rangle} sets the group mode to be used for the following created groups (a group is created at the first \element{\langle group\rangle} call). When no \setdefaultgroupmode is used, **fixed** is the default mode.

```

658 \def\AMCdefault@groupmode{fixed}
659 \newcommand{\setdefaultgroupmode}[1]{\def\AMCdefault@groupmode{#1}}
660 \newcommand{\setgroupmode}[2]{%
661   \expandafter\ifx\csname AMCgroup\relax%
662     \PackageError{automultiplechoice}{Unknown group mode for #1 : #2}%
663     {You asked to set group '#1' mode to '#2',%
664      but '#2' is not a valid group mode}%
665   \else%
666     \expandafter\global\expandafter\def\csname AMC#1@mode\endcsname{#2}%
667   \fi%
668 }

```

The functions `\AMCgroup $\langle group-name \rangle$ { $\langle n \rangle$ }{{ i }}` are called before using $\langle n \rangle$ elements from group $\langle group-name \rangle$ starting from index $\langle i \rangle$ (negative value for $\langle i \rangle$ stands for the current value of the group index), either with `\insertgroup` or `\copygroup`.

For mode **fixed**, the group index is set to $\langle i \rangle$, or 0 if $\langle i \rangle$ is negative (take elements from the beginning).

```

669 \newcommand{\AMCgroup\relax@fixed}[3]{%
670   \ifnum#3<\z@\%
671     \csname AMC#1@j\endcsname=\z@\%
672   \else%
673     \csname AMC#1@j\endcsname=#3%
674   \fi%
675 }

```

For mode **withreplacement**, the group is shuffled and the group index is set to $\langle i \rangle$ or 0 (take elements from the beginning) if negative.

```

676 \newcommand{\AMCgroup\relax@withreplacement}[3]{%
677   \ifnum#3<\z@\%
678     \csname AMC#1@j\endcsname=\z@\%
679   \else%
680     \csname AMC#1@j\endcsname=#3%
681   \fi%
682   \shufflegroup{#1}%
683 }

```

For mode **withoutreplacement**, the group index is set to $\langle i \rangle$, or left unchanged if $\langle i \rangle$ is negative. If there is not enough elements left in the group, the elements before the index and the elements after the index are shuffled.

```

684 \newcount\AMC@imax
685 \newcommand{\AMCgroup\relax@withoutreplacement}[3]{%
686   \ifnum#3<\z@\%
687   \else%
688     \csname AMC#1@j\endcsname=#3%
689   \fi%
690   \ifnum\AMCtok@ik=\AMCloop@k%
691     \AMCtok@ik=\z@\%
692   \fi%
693   \ifnum\AMCtok@ik=\z@\%
694     \shufflegroup{#1}%
695   \else%

```

```

696   \AMC@imax=\AMCloop@k%
697   \advance\AMC@imax -#2\relax%
698   \ifnum\AMCtok@ik>\AMC@imax%
699     \shufflegroupslice{\#1}{\one}{\AMCtok@ik}%
700     \ifnum\AMCtok@ik<\AMCloop@k%
701       \advance\AMCtok@ik\one%
702       \shufflegroupslice{\#1}{\AMCtok@ik}{\AMCloop@k}%
703     \fi%
704   \fi%
705 \fi%
706 }

```

For mode **cyclic**, nothing has to be done, except setting the group index if non-negative.

```

707 \newcommand{\AMCgroup@pre@cyclic}[3]{%
708   \ifnum#3<\z@%
709   \else%
710     \csname AMC#1@j\endcsname=#3%
711   \fi%
712 }

```

The function $\text{\AMCgroup@pre}\{\langle mode \rangle\}\{\langle group-name \rangle\}\{\langle n \rangle\}\{\langle i \rangle\}$ calls the right \AMCgroup@xxx command.

```

713 \newcommand{\AMCgroup@pre}[4]{%
714   \csname AMCGroup@#1\endcsname{#2}{#3}{#4}%
715 }

```

\shufflegroup Command $\text{\shufflegroup}\{\langle group-name \rangle\}$ shuffles the elements of group $\langle group-name \rangle$, and
\insertgroup $\text{\insertgroup}\{\langle group-name \rangle\}\{\langle a \rangle\}\{\langle b \rangle\}$ shuffles elements $\langle a \rangle$ to $\langle b \rangle$ from group $\langle group-name \rangle$.
\insertgroupfrom It can be called at each student sheet in order to get different student sheets and avoid cheating.

Command $\text{\insertgroup}\{\langle n \rangle\}\{\langle groupname \rangle\}$ inserts all the elements of group $\langle groupname \rangle$, or only the first $\langle n \rangle$ elements if $\langle n \rangle$ is given. $\text{\insertgroupfrom}\{\langle n \rangle\}\{\langle groupname \rangle\}\{\langle i \rangle\}$ inserts all the elements of group $\langle groupname \rangle$ starting from index $\langle i \rangle$ (the index of the first element is 0), or only the first $\langle n \rangle$ elements if $\langle n \rangle$ is given.

```

716 \newcommand{\shufflegroup}[1]{%
717   \ifAMC@shuffleG{\AMC@shuffletoks{\number\csname #1@k\endcsname}{#1@}}\fi%
718 }
719 \newcommand{\shufflegroupslice}[3]{%
720   \ifAMC@shuffleG{\AMC@shuffletoks[#2]{#3}{#10}}\fi%
721 }
722 \newcount\AMCtok@ik
723 \newcount\AMCloop@k
724 \newcommand{\AMCgrouploop@prep}[3]{%
725   \AMCtok@size=#1\relax%
726   \ifAMC@fullGroups\AMCtok@size=\z@\fi%
727   \ifnum\AMCtok@size<\one%
728     \AMCtok@size=\csname #2@k\endcsname%
729   \fi%
730   \AMCtok@ik=\csname AMC#2@j\endcsname%
731   \AMCloop@k=\csname #2@k\endcsname%
732   \expandafter\ifx\csname AMC#2@mode\endcsname\relax%

```

```

733     \PackageError{automultiplechoice}{No group mode for #2}%
734         {No mode has been defined for group '#2'. This should not occur...}%
735     \fi%
736     \AMCgroup@pre{\csname AMC#2@mode\endcsname}{#2}{\the\AMCtok@size}{#3}%
737 }
738 \newcommand{\AMCgrouploop@next}[1]{%
739     \global\advance\csname AMC#1@j\endcsname\@ne\relax%
740     \expandafter\ifnum\csname AMC#1@j\endcsname>\AMCloop@k\relax%
741         \global\csname AMC#1@j\endcsname=\@ne%
742     \fi%
743     \AMCtok@ik=\csname AMC#1@j\endcsname%
744     \advance\AMCtok@size\m@ne%
745 }
746 \newcommand{\insertgroupfrom}[3][0]{%
747     \AMCgrouploop@prep{#1}{#2}{#3}%
748     {\loop%
749         \AMCgrouploop@next{#2}%
750         {\the\csname #2@\roman{numeral}\AMCtok@ik\endcsname}%
751         \ifnum\AMCtok@size>\z@\repeat}%
752 }
753 \newcommand{\insertgroup}[2][0]{%
754     \insertgroupfrom[#1]{#2}{-1}%
755 }

```

\cleargroup The commands `\cleargroup` and `\copygroup` can also be used to make more complex questions
\copygroup combinations in the exams, allowing for example to ask the package to shuffle 3 questions taken at
\copygroupfrom random from group `groupa` and 5 questions taken at random from group `groupb`.

`\cleargroup{<group>}` clears the group `<group>`, erasing all of its elements.

`\copygroup[<n>]{<from>}{<to>}` copies `<n>` elements from group `<from>` to group `<to>`. If optional parameter `<n>` is not given, all the questions from group `<from>` are copied. `\copygroupfrom[<n>]{<from>}{<to>}{<i>}` copies `<n>` elements from group `<from>` to group `<to>`, starting from element at index `<i>` (the index of the first element is 0). If optional parameter `<n>` is not given, all the questions from group `<from>` are copied.

See section 3.4 for an illustration for these commands.

```

756 \newcommand{\cleargroup}[1]{%
757     \nouveauugroupe{#1}{}%
758     \csname #1@k\endcsname=\z@\relax%
759     \csname AMC#1@j\endcsname=\z@\relax%
760 }
761 \newcommand{\copygroupfrom}[4][0]{%
762     \AMCgrouploop@prep{#1}{#2}{#4}%
763     {\loop%
764         \AMCgrouploop@next{#2}%
765         \AMC@prepare@element{#3}%
766         \global\csname #3@\roman{numeral}\AMCtok@k\endcsname=\csname #2@\roman{numeral}\AMCtok@ik\endcsname%
767         \ifnum\AMCtok@size>\z@\repeat}%
768 }
769 \newcommand{\copygroup}[3][0]{%
770     \copygroupfrom[#1]{#2}{#3}{-1}%

```

```
771 }
```

4.11 Questions

To manage multiple choice questions, first set some counters and token registers to handle answers. Token registers `\reponse@i`, `\reponse@ii` and so on will be used for answers – we restrict the number of answers of a single questions to `\AMCload@counter = 199`.

```
772 \newcount\AMCrep@count
773 \AMCload@counter=199
774 \@whilenum\AMCload@counter>0\do{%
775   \expandafter\newtoks\csname reponse@\romannumeral\AMCload@counter\endcsname%
776   \advance\AMCload@counter\m@ne%
777 }
```

`\AMCload@reponse` Command `\AMCload@reponse{\langle n \rangle}{\langle text \rangle}` will be used to add answer number $\langle n \rangle$ with text $\langle text \rangle$ ($\langle text \rangle$ will include the box to be ticked and all the layout commands) to the set of answers (in a token register `\reponse@xxx` – counter `\AMCload@counter` keeps track of the number of answers), in order to shuffle them when all answers will be loaded.

When answers are not to be shuffled, command `\AMCrien@deux{\langle n \rangle}{\langle text \rangle}` will be used instead, only printing $\langle text \rangle$.

```
778 \newcommand\AMCload@reponse[2]{%
779   \global\advance\AMCload@counter\@ne\relax%
780   \global\csname reponse@\romannumeral\AMCload@counter\endcsname%
781   =\expandafter{\expandafter\AMCrep@count\expandafter=\#2 \#1}%
782 }
783 \newcommand\AMCrien@deux[2]{\#1}
```

`\shuffle@it` After loading all answers, commands `\shuffle@it` will be used to shuffle them, and `\AMCdump@responses` to print them.

```
784 \def\shuffle@it{\AMC@shuffletoks{\number\AMCload@counter}{reponse@}}
785 \newcount\AMCnum@questions
786 \newcommand\AMCdump@responses{%
787   \global\AMCnum@questions=\AMCload@counter%
788   \@whilenum\AMCload@counter>0\do{%
789     \the\csname reponse@\romannumeral\AMCload@counter\endcsname%
790     \advance\AMCload@counter\m@ne}}
```

4.11.1 Managing answers

`\lastchoices` Command `\AMCrep@init{\langle mode \rangle}` is called for each question before reading answers. $\langle mode \rangle$ is `r` for suffled answers, and `o` if answers are not to be shuffled. It sets the number of answers counter to zero, and calls `\AMCrep@o` or `\AMCrep@r` depending on $\langle mode \rangle$. These commands sets `\AMCload@reponse` and `\AMCrep@fini` that will be called for each answer and after the last answer respectively, depending on $\langle mode \rangle$:

- If $\langle mode \rangle=r$, `\AMCload@reponse` is `\AMCload@reponse` (loads answer to token register) and `\AMCrep@fini` calls `\shuffle@it` and `\AMCdump@responses`;

- If $\langle mode \rangle = o$, `\AMCload@reponse` is `\AMCrien@deux` (prints answer directly) and `\AMCrep@fini` does nothing.

Command `\lastchoices` is called before giving answers that are to be printed at the end (even when shuffling answers). It closes the answers list calling `\AMCrep@fini` and opens another one in ordered mode. Note that it also saves the value of `\AMCrep@count`, which is the number of the current answer among all answers given in the subject source for the current question.

Command `\AMC@fin@rep` is to be called after the last answer: it adds a “None of these answers are correct.” answer if necessary (package option `completemulti`) with answer number zero, and calls `\AMCrep@fini`.

```

791 \newcommand\AMCrep@init[1]{%
792   \ifAMC@ordre\AMCrep@o\else%
793     \csname AMCrep@\#1\endcsname\fi\AMCload@counter=\z@}
794 \newcommand\AMCrep@o{%
795   \def\AMCload@reponse{\AMCrien@deux}\def\AMCrep@fini{}}
796 \newcommand\AMCrep@r{%
797   \def\AMCload@reponse{\AMCload@reponse}%
798   \def\AMCrep@fini{\shuffle@it\AMCdump@responses}}
799 \newcount\AMCrep@count
800 \newcommand\lastchoices{%
801   \AMCrep@count=\AMCrep@count%
802   \AMCrep@fini\AMCrep@init{}%
803   \AMCrep@count=\AMCrep@count}
804 \newcommand\@aucune{\emph{\AMC@loc@none}}
805 \newcommand\AMC@fin@rep{%
806   \ifAMCcomplete@multi\ifAMCtype@multi%
807     \lastchoices\AMCrep@count=-1%
808     \ifAMCune@bonne\wrongchoice{\@aucune}\else%
809       \ifAMC@postcorrect\wrongchoice{\@aucune}\else\correctchoice{\@aucune}\fi%
810     \fi\fi\fi\AMCrep@fini}
```

4.11.2 Separate answer sheet

This package needs some memory to print questions/answers boxes again on a separate answer sheet.

`\AMCformQuestion` First define commands that will announce questions and answers on the separate answer sheet (these commands can be modified by the user): `\AMCformQuestion{<number>}` is responsible for announcing question, and `\AMCformAnswer{<box>}` is responsible for printing the box to be ticked, given as argument `<box>`.

Commands `\AMCformQuestionA` and `\AMCformAnswerA` set up counter `\AMC@ncase` value before calling their counterparts.

```

811 \def\AMCformBeforeQuestion{\vspace{\AMCformVSpace}\par}
812 \def\AMCformAfterQuestion{\ifAMC@asqbloc\egroup\fi}
813 \def\AMCformQuestion#1{\AMC@loc@qff{#1}}
814 \def\AMCformQuestionN{\AMCformQuestion{\AMC@qaff}}
815 \def\AMCformQuestionA{%
816   \setcounter{AMC@ncase}{0}%
817   \AMCformBeforeQuestion}
```

```

818 \ifAMC@asqbloc\vbox\bgroup\fi%
819 \ifx\@empty\AMC@sza@callout\@empty\else%
820   \csname\AMC@sza@callout\endcsname%
821 \fi%
822 \AMCformQuestionN%
823 \ifx\@empty\AMC@sza@callin\@empty\else%
824   \csname\AMC@sza@callin\endcsname%
825 \fi%
826 }
827 \def\AMCformAnswer#1{\hspace{\AMCformHSpace} #1}
828 \def\AMCformAnswerA#1{\addtocounter{AMC@ncase}{1}\AMCformAnswer{#1}}

```

\AMCmem@add@ifneeded These are commands to manage memory for separate answer sheet. \AMCmem@add@ifneeded{\langle code\rangle} adds \langle code\rangle to this memory. \AMCmem@answer{\langle code\rangle} adds to memory answer code \langle code\rangle, and \AMCmem@openQuestion adds to memory question code to announce current question.

\AMCformS The command \AMCformBegin defines the beginning of the separate answer sheet for the current student sheet, and \AMCform prints the whole memory: questions and answers boxes.

\AMCformS is a \AMCform variant that does not clear the list of answer boxes. It can be used to make the same exact subject for all students, displaying the questions before (outside) `oncopy`, so that `oncopy` contains only the answer sheet.

```

829 \ExplSyntaxOn
830
831 \prg_set_conditional:Nnn \amc_if_separate_question: { p , T } {
832   \ifAMC@ensemble
833     \ifAMC@zoneformulaire
834       \prg_return_false:
835     \else
836       \prg_return_true:
837     \fi
838   \else
839     \prg_return_false:
840   \fi
841 }
842 \cs_new_eq:NN \AMC@if@separate@question \amc_if_separate_question:T
843
844 \int_new:N \amc_memory_elts_count
845
846 \cs_new:Nn \amc_clear_memory: { \int_gzero:N \amc_memory_elts_count }
847 \cs_new_eq:NN \AMC@mem@clear \amc_clear_memory:
848
849 \cs_new:Npn \amc_memory_elt_i:n #1 {
850   \amc_memory_elts_ \int_to_alpha:n { #1 }
851 }
852 \cs_new:Nn \amc_memory_current_elt: {
853   \amc_memory_elt_i:n \amc_memory_elts_count
854 }
855 \cs_new:Npn \amc_memory_vars_i:n #1 {
856   \amc_memory_vars_ \int_to_alpha:n { #1 }

```

```

857 }
858 \cs_new:Nn \amc_memory_current_vars: {
859   \amc_memory_vars_i:n \amc_memory_elts_count
860 }
861
862 \cs_new:Nn \amc_add_memory_elt: {
863   \int_gincr:N \amc_memory_elts_count
864   \tl_gclear_new:c { \amc_memory_current_elt: }
865   \tl_gclear_new:c { \amc_memory_current_vars: }
866 }
867 \cs_new_eq:NN \AMC@mem@next \amc_add_memory_elt:
868
869 \cs_new:Npn \amc_add_to_memory:n #1 {
870   \tl_gput_right:cn { \amc_memory_current_elt: } { #1 }
871 }
872 \cs_new_eq:NN \AMC@mem@add \amc_add_to_memory:n
873
874 \cs_new:Npn \amc_add_to_vars:n #1 {
875   \tl_gput_right:cn { \amc_memory_current_vars: } { #1 }
876 }
877 \cs_new_eq:NN \AMC@mem@addvar \amc_add_to_vars:n
878
879 \cs_new:Npn \amc_add_qidaffname:nnn #1#2#3 {
880   \amc_add_to_vars:n {\AMC@quest=#1\setcounter{AMCquestionaff}{#2}%
881     \global\def\AMC@name{#3}}
882 }
883 \cs_generate_variant:Nn \amc_add_qidaffname:nnn { xxx }
884 \cs_new_eq:NN \AMC@mem@qidaffname \amc_add_qidaffname:xxx
885
886 \cs_new:Npn \amc_mem_elt_cat:n #1 {
887   \amc_add_to_vars:n { \def\AMCmem@elt@cat{ #1 } }
888 }
889 \cs_generate_variant:Nn \amc_mem_elt_cat:n { x }
890 \cs_new_eq:NN \AMC@mem@category \amc_mem_elt_cat:x
891
892 \cs_new:Npn \amc_add_aid:n #1 {
893   \amc_add_to_memory:n {\AMC@count=#1}
894 }
895 \cs_generate_variant:Nn \amc_add_aid:n { x }
896 \cs_new_eq:NN \AMC@mem@aid \amc_add_aid:x
897
898 \cs_new:Npn \amc_if_category_is_p:n #1 {
899   \str_if_eq_p:on { \AMCmem@elt@cat } { #1 }
900 }
901 \cs_new:Npn \amc_use_memory:n #1 {
902   \int_step_inline:nnnn { 1 } { 1 } \amc_memory_elts_count {
903     \def\AMCmem@elt@cat{ plain }
904     \tl_use:c { \amc_memory_vars_i:n { ##1 } }
905     \bool_if:NTF { #1 } {
906       \tl_use:c { \amc_memory_elt_i:n { ##1 } }

```

```

907     } { }
908   }
909 }
910 \cs_new:Nn \amc_use_memory: { \amc_use_memory:n { \c_true_bool } }
911 \cs_new_eq:NN \AMC@mem@show \amc_use_memory:
912 \cs_new_eq:NN \AMC@mem@show@filter \amc_use_memory:n
913 \cs_new_eq:NN \AMCifcategory \amc_if_category_is_p:n
914
915 \ExplSyntaxOff
916 \newcommand\AMC@mem@add@ifneeded[1]{%
917   \AMC@if@separate@question{%
918     \AMC@mem@add{#1}%
919   }%
920 }
921 \newcommand\AMC@mem@addsingle@ifneeded[2]{%
922   \AMC@if@separate@question{%
923     \AMC@mem@next%
924     \AMC@mem@category{#2}%
925     \AMC@mem@add{#1}%
926   }%
927 }
928 \newcommand\AMC@mem@answer[1]{%
929   \addtocounter{AMC@ncase}{1}%
930   \AMC@if@separate@question{%
931     \AMC@mem@aid{\the\AMCrep@count}%
932     \AMC@mem@add{\AMCformAnswerA{#1}}%
933   }%
934 }
935 \newcommand\AMC@mem@openQuestion{%
936   \AMC@if@separate@question{%
937     \AMC@mem@next%
938     \AMC@mem@qidaffname{\the\AMCid@quest}{\arabic{AMCquestionaff}}{\AMCid@name}%
939     \AMC@mem@add{\AMCformQuestionA}%
940   }%
941 }
942 \def\AMCformBegin{%
943   \AMC@zoneformulairetrue\setcounter{section}{0}%
944   \ifAMC@ensemble\ifAMC@automarks\pagestyle{AMCpageFull}\fi\fi%
945 }
946 \newcommand\AMCform{%
947   \ifAMC@ensemble\AMCformulaire@dedanstrue%
948     \AMC@mem@show{%
949   \fi}%
950 \newcommand\AMCformFilter[1]{%
951   \ifAMC@ensemble\AMCformulaire@dedanstrue%
952     \AMC@mem@show@filter{#1}%
953   \fi}%
954 \newif\ifAMC@keepmemory
955 \newcommand\AMCformS{%
956   \ifAMC@ensemble\AMCformulaire@dedanstrue%

```

```

957 \AMC@amclog{AUTOQCM[BR=0]^^J}\AMC@mem@show%
958 \AMC@keepmemorytrue%
959 \fi}

\AMCsection The \AMCsection and \AMCsubsection commands issue their standard counterparts (\section and \subsection with the same argument, both in the subject and in the separate answer sheet.
\AMCsubsection and \AMCsubsubsection with the same argument, both in the subject and in the separate answer sheet.

960 \newcommand{\AMCsectionNumbered}[1]{%
961   \section{\#1}\AMC@mem@addsingle@ifneeded{\section{\#1}}{section}%
962 \newcommand{\AMCsubsectionNumbered}[1]{%
963   \subsection{\#1}\AMC@mem@addsingle@ifneeded{\subsection{\#1}}{subsection}%
964 \newcommand{\AMCsectionStar}[1]{%
965   \section*{\#1}\AMC@mem@addsingle@ifneeded{\section*{\#1}}{section}%
966 \newcommand{\AMCsubsectionStar}[1]{%
967   \subsection*{\#1}\AMC@mem@addsingle@ifneeded{\subsection*{\#1}}{subsection}%
968 \def\AMCsection{\@ifstar\AMCsectionStar\AMCsectionNumbered}%
969 \def\AMCsubsection{\@ifstar\AMCsubsectionStar\AMCsubsectionNumbered}%

```

4.11.3 Formatting answers

choices Answers have to be included in an environment **choices** (standard), **choiceshoriz** (answers on one line) or **choicescustom** (user defined) depending on the desired formatting.
choiceshoriz Use \AMCBoxedAnswers to request all answers to be included in L^AT_EX boxes; this can be useful
choicescustom for example when using multicolumn answers formatting.
tikz-single
tikz-multi 970 \def\AMCBoxedAnswers{\AMC@rbloctrue}
\AMCBoxedAnswers 971 \newenvironment{choices}[1][r]{%
972 \AMCrep@count=\z@\def\une@rep{\AMCrep@itemize}%
973 \ifAMC@rbloc\def\une@rep{\AMCrep@bloc}%
974 \else\begin{itemize}\setlength{\itemsep}{\AMCinterIrep}\fi%
975 \AMCrep@init{\#1}%
976 {\AMC@fin@rep\ifAMC@rbloc\else\end{itemize}\fi}
977 \newenvironment{choiceshoriz}[1][r]{%
978 \AMCrep@count=\z@\def\une@rep{\AMCrep@ligne}\AMCrep@init{\#1}%
979 \par\begin{center}}%
980 {\AMC@fin@rep\end{center}}
981 \newenvironment{choicescustom}[1][r]{%
982 \AMCrep@count=\z@\def\une@rep{\AMCrep@perso}\AMCrep@init{\#1}%
983 \AMCbeginAnswerignorespaces}%
984 {\AMC@fin@rep\AMCendAnswer}
985 \newenvironment{tikz-single}[1][r]{%
986 \AMCrep@count=\z@\def\une@rep{\AMCrep@tikz}\AMCrep@init{\#1}%
987 \begin{tikzpicture}}{\AMC@fin@rep\end{tikzpicture}}
988 \newenvironment{tikz-multi}[1][r]{%
989 \AMCrep@count=\z@\def\une@rep{\AMCrep@tikzmat}\AMCrep@init{\#1}%
990 \begin{tikzpicture}[remember picture]}{\AMC@fin@rep\end{tikzpicture}}

\AMCrep@bloc For each of these styles, a corresponding \AMCrep@xxx{\langle box\rangle}{\langle text\rangle} is defined, which will format
\AMCrep@tikz the answer with a box given in *\langle box\rangle* and text *\langle text\rangle*. \AMCrep@bloc is also defined and used in
\AMCrep@tikzmat standard formatting when the user wants to put answers inside a L^AT_EX box.
\AMCrep@itemize 991 \newcommand{\AMCrep@bloc}[2]{\AMC@mem@answer{\#1}}%
\AMCrep@ligne
\AMCrep@perso

\AMCbeginAnswer The `custom` style will use user-defined commands to format answers: `\AMCbeginAnswer` is called once before answers, `\AMCanswer{\langle box\rangle}{\langle text\rangle}` is called for each answer (`\langle box\rangle` being the box to be ticked and `\langle text\rangle` the text associated with the proposed answer), and `\AMCendAnswer` is called after all answers.

```
1012 \def\AMCbeginAnswer{}  
1013 \def\AMCanswer#1#2{#1 #2}  
1014 \def\AMCendAnswer{}
```

`\answer` The commands `\correctchoice` and `\wrongchoice` are used inside `choices`-like environments to give the proposed answers and specify if they are to be ticked by the students or not.

```
\wrongchoice 1015 \newcommand{\correctchoice}[2][]{\global\advance\AMCrep@count@ne\relax%
1016   \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:B]^^J}\fi%
1017   \global\AMCune@bonnettrue%
1018   \AMCload@@reponse{\une@rep{\ifAMC@correc\AMC@box[#1]{\AMC@checkbox}%
1019     \else\AMC@box[#1]{}{}\fi{}{#2}}{\the\AMCrep@count}\ignorespaces}
1020 \newcommand{\wrongchoice}[2][]{\global\advance\AMCrep@count@ne\relax%
1021   \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:M]^^J}\fi%
1022   \AMCload@@reponse{\une@rep{\AMC@box[#1]{}{}}{#2}}{\the\AMCrep@count}\%
1023   \ignorespaces}
```

4.11.4 Score zones

\AMCscoreZone The position of the scores on the annotated answer sheets can be defined in the **LATEX** source file using **\AMCsetScoreZone{<options>}** (or **\AMCsetScoreZoneAnswerSheet{<options>}** for the answer sheets when the separate answer sheet option is used).

First begin with some helpers: `\AMCemptybox{\langle width \rangle}{\langle height \rangle}{\langle depth \rangle}` draws an empty box with specified dimensions, and `\AMCmarginNote{\langle note \rangle}` (code from one of sgmyoe's comments on

`tex.stackexchange.com`) prints a marginal note in the left or right margin, depending on current the position (usefull in `multicols` environment).

```

1024 \newcommand{\AMCemptybox}[3]{%
1025   \sbox0{}\wd0=#1\ht0=#2\dp0=#3\relax\box0}
1026 \newlength\AMC@mn@test
1027 \newlength\AMC@mn@sep\AMC@mn@sep=4mm
1028 \newlength\AMC@mn@leftmargin
1029 \newlength\AMC@mn@rightmargin
1030 \newcommand\AMCmarginNote[1]{%
1031   \begin{tikzpicture}[remember picture,overlay]%
1032     \coordinate (here) at (0,0);%
1033     \pgfextractx{\AMC@mn@test}{\pgfpointdiff{\pgfpointorigin}%
1034       {\pgfpointanchor{current page}{center}}}%
1035     \ifodd\thepage%
1036       \AMC@mn@leftmargin=\oddsidemargin%
1037       \AMC@mn@rightmargin=\evensidemargin%
1038     \else
1039       \AMC@mn@leftmargin=\evensidemargin%
1040       \AMC@mn@rightmargin=\oddsidemargin%
1041     \fi
1042     \ifdim\AMC@mn@test < 1cm%
1043       \draw (current page.east |- here)+(-\AMC@mn@rightmargin-1in+\AMC@mn@sep,0pt) node[anchor=text,align=left]
1044     \else%
1045       \draw (current page.west |- here)+(0cm,0pt) node[anchor=text,align=right,text width=\AMC@mn@leftmargin]%
1046     \fi%
1047   \end{tikzpicture}%
1048 }
```

Define now different ways to place the score zone:

`none` nowhere

`question` right after the question heading

`margin` in the margin, using `marginpar` (this does not work with `multicols` environment)

`margins` in the left or right margin, depending on the current position (needs `tikz` package)

```

1049 \newcommand{\AMC@sz@box}{\AMCemptybox{\AMC@sz@width}{\AMC@sz@height}{\AMC@sz@depth}}
1050 %
1051 \newcommand{\AMC@sz@callin@question}{\AMCscoreZone{\AMC@sz@box}}
1052 %
1053 \newcommand{\AMC@sz@callout@margin}{\hspace{0pt}\marginpar{\AMCscoreZone{\AMC@sz@box}}}
1054 %
1055 \newcommand{\AMC@sz@init@margins}{\PackageWarning{automultiplechoice}{Please run twice to get proper margin}}
1056 \newcommand{\AMC@sz@callout@margins}{\hspace{0pt}\AMCmarginNote{\AMCscoreZone{\AMC@sz@box}}}
```

Let us now set up options handling.

```

1057 \newlength\AMC@sz@width
1058 \newlength\AMC@sz@height
1059 \newlength\AMC@sz@depth
1060 \def\AMC@sz@callout{}
```

```

1061 \def\AMC@sz@callin{}
1062 \define@key{AMCsz}{width}{\AMC@sz@width=#1}
1063 \define@key{AMCsz}{height}{\AMC@sz@height=#1}
1064 \define@key{AMCsz}{depth}{\AMC@sz@depth=#1}
1065 \define@key{AMCsz}{calloutside}{\def\AMC@sz@callout{#1}}
1066 \define@key{AMCsz}{callinside}{\def\AMC@sz@callin{#1}}
1067 \define@choicekey{AMCsz}{position}{none,question,margin,margins}{%
1068   \ifcsname AMC@sz@callout@#1\endcsname%
1069     \def\AMC@sz@callout{AMC@sz@callout@#1}%
1070   \else%
1071     \def\AMC@sz@callout{}%
1072   \fi%
1073   \ifcsname AMC@sz@callin@#1\endcsname%
1074     \def\AMC@sz@callin{AMC@sz@callin@#1}%
1075   \else%
1076     \def\AMC@sz@callin{}%
1077   \fi%
1078   \ifcsname AMC@sz@init@#1\endcsname%
1079     \csname AMC@sz@init@#1\endcsname%
1080   \fi%
1081 }
1082 \newcommand{\AMCsetScoreZone}[1]{\setkeys{AMCsz}{#1}}
1083 \AMCsetScoreZone{width=1.5em,height=1.5ex,depth=.5ex,position=none}

```

And do the same for \AMCsetScoreZoneAnswerSheet...

```

1084 \newcommand{\AMC@sza@box}{\AMCemptybox{\AMC@sza@width}{\AMC@sza@height}{\AMC@sza@depth}}
1085 %
1086 \newcommand{\AMC@sza@init@none}={}
1087 \newcommand{\AMC@sza@callout@none}={}
1088 \newcommand{\AMC@sza@callin@none}={}
1089 %
1090 \newcommand{\AMC@sza@init@question}={}
1091 \newcommand{\AMC@sza@callout@question}={}
1092 \newcommand{\AMC@sza@callin@question}{\AMCscoreZone{\AMC@sza@box}}
1093 %
1094 \newcommand{\AMC@sza@init@margin}={}
1095 \newcommand{\AMC@sza@callout@margin}{\hspace{0pt}\marginpar{\AMCscoreZone{\AMC@sza@box}}}
1096 \newcommand{\AMC@sza@callin@margin}={}
1097 %
1098 \newcommand{\AMC@sza@init@margins}{\PackageWarning{automultiplechoice}{Please run twice to get proper margin}}
1099 \newcommand{\AMC@sza@callout@margins}{\hspace{0pt}\AMCmarginNote{\AMCscoreZone{\AMC@sza@box}}}
1100 \newcommand{\AMC@sza@callin@margins}={}
1101 %
1102 \newlength\AMC@sza@width
1103 \newlength\AMC@sza@height
1104 \newlength\AMC@sza@depth
1105 \def\AMC@sza@callout={}
1106 \def\AMC@sza@callin={}
1107 \define@key{AMCsza}{width}{\AMC@sza@width=#1}
1108 \define@key{AMCsza}{height}{\AMC@sza@height=#1}
1109 \define@key{AMCsza}{depth}{\AMC@sza@depth=#1}

```

```

1110 \define@key{AMCsza}{calloutside}{\def\AMC@sza@callout{\#1}}
1111 \define@key{AMCsza}{callinside}{\def\AMC@sza@callin{\#1}}
1112 \define@choicekey{AMCsza}{position}{none,question,margin,margins}{%
1113   \ifcsname AMC@sza@callout@\#1\endcsname%
1114     \def\AMC@sza@callout{\AMC@sza@callout@\#1}%
1115   \else%
1116     \def\AMC@sza@callout{}%
1117   \fi%
1118   \ifcsname AMC@sza@callin@\#1\endcsname%
1119     \def\AMC@sza@callin{\AMC@sza@callin@\#1}%
1120   \else%
1121     \def\AMC@sza@callin{}%
1122   \fi%
1123   \ifcsname AMC@sza@init@\#1\endcsname%
1124     \csname AMC@sza@init@\#1\endcsname%
1125   \fi%
1126 }
1127 \newcommand{\AMCsetScoreZoneAnswerSheet}[1]{\setkeys{AMCsza}{#1}}
1128 \AMCsetScoreZoneAnswerSheet{width=1.5em,height=1.5ex,depth=.5ex,position=none}
1129 \newcommand{\AMCnoScoreZone}{\AMCsetScoreZone{position=none}\AMCsetScoreZoneAnswerSheet{position=none}}

```

4.11.5 Formatting questions

\AMCquestionaff The counter \AMCquestionaff keeps track of the current question number. It can be redefined by \AMC@stepQuestion the user, for example to print several questions without a number, and then print questions with a number starting at one.
 \AMC@stepQuestion will increase this counter and \AMC@qaff will format the question number out.

```

1130 \newcounter{AMCquestionaff}
1131 \newcommand{\AMCnumero}[1]{\setcounter{AMCquestionaff}{#1}\addtocounter{AMCquestionaff}{-1}}
1132 \AtBeginDocument{%
1133   \ifx\@skiphyperreftrue\@undefined%
1134     \expandafter\newif\csname if@skiphyperref\endcsname%
1135   \fi%
1136 }
1137 \newcommand{\AMC@stepQuestion}{\ifAMCquestionNumber\@skiphyperreftrue\refstepcounter{AMCquestionaff}\@skiphyperreffalse\@empty}
1138 \newcommand{\AMC@qaff}{\arabic{AMCquestionaff}}

```

\AMCbeforeQuestion The command \AMCbeforeQuestion opens a new question. The command \AMCbeginQuestion{\langle n \rangle}{\langle sign \rangle} \AMCbeginQuestion will format the question header, where \langle n \rangle is the question number and \langle sign \rangle beeing \multiSymbole in case of a multiple question, and empty in case of a simple one. \AMCbeforeQuestion, \AMCbeginQuestion and \multiSymbole can be user-redifined.

```

1139 \def\AMCbeforeQuestion{\ifAMC@qbloc\else\par\noindent\fi}
1140 \def\AMCbeginQuestion{\noindent\AMC@loc@q{\#1}{\#2}%
1141   \ifx\@empty\AMC@sz@callin\@empty\hspace*{1em}\fi%
1142 }
1143 \def\multiSymbole{$\clubsuit$}

```

question Environment \{question\}{\langle key \rangle} encloses a simple question (with one and only one correct choice) questionmult with associated unique key \langle key \rangle and the proposed answers.

variable-single
 variable-multi
 questionouverte
 \ouverte@vs

Environment `{questionmult}{<key>}` is the same for multiple questions (with none, one or several correct choices).

Environment `{questionmultx}{<key>}` is the same as `questionmult`, but with no use of `\multiSymbole`.

Environment `{questionouverte}[<width>]` is used for open questions (that won't be marked automatically!), with width given as an optional argument (defaults to 3cm).

```

1144 \ifx\question\undefined\else\let\question\undefined\fi
1145 \def\AMCnoglobloc{\AMC@qglobfalse}
1146 \def\AMCbloc{\AMC@qglobtrue}
1147 \newenvironment{question}[2][]{%
1148   \def\AMCcurrentenv{question}%
1149   \AMC@stepQuestion%
1150   \global\def\AMCid@name{\#2}\AMC@affecte{\#2}{\AMCid@quest}%
1151   \ifAMC@calibration\AMCmessage{Q=\the\AMCid@quest}\fi%
1152   \AMCbeforeQuestion%
1153   \ifx\@empty\AMC@sz@callout\@empty\else%
1154     \csname\AMC@sz@callout\endcsname%
1155   \fi%
1156   \AMCtype@multifalse\ifAMC@qglob\ifAMC@textPos\vbox\bgroup\AMC@tracepos{1}{qtext:#2:\the\AMCid@quest,0}\hbo%
1157   \ifAMC@affichekeys\index{\texttt{\#2}}\ifAMC@keysline[\texttt{\#2}]\newline\fi\fi%
1158   \AMCbeginQuestion\ifAMC@affichekeys\ifAMC@ensemble\AMC@qaff\ \fi\ifAMC@keysline\else[\texttt{\#2}]\fi\else%
1159   \ifx\@empty\AMC@sz@callin\@empty\else%
1160     \csname\AMC@sz@callin\endcsname%
1161   \fi%
1162   \AMCformulaire@dedansfalse\setcounter{AMC@ncase}{0}%
1163   \AMC@mem@openQuestion}%
1164 {\ifAMC@qglob\end{minipage}\ifAMC@textPos\AMC@tracepos{1}{qtext:\AMCid@name:\the\AMCid@quest,0}\egroup\AMC@t%
1165 \newenvironment{questionmult}[1]{%
1166   \AMCune@bonnefalse\begin{question}[\{\multiSymbole\}]\#1}%
1167   \AMCtype@multittrue\ifAMC@calibration%
1168   \AMC@amclog{AUTOQCM[MULT]^\#1}\fi}%
1169 {\end{question}}
1170 \newenvironment{variable-single}[2]
1171 {\def\AMCbeginQuestion##1##2{}%
1172 \begin{questionmult}{##1}\scoring{v=##2}%
1173 \begin{tikz-single}[o]%
1174 {\end{tikz-single}%
1175 \end{questionmult}%
1176 \newenvironment{variable-multi}[4]
1177 {\def\AMCbeginQuestion##1##2{}%
1178 \begin{questionmult}{##1}\scoring{v=##4}%
1179 \begin{tikz-multi}[o]%
1180 \node[##3] (var) at (0,0) {##2};%
1181 {\end{tikz-multi}%
1182 \end{questionmult}%
1183 \newenvironment{questionmultx}[1]{%
1184   \begingroup\def\multiSymbole{}\begin{questionmult}{##1}}%
1185 {\end{questionmult}\endgroup}%
1186 \newdimen\ouverte@vs
1187 \newenvironment{questionouverte}[1][3cm]{%

```

```

1188 \AMC@stepQuestion%
1189 \AMCtype@multifalse\ouverte@vs=#1%
1190 \ifAMC@qbloc\noindent\begin{minipage}{\linewidth}\fi%
1191 \AMCbeginQuestion{\AMC@qaff}{}%
1192 {\vspace*{\ouverte@vs}\ifAMC@qbloc\end{minipage}\vspace{3ex}\fi}

```

4.11.6 Explanations

\explain The command \explain is used inside question-like environments to give the explanation for the answers of a question.

```

1193 \newcommand{\explain}[1]{%
1194 \ifAMC@correchead%
1195 \AMCif@env{question}{\par\noindent{\AMC@loc@explain #1}}{\AMC@error@explain}\vspace{1ex}%
1196 \else%
1197 \AMCif@env{question}{}{\AMC@error@explain}%
1198 \fi%
1199 }

```

4.12 Scoring

\scoring Scoring strategies are simply transmitted to the .amc file for later analysis.

\scoringDefaultS \scoring{\langle score \rangle} details the scoring strategy for current question or current answer, \scoringDefaultS{\langle score \rangle} and \scoringDefaultM{\langle score \rangle} gives default scoring strategy for simple and multiple questions, and \QuestionIndicative tells that the current question is not no be taken into account in the global mark.

```

1200 \def\scoring#1{\ifAMC@calibration\AMC@amclog{AUTOQCM[B=#1]^^J}\fi}
1201 \def\scoringDefaultS#1{\ifAMC@calibration\AMC@amclog{AUTOQCM[BDS=#1]^^J}\fi}
1202 \def\scoringDefaultM#1{\ifAMC@calibration\AMC@amclog{AUTOQCM[BDM=#1]^^J}\fi}
1203 \def\QuestionIndicative{\ifAMC@calibration\AMC@amclog{AUTOQCM[INDIC]^^J}\fi}

```

4.13 Numerical data

4.13.1 Codes

`\AMCcodeGrid` Students can code some numerical information (such as student number) through special questions, which can be formatted easily with the command `\AMCcodeGrid[⟨opts⟩]{⟨key⟩}{⟨descr⟩}`, where `⟨key⟩` is a key prefix and `⟨descr⟩` is a coma-separated list of character pools to offer. The characters entered by the student will be available through the questions `⟨key⟩[1], …, ⟨key⟩[⟨length(descr)⟩]`.

As an example,

`\AMCcodeGrid{code}{ABCD,012345,012345,012345,012345}` produces the opposite boxes (two results are show here: without or with `separateanswersheet` option), and trace positions of all the boxes in the `.xy` file with the `code` identifier: the first digit is represented by question with key `code[6]`, the second by question with key `code[5]`, and so on.

Positions of the boxes are logged in the `.xy` file, as shown in section 5.3 for the first set of boxes (without `separateanswersheet`, with digits outside boxes).

The “horizontal” version can also be considered using option `h`, especially with a small number of digits. See opposite for the result of

`\AMCcodeGrid[h]{code}{ABCDEF,0123456789,0123456789}.`

The `\AMCcodeGridInt[⟨opts⟩]{⟨key⟩}{⟨n⟩}` is a shortcut for calling `\AMCcodeGrid` with `⟨n⟩` digits from 0 to 9. This allows to create grids for `⟨n⟩`-digits integers easily.

These two commands supports the following options (given as a comma-separated list optional argument `⟨opts⟩`):

- `vertical=true` or `false` to indicate the direction to be used (default is `true`);
- `h` is a shortcut for `vertical=false`;
- `v` is a shortcut for `vertical=true`;
- `top` to request top-aligned columns in vertical direction.

```

1204 \newcount\AMC@chiffres
1205 \newdimen\AMCcodeHspace\AMCcodeHspace=.5em
1206 \newdimen\AMCcodeVspace\AMCcodeVspace=.5em
1207 \newcommand\AMCcodeID@squarebrackets[2]{#1[#2]}
1208 \newcommand\AMCcodeID@dot[2]{#1.#2}
1209 \newcommand\AMCcodeID@@[1]{%
1210   \expandafter\def\expandafter\AMCcodeID\expandafter{\csname AMCcodeID@#1\endcsname}%
1211 }
1212 \AMCcodeID@@{squarebrackets}

```

<input type="text"/>				
<input type="text"/>				
A	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
B	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
C	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
D	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
0	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

<input type="text"/>				
<input type="text"/>				
A	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
B	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
C	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
D	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
0	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

<input type="text"/>				
<input type="text"/>				
A	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
B	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
C	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
D	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
0	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

```

1213 \ExplSyntaxOn
1214
1215 \clist_new:N \amc_code_descr_clist
1216 \seq_new:N \amc_code_digits_seq
1217 \int_new:N \amc_code_digit_n_int
1218 \bool_new:N \amc_code_vertical_bool
1219 \bool_new:N \amc_code_top_bool
1220
1221 \cs_new:Npn \amc_code_init:N #1 {
1222   \def\AMCbeginQuestion##1##2{}
1223   \def\AMCbeforeQuestion{}
1224   \AMCnoScoreZone
1225   \AMCquestionNumberfalse
1226   \setlength{\parindent}{0pt}
1227   \AMCnobloc
1228   \int_set:Nn \amc_code_digit_n_int { \clist_count:N #1 }
1229 }
1230
1231 \cs_new:Nn \amc_code_digit_init: {
1232   \QuestionIndicative
1233   \global\AMCrep@count=\z@
1234 }
1235
1236 \cs_new:Npn \amc_code_digit:n #1 {
1237   \global\advance\AMCrep@count\@ne\relax
1238   \ifAMC@calibration\AMC@amclog{AUTOQCM[ REP = \the\AMCrep@count : M ]^^J}\fi
1239   \hbox{\AMC@keyBox{#1}{}{1}{case : \AMCid@name : \the\AMCid@quest , \the\AMCrep@count}}
1240   \bool_if:NTF \amc_code_vertical_bool {
1241     \vspace{\AMCcodeVspace}
1242   }{
1243     \hspace{\AMCcodeHspace}
1244   }
1245 }
1246
1247 \keys_define:nn { amccode } {
1248   vertical .bool_set:N = \amc_code_vertical_bool,
1249   vertical .initial:n = { true },
1250   vertical .default:n = { true },
1251   v .code:n = { \bool_set_true:N \amc_code_vertical_bool },
1252   h .code:n = { \bool_set_false:N \amc_code_vertical_bool },
1253   top .bool_set:N = \amc_code_top_bool,
1254   top .initial:n = { false },
1255   top .default:n = { true }
1256 }
1257
1258 \cs_new:Npn \amc_code_generate:nNn #1#2#3 {
1259   { \keys_set:nn { amccode } { #3 }
1260     \amc_code_init:N #2
1261     \clist_map_inline:Nn #2 { % iterates over 'digits'
1262       \begin{question}{\AMCcodeID{#1}{ \int_use:N \amc_code_digit_n_int }}}

```

```

1263     \amc_code_digit_init:
1264     \seq_set_split:Nnn \amc_code_digits_seq {} { ##1 }
1265     \bool_if:NTF \amc_code_vertical_bool {
1266         \hspace{0pt}
1267         \bool_if:NTF \amc_code_top_bool { \vtop } { \vbox }
1268         \bgroup
1269     }{
1270         \hbox\bgroup
1271     }
1272     \seq_map_inline:Nn \amc_code_digits_seq {
1273         % iterates over available characters for 'digit'
1274         \amc_code_digit:n { #####1 }
1275     }
1276     \bool_if:NTF \amc_code_vertical_bool {
1277         \vspace{-\AMCcodeVspace}\egroup
1278         \hspace{\AMCcodeHspace}
1279     }{
1280         \egroup\vspace{\AMCcodeVspace}
1281         \par
1282     }
1283     \end{question}
1284     \int_decr:N \amc_code_digit_n_int
1285 }
1286 }
1287 }
1288
1289 \cs_new:Npn \amc_code_generate:nnn #1#2#3 {
1290     \clist_set:Nn \amc_code_descr_clist { #2 }
1291     \amc_code_generate:nNn { #1 } \amc_code_descr_clist { #3 }
1292 }
1293 \cs_generate_variant:Nn \amc_code_generate:nnn { xxx }
1294 \newcommand{\AMCcodeGrid}[3][]{%
1295     \amc_code_generate:xxx { #2 } { #3 } { #1 }
1296 }
1297
1298 \cs_new:Npn \amc_code_generate_integer:nnn #1#2#3 {
1299     \clist_clear:N \amc_code_descr_clist
1300     \prg_replicate:nn { #2 } { \clist_put_right:Nn \amc_code_descr_clist { 0123456789 } }
1301     \amc_code_generate:nNn { #1 } \amc_code_descr_clist { #3 }
1302 }
1303 \cs_generate_variant:Nn \amc_code_generate_integer:nnn { xxx }
1304 \newcommand{\AMCcodeGridInt}[3][]{%
1305     \amc_code_generate_integer:xxx { #2 } { #3 } { #1 }
1306 }
1307
1308 \cs_new:Npn \amc_code_generate_integer_v:nn #1#2 {
1309     \amc_code_generate_integer:nnn { #1 } { #2 } { v }
1310 }
1311 \cs_new:Npn \amc_code_generate_integer_h:nn #1#2 {
1312     \amc_code_generate_integer:nnn { #1 } { #2 } { h }

```

```

1313 }
1314 \cs_generate_variant:Nn \amc_code_generate_integer_v:nn { xx }
1315 \cs_generate_variant:Nn \amc_code_generate_integer_h:nn { xx }
1316 \cs_new_eq:NN \AMCcode \amc_code_generate_integer_v:xx
1317 \cs_new_eq:NN \AMCcodeH \amc_code_generate_integer_h:xx
1318
1319 \ExplSyntaxOff

```

4.13.2 Numerical questions

\AMCnumericChoices The command `\AMCnumericChoices{<correct>}{<options>}` can be used as a replacement for the `choices` environment when the questions asks for a numeric value to code on the answer sheet.

As an example,

```

\begin{question}{product}
    What is the value of $7\times 5$?
    \AMCnumericChoices{35}{digits=2,sign=false}
\end{question}

```

produces (in correction mode):

Question 3 What is the value of 7×5 ?									
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 3	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 5	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

and these boxes are only shown on the separate answer sheet if the `separateanswersheet` option is used.

This command uses the `\AMCformatChoices{<showcommand>}{<hidecommand>}{<arg1>}{<arg2>}` command, that calls either `<hidecommand>{<arg1>}{<arg2>}` if the `separateanswersheet` option is used and if we are currently in the question part (not in the answer sheet), or `<showcommand>{<arg1>}{<arg2>}` when all the boxes are to be produced.

```

1320 \newcommand\AMCformatChoices[4]{%
1321   \global\AMCrep@count=\z@%
1322   \AMC@if@separate@question{%
1323     \AMC@mem@add{\global\AMCrep@count=\z@}%
1324     #1{#3}{#4}}%
1325   }%
1326   \ifAMC@ensemble%
1327     #2{#3}{#4}%
1328     \AMC@amclog{AUTOQCM[QPART] ^^ J}%
1329   \else%
1330     #1{#3}{#4}%
1331   \fi%
1332 }

```

Some computation commands are now defined. The command `\amc_fp_decompose>NNn{<fp var>}{<int var>}{<x>}` sets `<fp var>` to be the *mantissa* and `<int var>` the *exponent* of the floating

point number $\langle x \rangle$. For example, `\amc_fp_decompose:Nnn\mant_fp\expo_int{123.456}` give the value 1.23456 to `\mant_fp` and 2 to `\expo_int` (because $123.456 = 1.23456 \times 10^2$).

The command `\amc_fp_to_digits:Nnnn{clist}{x}{n digits}{base}` rounds the floating point number $\langle x \rangle$ and populates the comma separated list `clist` with its $\langle n \text{ digits} \rangle$ digits in base `base`. An error is issued if $\langle x \rangle$ would have required more digits.

```
1333 \ExplSyntaxOn
1334
1335 \cs_generate_variant:Nn \tl_replace_once:Nn { Nnx }
1336
1337 \tl_new:N \amc_ee_tl
1338 \seq_new:N \amc_ee_seq
```

Note that with some versions of 13fp-convert (prior to 2017-09-18), `\fp_to_scientific` leads to a ‘e’ with catcode 12 (*other*). We convert it to catcode *letter* before splitting.

```
1339 \group_begin:
1340 \char_set_catcode_other:N E
1341 \tex_lowercase:D
1342 {
1343   \cs_new:Npn \amc_read_scientific:NNn #1 #2 #3 {
1344     \tl_set:Nn \amc_ee_tl { #3 }
1345     \tl_replace_once:Nnx \amc_ee_tl { E } { e }
1346     \seq_set_split:NnV \amc_ee_seq e \amc_ee_tl
1347     \fp_set:Nn #1 { \seq_item:Nn \amc_ee_seq 1 }
1348     \int_set:Nn #2 { \seq_item:Nn \amc_ee_seq 2 }
1349   }
1350 }
1351 \group_end:
1352
1353 \cs_generate_variant:Nn \amc_read_scientific:NNn { NNf, NNx }
1354
1355 \fp_new:N \amc_fulls_fp
1356 \cs_new:Npn \amc_fp_decompose>NNn #1 #2 #3 {
1357   \fp_set:Nn \amc_fulls_fp { #3 }
```

Note that with some versions of 13fp-convert, the exponent part is omitted for some values, so that we add e 0.

```
1358   \amc_read_scientific:NNx #1 #2
1359   { \fp_to_scientific:N \amc_fulls_fp e 0 }
1360 }
1361 \cs_generate_variant:Nn \amc_fp_decompose:NNn { NNx }
1362
1363 \fp_new:N \amc_num_mantissa_fp
1364 \int_new:N \amc_num_exponent_int
1365 \cs_new:Npn \amc_fp_n_significant_digits:Nnn #1 #2 #3 {
1366   \amc_fp_decompose>NNn \amc_num_mantissa_fp \amc_num_exponent_int
1367   { #2 }
1368   \fp_set:Nn #1
1369   { round(\amc_num_mantissa_fp * 10^{(#3)-1}) }
1370   \fp_compare:nTF { abs(#1) >= 10^{#3} }
1371   {
```

```

1372     \fp_set:Nn #1 { #1 / 10 }
1373 } { }
1374 }
1375
1376 \fp_new:N \amc_num_nsig_fp
1377 \cs_new:Npn \amc_fp_show_n_significant_digits:nn #1 #2 {
1378     \amc_fp_n_significant_digits:Nnn \amc_num_nsig_fp { #1 } { #2 }
1379 }
1380 \cs_new_eq:NN \AMCsignificantDigits \amc_fp_show_n_significant_digits:nn
1381
1382 \cs_new:Npn \amc_fp_show_significant_digits: {
1383     \fp_use:N \amc_num_nsig_fp
1384 }
1385 \cs_new_eq:NN \AMCshowSignificantDigits \amc_fp_show_significant_digits:
1386
1387 \cs_new:Npn \amc_fp_n_digits:Nnn #1 #2 #3 {
1388     \fp_set:Nn #1
1389     { round((#2) * 10^(#3)) }
1390 }
1391
1392 \int_new:N \amc_todigits_int
1393 \cs_new:Npn \amc_fp_to_digits:Nnnn #1 #2 #3 #4 {
1394     \clist_clear:N #1
1395     \int_set:Nn \amc_todigits_int { \fp_eval:n { abs(round(#2)) } }
1396     \prg_replicate:nn { #3 } {
1397         \clist_put_left:Nx #1 { \int_mod:n \amc_todigits_int { #4 } }
1398         \int_set:Nn \amc_todigits_int
1399         { \int_div_truncate:nn \amc_todigits_int { #4 } }
1400     }
1401     \int_compare:nNnTF \amc_todigits_int = 0 { } {
1402         \message{^^J!~Error:~number~too~large,
1403             ~some~digits~will~be~discarded^^J}
1404     }
1405 }
1406
1407 \cs_new:Npn \amc_invalid_digits:Nn #1 #2 {
1408     \clist_clear:N #1
1409     \prg_replicate:nn { #2 } { \clist_put_left:Nx #1 { -1 } }
1410 }
1411
1412 \cs_new:Npn \amc_get_fp_sign:Nn #1 #2 {
1413     \fp_compare:nNnTF #2 < 0 {
1414         \int_set:Nn #1 { -1 }
1415     }{
1416         \fp_compare:nNnTF #2 > 0 {
1417             \int_set:Nn #1 { 1 }
1418         }{
1419             \int_set:Nn #1 { 0 }
1420         }
1421     }

```

```

1422 }
1423
1424 \cs_new:Npn \amc_get_int_sign:Nn #1 #2 {
1425   \int_compare:nNnTF #2 < 0 {
1426     \int_set:Nn #1 { -1 }
1427   }{
1428     \int_compare:nNnTF #2 > 0 {
1429       \int_set:Nn #1 { 1 }
1430     }{
1431       \int_set:Nn #1 { 0 }
1432     }
1433   }
1434 }
1435
1436 \ExplSyntaxOff

```

The command `\AMCnumericShow{<value>}{<opts>}` is called to draw all necessary boxes to code a numerical value `<value>` with options given as a comma separated list `<opts>`. `\AMCnumericOpts{<opts>}` can be used to set some default values for these options.

Begin with the available options:

```

1437 \def\AMCncontextGoto{}
1438 \def\AMCncontextVHead#1{\emph{b#1}}
1439 \newdimen\AMCnumeric@Hspace\AMCnumeric@Hspace=.5em
1440 \newdimen\AMCnumeric@Vspace\AMCnumeric@Vspace=1ex
1441 \ExplSyntaxOn
1442
1443 \keys_define:nn { amcnumeric } {
1444   Tsign .code:n = {\def\AMCncontextSign{#1}},
1445   Tsign .initial:n = {},
1446   Tpoint .code:n = {\def\AMCdecimalPoint{#1}},
1447   Tpoint .initial:n = { \raisebox{1ex}{\bf .} },
1448   Texponent .code:n = {\def\AMCexponent{#1}},
1449   Texponent .initial:n = { $\times 10^{\text{asciicircum}} },
1450   vspace .code:n = {\AMCnumeric@Vspace=#1},
1451   hspace .code:n = {\AMCnumeric@Hspace=#1},
1452   bordercol .code:n = {\def\AMCncol@Border{#1}},
1453   bordercol .initial:n = { lightgray },
1454   borderwidth .code:n = {\def\AMCncol@BorderWidth{#1}},
1455   borderwidth .initial:n = { 1mm },
1456   backgroundcol .code:n = {\def\AMCncol@Background{#1}},
1457   backgroundcol .initial:n = { white },
1458   digits .int_set:N = \amc_num_ndigits_int,
1459   digits .initial:n = { 3 },
1460   decimals .int_set:N = \amc_num_decd_int,
1461   decimals .initial:n = { 0 },
1462   exponent .int_set:N = \amc_num_expo_int,
1463   exponent .initial:n = { 0 },
1464   base .int_set:N = \amc_num_base_int,
1465   base .initial:n = { 10 },
1466   sign .bool_set:N = \amc_num_sign_bool,

```

```

1467 sign .initial:n = { true },
1468 sign .default:n = { true },
1469 exposign .bool_set:N = \amc_num_exposign_bool,
1470 exposign .initial:n = { true },
1471 exposign .default:n = { true },
1472 strict .bool_set:N = \amc_num_strict_bool,
1473 strict .initial:n = { false },
1474 strict .default:n = { true },
1475 scoring .bool_set:N = \amc_num_scoring_bool,
1476 scoring .initial:n = { true },
1477 scoring .default:n = { true },
1478 vertical .bool_set:N = \amc_num_vertical_bool,
1479 vertical .initial:n = { false },
1480 vertical .default:n = { true },
1481 expovertical .bool_set:N = \amc_num_expovertical_bool,
1482 expovertical .initial:n = { false },
1483 expovertical .default:n = { true },
1484 reverse .bool_set:N = \amc_num_reverse_bool,
1485 reverse .initial:n = { false },
1486 reverse .default:n = { true },
1487 vhead .bool_set:N = \amc_num_vhead_bool,
1488 vhead .initial:n = { false },
1489 vhead .default:n = { true },
1490 nonzero .bool_set:N = \amc_num_nonzero_bool,
1491 nonzero .initial:n = { false },
1492 nonzero .default:n = { true },
1493 significant .bool_set:N = \amc_num_significant_bool,
1494 significant .initial:n = { false },
1495 significant .default:n = { true },
1496 scoreexact .code:n = {\def\AMC@numeric@scoreexact{\#1}},
1497 scoreexact .initial:n = { 2 },
1498 scoreapprox .code:n = {\def\AMC@numeric@scoreapprox{\#1}},
1499 scoreapprox .initial:n = { 1 },
1500 scorewrong .code:n = {\def\AMC@numeric@scorewrong{\#1}},
1501 scorewrong .initial:n = { 0 },
1502 exact .int_set:N = \amc_num_exact_int,
1503 exact .initial:n = { 0 },
1504 approx .int_set:N = \amc_num_approx_int,
1505 approx .initial:n = { 0 },
1506 keepas .code:n = {\def\AMC@numeric@keepas{\#1}},
1507 keepas .initial:n = {},
1508 alsocorrect .code:n = {\def\AMC@numeric@alsocorrect{\#1}},
1509 alsocorrect .initial:n = {}
1510 }
1511
1512 \cs_new:Npn \amc_num_setopts #1 {
1513   \keys_set:nn { amcnumeric } { #1 }
1514 }
1515
1516 \cs_new_eq:NN \AMCnumeric0pts \amc_num_setopts

```

1517

The command `\amc_num_char:nn{<inside>}{<answer>}` draw a box with content `<inside>` (only if needed), where `<answer>` is `\AMC@checkbox` if the corresponding choice is correct and empty if not.

```
1518 \cs_new:Npn \amc_num_char:nn #1 #2 {
1519   \global\advance\AMCrep@count\@ne\relax
1520   \AMC@amclog{AUTOQCM[REP= \the\AMCrep@count :
1521     \ifx#2\AMC@checkbox B\else M\fi ]^^J}
1522   \ifAMC@correc
1523     \protect\AMC@keyBox@{#1}{#2}{1}{case : \AMCid@name :
1524       \the\AMCid@quest , \the\AMCrep@count}
1525   \else
1526     \protect\AMC@keyBox@{#1}{}{1}{case : \AMCid@name :
1527       \the\AMCid@quest , \the\AMCrep@count}
1528   \fi
1529 }
```

The command `\amc_num_digit_box:nn{<i>}{{<j>}}` draws a box for current digit value `<i>`, where `<j>` is the correct value for the current digit. If `<i>` is greater than 9, it is converted to a character from the English alphabet (A for 10, B for 11...)

```
1530 \int_new:N \amc_num_digit_value_int
1531 \tl_new:N \amc_num_digit_value_tl
1532 \cs_new:Npn \amc_num_digit_box:nn #1 #2 {
1533   \int_set:Nn \amc_num_digit_value_int { #1 }
1534   \tl_set:Nn \amc_num_digit_value_tl {
1535     \int_compare:nNnTF { \amc_num_digit_value_int } < { 10 }
1536     { \int_to_arabic:n { \amc_num_digit_value_int } }
1537     { \int_to_Alph:n { \amc_num_digit_value_int - 9 } }
1538   }
1539   \int_compare:nNnTF { #1 } = { #2 } {
1540     \amc_num_char:nn{ \tl_use:N \amc_num_digit_value_tl }
1541           {\AMC@checkbox}
1542   } {
1543     \amc_num_char:nn{ \tl_use:N \amc_num_digit_value_tl }
1544           {}
1545   }
1546 }
```

The command `\amc_num_sign_boxes:Nn{<sign>}{<prefix>}` draws two boxes for the students to code the sign (with a right value given by the boolean `<negative>`).

```
1547 \cs_new:Npn \amc_num_sign_boxes:Nn #1 #2 {
1548   \int_case:nn { #1 } {
1549     { -1 } {
1550       \hbox{\amc_num_char:nn{$+$}{$-$}}
1551       \vspace{\AMCnumeric@Vspace}
1552       \AMC@amclog{AUTOQCM[B=set. sign #2 =1]^^J}
1553       \hbox{\amc_num_char:nn{$-$}{$-$}\{\AMC@checkbox\}}
1554       \AMC@amclog{AUTOQCM[B=set. sign #2 =-1]^^J}
1555     }
1556     { 1 } {
```

```

1557 \hbox{\amc_num_char:nn{$+$}{\AMC@checkbox}}
1558 \vspace{\AMCnumeric@Vspace}
1559 \AMC@amclog{AUTOQCM[B=set. sign #2 =1]^^J}
1560 \hbox{\amc_num_char:nn{$-$}{}}
```

```

1561 \AMC@amclog{AUTOQCM[B=set. sign #2 =-1]^^J}
1562 }
1563 { 0 } {
1564 \hbox{\amc_num_char:nn{$+$}{}}
```

```

1565 \vspace{\AMCnumeric@Vspace}
1566 \AMC@amclog{AUTOQCM[B=set. sign #2 =1]^^J}
1567 \hbox{\amc_num_char:nn{$-$}{}}
```

```

1568 \AMC@amclog{AUTOQCM[B=set. sign #2 =-1]^^J}
1569 }
1570 }
1571 }
```

The command `\amc_num_digit_boxes_h:nnn{<varname>}{{<correct>}}{<maxdigit>}` draws a serie of boxes for all possible values of a digit (from 0 to `<maxdigit>`), where the correct value is `<correct>`, transmitting scoring data to AMC so that the variable `<varname>` will be set to the value chosen by the student.

```

1572 \cs_new:Npn \amc_num_digit_boxes_h:nnn #1 #2 #3 {
1573   \int_step_inline:nnnn
1574   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1575   { 1 } { #3 - 1 } {
1576     \amc_num_digit_box:nn { ##1 }{ ##2 }
1577     \AMC@amclog{AUTOQCM[B= set. #1 = ##1 ]^^J}
1578     \hspace{\AMCnumeric@Hspace}
1579   }
1580   \hspace{-\AMCnumeric@Hspace}
1581 }
1582
1583 \cs_new:Npn \amc_num_digit_boxes_v:nnn #1 #2 #3 {
1584   \int_step_inline:nnnn
1585   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1586   { 1 } { #3 - 1 } {
1587     \vbox{\hbox{
1588       \amc_num_digit_box:nn { ##1 }{ ##2 }
1589     }}
1590     \AMC@amclog{AUTOQCM[B= set. #1 = ##1 ]^^J}
1591     \int_compare:nNnTF { ##1 } < { #3 - 1 } {
1592       \vspace{\AMCnumeric@Vspace}
1593     } {}
1594   }
1595 }
1596
1597 \int_new:N \amc_num_first_digit_int
1598 \cs_new:Npn \amc_num_digit_boxes_vr:nnn #1 #2 #3 {
1599   \int_set:Nn \amc_num_first_digit_int
1600   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1601   \int_step_inline:nnnn { #3 - 1 } { -1 }
```

```

1602 \amc_num_first_digit_int {
1603   \vbox{\hbox{
1604     \amc_num_digit_box:nn { ##1 }{ ##2 }
1605   }}
1606 \AMC@amclog{AUTOQCM[B= set. #1 = ##1 ]^^J}
1607 \int_compare:nNnTF { ##1 } > \amc_num_first_digit_int {
1608   \vspace{\AMCnumeric@Vspace}
1609 } {}
1610 }
1611 }

```

The command `\amc_num_integer_boxes_v:Nnn{<correct digits>}{<prefix>}{<decimals>}` draws boxes for integer entry, without the sign.

```

1612 \cs_new:Npn \amc_num_integer_boxes_v:Nnn #1 #2 #3 {
  begin a loop over all digits,
1613   \int_set_eq:NN \amc_num_digit_int { \clist_count:N #1 }
1614   \clist_map_inline:Nn #1 {
    place the decimal point if necessary,
1615     \int_compare:nNnTF \amc_num_digit_int = { #3 } {
1616       \hbox{ \AMCdecimalPoint }\hspace{\AMCnumeric@Hspace}
1617     } {}
    draw the box for this digit,
1618     \hbox{\vbox{
1619       \bool_if:NTF \amc_num_vhead_bool {
1620         \vbox{\hbox{\AMCtextVHead{ \int_eval:n
1621           { \amc_num_digit_int - 1 } }}}}
1622         \vspace{\AMCnumeric@Vspace}
1623       } {}
1624       \bool_if:NTF \amc_num_reverse_bool {
1625         \amc_num_digit_boxes_vr:nnn { #2
1626           \int_to_Alph:n \amc_num_digit_int }
1627         { ##1 } { \amc_num_base_int }
1628       } {}
1629         \amc_num_digit_boxes_v:nnn { #2
1630           \int_to_Alph:n \amc_num_digit_int }
1631         { ##1 } { \amc_num_base_int }
1632       } {}
1633     } {}

```

and end the loop over digits, adding space if this is not the last one.

```

1634   \int_compare:nNnTF \amc_num_digit_int > 1 {
1635     \hspace{\AMCnumeric@Hspace}
1636   } {}
1637   \int_decr:N \amc_num_digit_int
1638 }
1639 }
1640

```

The command `\amc_num_integer_boxes_h:Nnn{<correct digits>}{<prefix>}{<decimals>}` does the same, in horizontal mode.

```

1641
1642 \cs_new:Npn \amc_num_integer_boxes_h:Nnn #1 #2 #3 {
1643   \vbox{
1644     \int_set_eq:NN \amc_num_digit_int { \clist_count:N #1 }
1645     \clist_map_inline:Nn #1 {
1646       \int_compare:nNnTF
1647         \amc_num_digit_int = { #3 } {
1648           \hbox{ \AMCdecimalPoint }
1649         } { }
1650       \hbox{
1651         \amc_num_digit_boxes_h:nnn { #2
1652           \int_to_Alph:n \amc_num_digit_int }
1653           { ##1 } \amc_num_base_int
1654         }
1655       \int_compare:nNnTF \amc_num_digit_int > 1 {
1656         \vspace{\AMCnumeric@Vspace}
1657       } { }
1658       \int_decr:N \amc_num_digit_int
1659     }
1660   }
1661
Finally, \amc_num_integer_boxes:NnnNN{<correct digits>}{<prefix>}{<decimals>}{<sign bool>}{<sign>}
draws boxes for integer entry, including the sign if <sign bool> is true.

```

```

1662
1663 \cs_new:Npn \amc_num_integer_boxes:NnnNN #1 #2 #3 #4 #5 {
1664   \hbox{
1665     \bool_if:NTF { #4 } {
1666       \vbox{
1667         \ifx\AMCtextSign\empty\empty\else
1668           \hbox{\AMCtextSign}\vspace{\AMCnumeric@Vspace}\fi
1669           \amc_num_sign_boxes:Nn { #5 } { #2 }
1670         }
1671       \hskip.5em
1672       \vrule
1673       \hskip.5em
1674     } { }
1675   \hbox{
1676     \bool_if:NTF \amc_num_vertical_bool
1677       \amc_num_integer_boxes_v:Nnn \amc_num_integer_boxes_h:Nnn
1678       #1 { #2 } { #3 }
1679     }
1680   }
1681 }
1682

```

The command \amc_num_build_integer_scoring:Nnnn{<tl var>}{<sign bool>}{<prefix>}{<n>} builds a scoring to compute an integer from a serie of <n>-digits boxes, with name prefix <prefix>, using a sign variable if <sign bool> is true.

```

1683
1684 \cs_new:Npn \amc_num_build_integer_scoring:Nnnn #1 #2 #3 #4 {

```

```

1685 \tl_clear:N #1
1686 \int_set_eq:NN \amc_num_digit_int { #4 }
1687 \int_while_do:nNnn \amc_num_digit_int > 0 {
1688     \bool_if:NTF \amc_num.strict_bool {
1689         \AMC@amclog{AUTOQCM[B=requires. #3
1690             \int_to_Alph:n \amc_num_digit_int = 1]^^J}
1691     } {
1692         \AMC@amclog{AUTOQCM[B=default. #3
1693             \int_to_Alph:n \amc_num_digit_int = 0]^^J}
1694     }
1695     \int_compare:nNnTF \amc_num_digit_int = #4 { } {
1696         \tl_put_left:Nn #1 { ( }
1697         \tl_put_right:Nx #1 { ) *
1698             \int_use:N \amc_num_base_int + }
1699     }
1700     \tl_put_right:Nx #1
1701     { #3 \int_to_Alph:n \amc_num_digit_int }
1702     \int_decr:N \amc_num_digit_int
1703 }
1704 \tl_put_left:Nn #1 { ( }
1705 \tl_put_right:Nn #1 { ) }
1706 \bool_if:NTF { #2 } {
1707     \bool_if:NTF \amc_num.strict_bool {
1708         \AMC@amclog{AUTOQCM[B=requires. sign #3 =1]^^J}
1709     } {
1710         \AMC@amclog{AUTOQCM[B=default. sign #3 =1]^^J}
1711     }
1712     \tl_put_right:Nx #1 { * ( sign #3 ) }
1713 } { }
1714 }
1715

```

Then the command `\AMCnumericShow{x}{{options}}` itself:

```

1716
1717 \fp_new:N \amc_num_result_fp
1718 \fp_new:N \amc_num_correct_fp
1719 \clist_new:N \amc_num_digits_clist
1720 \clist_new:N \amc_num_expo_digits_clist
1721 \int_new:N \amc_num_digit_int
1722 \int_new:N \amc_num_sign_int
1723 \int_new:N \amc_num_expo_sign_int
1724 \tl_new:N \amc_num_compute_tl
1725 \tl_new:N \amc_num_expo_tl
1726 \int_new:N \amc_num_correct_expo_int
1727
1728 \cs_new:Npn \amc_numeric_show:nn #1 #2 {

```

We have to tell AMC that the scoring we will give concerns this question:

```

1729 \ifAMC@ensemble\ifAMCformulaire@dedans
1730     \AMC@amclog{AUTOQCM[Q=\the\AMCid@quest]^^J}
1731 \fi\fi

```

Then we parse the options from $\langle opts \rangle$:

```

1732  {\keys_set:nn { amcnumeric } { #2 }
1733    \bool_if:nTF { \bool_if_p:N\amc_num_significant_bool
1734      && \int_compare_p:n { \amc_num_base_int != 10 } } {
1735        \message{^^J!~AMCnumeric~Error:~significant=true~can't~be~used~with~base!=10.^^J}
1736    } {}
1737    \bool_if:nTF { \int_compare_p:n { \amc_num_expo_int != 0 } 
1738      && \int_compare_p:n { \amc_num_base_int != 10 } } {
1739        \message{^^J!~AMCnumeric~Error:~scientific~notation~can't~be~used~with~base!=10.^^J}
1740    } {}

```

Convert the floating point correct value to integer, taking into account the parameters **significant**, **exponent** and **decimals**:

```

1741  \ifx\@empty#1\@empty
1742    \fp_set:Nn \amc_num_correct_fp { 0 }
1743    \fp_set:Nn \amc_num_mantissa_fp { 0 }
1744    \int_set:Nn \amc_num_correct_expo_int { 0 }
1745  \else
1746    \bool_if:NTF \amc_num_significant_bool {
1747      \amc_fp_n_significant_digits:Nnn \amc_num_correct_fp { #1 } \amc_num_ndigits_int
1748    } {
1749      \int_compare:nNnTF \amc_num_expo_int > 0 {
1750        \amc_fp_decompose:NNn \amc_num_mantissa_fp \amc_num_correct_expo_int { #1 }
1751        \int_compare:nNnTF { \amc_num_ndigits_int - \amc_num_decd_int } > 1 {
1752          \fp_set:Nn \amc_num_mantissa_fp {
1753            \amc_num_mantissa_fp * 10^( \amc_num_ndigits_int - \amc_num_decd_int - 1 )
1754          }
1755          \int_set:Nn \amc_num_correct_expo_int {
1756            \amc_num_correct_expo_int - ( \amc_num_ndigits_int - \amc_num_decd_int - 1 )
1757          }
1758        } {}
1759        \amc_fp_n_digits:Nnn \amc_num_correct_fp \amc_num_mantissa_fp \amc_num_decd_int
1760      } {
1761        \amc_fp_n_digits:Nnn \amc_num_correct_fp { #1 } \amc_num_decd_int
1762      }
1763    }
1764  \fi

```

Now extracts the required digits:

```

1765  \ifx\@empty#1\@empty
1766    \amc_invalid_digits:Nn \amc_num_digits_clist \amc_num_ndigits_int
1767    \amc_invalid_digits:Nn \amc_num_expo_digits_clist \amc_num_expo_int
1768    \int_set:Nn \amc_num_sign_int { 0 }
1769    \int_set:Nn \amc_num_expo_sign_int { 0 }
1770  \else
1771    \amc_fp_to_digits:Nnnn \amc_num_digits_clist \amc_num_correct_fp
1772      \amc_num_ndigits_int \amc_num_base_int
1773    \amc_get_fp_sign:Nn \amc_num_sign_int \amc_num_correct_fp
1774    \int_compare:nNnTF \amc_num_expo_int > 0 {
1775      \amc_fp_to_digits:Nnnn \amc_num_expo_digits_clist \amc_num_correct_expo_int
1776      \amc_num_expo_int \amc_num_base_int

```

```

1777      \amc_get_int_sign:Nn \amc_num_expo_sign_int \amc_num_correct_expo_int
1778  } {}
1779 \fi

The question scoring is given to AMC (if requested by the scoring=true option). Note that the variable intV refers to the correct value, and intX to the value entered by the student.

1780 \fp_set:Nn \amc_num_result_fp { #1 }
1781 \AMC@amclog{AUTOQCM[B=numval=\fp_to_scientific:N \amc_num_result_fp ,
1782   numex=\int_use:N \amc_num_exact_int,
1783   numapp=\int_use:N \amc_num_approx_int,
1784   numsex=\AMC@numeric@scoreexact,
1785   numsapp=\AMC@numeric@scoreapprox
1786 ]}
1787 \bool_if:NTF \amc_num_scoring_bool {
1788   \AMC@amclog{AUTOQCM[B=haut,,mz=,
1789     formula=(Vdifference <= \int_use:N \amc_num_exact_int ?
1790       \AMC@numeric@scoreexact :
1791       \int_compare:nNnTF \amc_num_approx_int = 0 {
1792         \AMC@numeric@scorewrong
1793       } {
1794         (Vdifference <= \int_use:N\amc_num_approx_int ?
1795           \AMC@numeric@scoreapprox : \AMC@numeric@scorewrong)
1796         }
1797       )]^^J}
1798 } {}
1799 \amc_num_build_integer_scoring:Nnnn
1800   \amc_num_compute_tl \amc_num_sign_bool { digit } \amc_num_ndigits_int
1801 \int_compare:nNnTF \amc_num_expo_int > 0 {
1802   \amc_num_build_integer_scoring:Nnnn
1803   \amc_num_expo_tl \amc_num_exposign_bool { expo } \amc_num_expo_int
1804   \AMC@amclog{AUTOQCM[B= set. intE = \amc_num_expo_tl ]^^J}
1805 } {}
1806 \AMC@amclog{AUTOQCM[B= set.intV = \fp_to_int:N\amc_num_correct_fp ,
1807   set.intXX = \amc_num_compute_tl ]^^J}
1808 \int_compare:nNnTF \amc_num_expo_int > 0 {
1809   \AMC@amclog{AUTOQCM[B= set.intX = intXX * \int_use:N\amc_num_base_int **( intE - (\int_use:N\amc_num_co
1810 }{
1811   \AMC@amclog{AUTOQCM[B= set.intX = intXX]^^J}
1812 }
1813 \int_compare:nNnTF \amc_num_expo_int > 0 {
1814   \AMC@amclog{AUTOQCM[B= set.valueX = intXX * \int_use:N\amc_num_base_int ** (intE - \int_use:N\amc_num_d
1815 }{
1816   \AMC@amclog{AUTOQCM[B= set.valueX = intXX * \int_use:N\amc_num_base_int ** (- \int_use:N\amc_num_decd_i
1817 }
1818 \ifx\@empty\AMC@numeric@keepas\@empty\else
1819 \AMC@amclog{AUTOQCM[B= setglobal.\AMC@numeric@keepas = valueX ]^^J}
1820 \fi
1821 \ifx\@empty\@empty\@empty
1822 \bool_if:NTF \amc_num_significant_bool {
1823   \AMC@amclog{AUTOQCM[B=set.Vdifference=0]^^J}
1824 }{

```

```

1825   \ifx\@empty\AMC@numeric@alsocorrect\@empty
1826     \AMC@amclog{AUTOQCM[B=set.Vdifference=0]^^J}
1827   \else
1828     \AMC@amclog{AUTOQCM[B="set.Vdifference =
1829       amcvdifference( \AMC@numeric@alsocorrect, valueX, \int_use:N\amc_num_decd_int, \int_use:N\amc_num_e
1830       "]^^J}
1831   \fi
1832 }
1833 \else
1834 \bool_if:NTF \amc_num_significant_bool {
1835   \AMC@amclog{AUTOQCM[B=set.Vdifference="min( abs((intV)-(intX)) ,
1836     abs(\int_use:N\amc_num_base_int * (intV) - (intX)) ,
1837     abs((intV) - \int_use:N\amc_num_base_int * (intX)) )" ]^^J}
1838 } {
1839   \ifx\@empty\AMC@numeric@alsocorrect\@empty
1840     \AMC@amclog{AUTOQCM[B=set.Vdifference=abs((intV)-(intX))]^^J}
1841   \else
1842     \AMC@amclog{AUTOQCM[B="set.Vdifference =
1843       min( amcvdifference( \AMC@numeric@alsocorrect, valueX, \int_use:N\amc_num_decd_int, \int_use:N\amc_num
1844       abs((intV)-(intX)) )" ]^^J}
1845   \fi
1846 }
1847 \fi

```

Begin now with the frame around all the boxes:

```

1848 \ifAMC@extractOnly\else
1849 \vspace{1.5ex}\par{
1850   \fboxrule=\AMCncl@BorderWidth
1851   \fcolorbox{\AMCncl@Border}{\AMCncl@Background}{
1852     \bool_if:NTF \amc_num_expovertical_bool {
1853       \hbox{\vbox{
1854         \vbox{\amc_num_integer_boxes:NnnNN
1855           \amc_num_digits_clist { digit } \amc_num_decd_int \amc_num_sign_bool
1856           \amc_num_sign_int
1857           \int_compare:nNnTF \amc_num_expo_int > 0 {
1858             \vspace{\AMCnumeric@Vspace}
1859             \vbox{\hbox{\AMCexponent}}
1860             \vspace{\AMCnumeric@Vspace}
1861             \vbox{\amc_num_integer_boxes:NnnNN
1862               \amc_num_expo_digits_clist { expo } { 0 } \amc_num_exposign_bool
1863               \amc_num_expo_sign_int
1864             } {}
1865           } }
1866     } {
1867       \amc_num_integer_boxes:NnnNN
1868       \amc_num_digits_clist { digit } \amc_num_decd_int \amc_num_sign_bool
1869       \amc_num_sign_int
1870       \int_compare:nNnTF \amc_num_expo_int > 0 {
1871         \hspace{\AMCnumeric@Hspace}\AMCexponent\hspace{\AMCnumeric@Hspace}
1872         \amc_num_integer_boxes:NnnNN
1873         \amc_num_expo_digits_clist { expo } { 0 } \amc_num_exposign_bool

```

```

1874         \amc_num_expo_sign_int
1875     } {}
1876   }
1877 }
1878 }
1879 \fi

```

And tell AMC that we finished with this question:

```

1880 \ifAMC@ensemble\else\vspace{1.5ex}\par\fi
1881 \ifAMC@ensemble\ifAMCformulaire@dedans
1882   \AMC@amclog{AUTOQCM[FQ]^^J}
1883 \fi\fi
1884 }
1885 }
1886
1887 \cs_new_eq:NN \AMCnumericShow \amc_numeric_show:nn
1888

```

`\AMCnumericHide` is called when the boxes are not to be drawn (in the question sheets for separate answer sheet layout), and `\AMCnumericChoices{<value>}{<options>}` is the function to be used in the LaTeX source code of the exam.

```

1889 \cs_new:Npn \amc_numeric_hide:nn #1 #2 {
1890   \keys_set:nn { amcnumeric } { #2 }
1891   \AMCtextGoto
1892   \ifAMC@qbloc\else\vspace{1.5ex}\par\fi
1893 }
1894
1895 \cs_new_eq:NN \AMCnumericHide \amc_numeric_hide:nn
1896
1897 \ExplSyntaxOff
1898 \def\AMCnumericChoicesPlain{%
1899   \AMC@if@separate@question{\AMC@mem@category{numeric}}%
1900   \AMCformatChoices{\AMCnumericShow}{\AMCnumericHide}%
1901 }

```

The `{<value>}` argument is often given as a macro, that is to be expanded before calling `\AMCnumericChoicesPlain`, so that its value will be the same in the separate answer sheet...

```

1902 \ExplSyntaxOn
1903
1904 \cs_new:Npn \amc_numeric_choices:nn #1#2 {
1905   \AMCnumericChoicesPlain{#1}{#2}
1906 }
1907 \cs_generate_variant:Nn \amc_numeric_choices:nn { xn }
1908 \cs_new_eq:NN \AMCnumericChoices \amc_numeric_choices:xn
1909
1910 \ExplSyntaxOff

```

4.13.3 Intervals

\AMCIntervals The command `\AMCIntervals{<x>}{<x0>}{<x1>}{<delta>}` can be used to present answers as intervals $[x_i, x_i + \delta]$ covering $[\langle x0 \rangle, \langle x1 \rangle]$, such that the only interval containing $\langle x \rangle$ is declared as

`\correctchoice`, and the other as `\wrongchoice`.

For this command to work, one has to load package fp.

As an example,

```
\begin{question}{quarter}
  In which interval falls $1/4$?
  \begin{multicols}{5}
    \begin{choices}[o]
      \AMCIntervals{0.25}{0}{1}{0.1}
    \end{choices}
  \end{multicols}
\end{question}
```

produces (in correction mode):

Question 4 In which interval falls 1/4?

- | | | | | |
|-------------------------------------|--|-------------------------------------|-------------------------------------|-------------------------------------|
| <input type="checkbox"/> [0, 0.1[| <input checked="" type="checkbox"/> [0.2, 0.3[| <input type="checkbox"/> [0.4, 0.5[| <input type="checkbox"/> [0.6, 0.7[| <input type="checkbox"/> [0.8, 0.9[|
| <input type="checkbox"/> [0.1, 0.2[| <input type="checkbox"/> [0.3, 0.4[| <input type="checkbox"/> [0.5, 0.6[| <input type="checkbox"/> [0.7, 0.8[| <input type="checkbox"/> [0.9, 1[|

Note that the interval formatting can be changed redefining the `\AMCintervalFormat` command, which is originally defined as

```
1911 \def\AMCintervalFormat#1#2{[#1,\,#2[]}
```

to follow local conventions (writing $[a, b)$ instead of $[a, b[$ is for example a common usage).

```
1912 \ExplSyntaxOn
```

```
1913
```

```
1914 \fp_new:N \amc_interv_a
1915 \fp_new:N \amc_interv_b
1916 \cs_new:Npn \amc_intervals:nnnn #1 #2 #3 #4 {
  1917   \fp_set:Nn \amc_interv_a { #2 }
  1918   \fp_do_while:nn { \amc_interv_a < #3 } {
    1919     \fp_set:Nn \amc_interv_b { \amc_interv_a + #4 }
    1920     \fp_compare:nTF { \amc_interv_a <= #1 < \amc_interv_b }
      1921       \correctchoice \wrongchoice
    1922     {\AMCintervalFormat{\fp_use:N \amc_interv_a}{\fp_use:N \amc_interv_b}}
    1923     \fp_set:Nn \amc_interv_a \amc_interv_b
  1924   }
  1925 }
1926 \cs_new_eq:NN \AMCIntervals \amc_intervals:nnnn
1927
1928 \ExplSyntaxOff
```

4.14 Open questions

`\AMCopen` The command `\AMCopen{options}{choices}` can be used as a replacement for the `choices` environment when asking the student to write some answer by hand. The teacher will correct and mark this answer either on the paper before scanning, or with manual data capture, thanks to the scoring boxes.

As an example,

```
\begin{question}{Linux}
    What is the first name of the person who started working on the Linux kernel?
    \AMCOpen{}\wrongchoice[w]{w}\scoring{0}\correctchoice[c]{c}\scoring{2}}
\end{question}
```

shows:

Question 5 What is the first name of the person who started working on the Linux kernel?	<input type="checkbox"/> w <input type="checkbox"/> c
<div style="border: 1px solid black; height: 100%; width: 100%;"></div> <div style="text-align: center; margin-top: 5px;">.....</div>	

The teacher will have to tick the ‘w’ box for wrong answers, and the ‘c’ box for correct answers.

Begin with the options definitions:

```
1929 \def\AMCotextGoto{}
1930 \def\AMCotextReserved{}
1931 \def\AMCocol@Background{lightgray}
1932 \def\AMCocol@BoxFrameRule{white}
1933 \def\AMCocol@FrameRule{black}
1934 \def\AMCocol@Foreground{}
1935 \def\AMCopen@answer{}
1936 \def\AMCopen@question{}
1937 \def\AMCopen@lineuptext{}
1938 \define@key{AMCOpen}{backgroundcol}{\def\AMCocol@Background{\#1}}
1939 \define@key{AMCOpen}{foregroundcol}{\def\AMCocol@Foreground{\#1}}
1940 \define@key{AMCOpen}{Treserved}{\def\AMCotextReserved{\#1}}
1941 \define@key{AMCOpen}{question}{[\AMCid@name]{\def\AMCopen@question{\#1}}}
1942 \define@key{AMCOpen}{answer}{\def\AMCopen@answer{\#1}}
1943 \define@key{AMCOpen}{contentcommand}{[AMCopen@lines]{\def\AMCopen@contentcommand{\#1}}}
1944 \newdimen\AMCopen@Hspace\AMCopen@Hspace=.5em
1945 \define@key{AMCOpen}{hspace}{\AMCopen@Hspace=\#1}
1946 \def\AMCopen@Width{.95\linewidth}
1947 \define@key{AMCOpen}{width}{\def\AMCopen@Width{\#1}}
1948 \newdimen\AMCopen@LineHeight\AMCopen@LineHeight=1cm
1949 \define@key{AMCOpen}{lineheight}{\AMCopen@LineHeight=\#1}
1950 \newcount\AMCopen@Lines\AMCopen@Lines=1
1951 \define@key{AMCOpen}{lines}{\AMCopen@Lines=\#1}
1952 \newdimen\AMCopen@boxmargin\AMCopen@boxmargin=3pt
1953 \define@key{AMCOpen}{boxmargin}{\AMCopen@boxmargin=\#1}
1954 \newdimen\AMCopen@boxframerule\AMCopen@boxframerule=1pt
1955 \define@key{AMCOpen}{boxframerule}{\AMCopen@boxframerule=\#1}
1956 \define@key{AMCOpen}{boxframerulecol}{\def\AMCocol@BoxFrameRule{\#1}}
1957 \define@key{AMCOpen}{framerulecol}{\def\AMCocol@FrameRule{\#1}}
1958 \newdimen\AMCopen@framerule\AMCopen@framerule=1pt
1959 \define@key{AMCOpen}{framerule}{\AMCopen@framerule=\#1}
1960 \define@key{AMCOpen}{lineuptext}{\def\AMCopen@lineuptext{\#1}}
```

```

1961 \define@boolkey{AMCOpen}{dots}[true]{}
1962 \define@boolkey{AMCOpen}{scan}[true]{}
1963 \define@boolkey{AMCOpen}{annotate}[false]{}
1964 \define@boolkey{AMCOpen}{lineup}[false]{}
1965 \setkeys{AMCOpen}{dots,scan,annotate,lineup,contentcommand}
1966 \newcommand\AMCopenOpts[1]{\setkeys{AMCOpen}{#1}}
The command \AMCopen is similar to \AMCnumericChoices, calling either \AMCopenShow or
\AMCopenHide.
1967 \newcommand\AMCopen@lines{%
1968   \begin{minipage}{\AMCopen@Width}%
1969     \loop\vspace{\AMCopen@LineHeight}%
1970     \hspace*{.5em}\ifAMC@correc\smash{\AMCopen@answer}\def\AMCopen@answer{}\\fi%
1971     \ifKV@AMCOpen@dots%
1972       \dotfill\hspace*{.5em}%
1973     \\fi%
1974     \ifnum\AMCopen@Lines>\\one\\par\advance\AMCopen@Lines\\m@ne\\repeat%
1975   \end{minipage}%
1976 }%
1977 \newcommand\AMCopenShow[2]{%
1978   \ifAMC@ensemble\ifAMCformulaire@dedans%
1979     \AMC@amclog{AUTOQCM[Q=\\the\\AMCid@quest]^{\\J}}%
1980   \\fi\\fi%
1981   {\\setkeys{AMCOpen}{#1}%
1982     \\ifKV@AMCOpen@lineup%
1983     \\ifAMC@ensemble\\else%
1984       \\ifx\\empty\\AMCopen@lineuptext\\empty\\fi%
1985     \\fi%
1986     \\ifAMC@correc\smash{\AMCopen@answer}\\fi%
1987     \\ifx\\empty\\AMCopen@lineuptext\\empty%
1988       \\dotfill%
1989     \\else%
1990       \\AMCopen@lineuptext\\hfill%
1991     \\fi%
1992   \\else%
1993     \\hspace*{.5em}\\linebreak[1]\\hspace*{\\fill}%
1994   \\fi%
1995   {\\AMCnoCompleteMulti%
1996     \\def\\AMCbeginAnswer{}\\def\\AMCendAnswer{}%
1997     \\def\\AMCanswer##1##2{\\ifAMC@ensemble ##1\\else%
1998       \\ifAMC@inside@box ##1\\else{\\AMCboxOutsideLetter{##1}{##2}}\\fi\\fi%
1999       \\hspace{\\AMCopen@Hspace}%
2000     \\fboxsep=\\AMCopen@boxmargin%
2001     \\fboxrule=\\AMCopen@boxframerule%
2002     \\fcolorbox{\\AMCocol@BoxFrameRule}{\\AMCocol@Background}{%
2003       \\ifAMC@ensemble\\AMCopen@question%
2004         \\ifx\\empty\\AMCopen@question\\empty\\else\\hspace{\\AMCopen@Hspace}\\fi%
2005       \\fi%
2006       \\begin{choicescustom}[o]%
2007         \\ifx\\AMCocol@Foreground\\empty\\empty\\else%
2008           \\def\\AMC@boxcolor{\\AMCocol@Foreground}%

```

```

2009      \fi%
2010      #2%
2011      \ifKV@AMCOpen@scan\else\AMCdontScan\fi%
2012      \ifKV@AMCOpen@annotate\else\AMCdontAnnotate\fi%
2013      \end{choicescustom}%
2014      \ifx\@empty\AMCotextReserved\@empty%
2015          \hspace{-\AMCopen@Hspace}%
2016      \else%
2017          \ifx\AMCocol@Foreground\@empty\@empty%
2018              \AMCotextReserved%
2019          \else%
2020              \textcolor{\AMCocol@Foreground}{\AMCotextReserved}%
2021          \fi%
2022          \fi%
2023      }%
2024      \ifKV@AMCOpen@lineup\else%
2025          \par\nobreak\noindent%
2026          \hspace*{\fill}%
2027          \fboxrule=\AMCopen@framerule%
2028          \fcolorbox{\AMCocol@FrameRule}{white}{%
2029              \csname\AMCopen@contentcommand\endcsname
2030          }%
2031          \vspace{\AMCpost0quest}\par%
2032      \fi%
2033  }%
2034  \ifAMC@ensemble\ifAMCformulaire@dedans%
2035  \AMC@amclog{AUTOQCM[FQ]^^J}%
2036  \fi\fi%
2037 }
2038 \newcommand\AMCopenHide[2]{%
2039     \AMCotextGoto%
2040     \ifAMC@qbloc\else\vspace{1.5ex}\par\fi%
2041 }
2042 \def\AMCopen{%
2043     \AMC@if@separate@question{\AMC@mem@category{open}}%
2044     \AMCformatChoices{\AMCopenShow}{\AMCopenHide}%
2045 }

```

4.15 Boxes with letters only

\AMCBoxOnly Sometimes the letters printed in the boxes (or just after them) are enough to describe the answers. In such cases, printing the boxes both on the question and on the answer sheet is not necessary. The \AMCBoxOnly{\{options\}}{\{choices\}} can be used as a replacement for the `choices` environment:

```

\begin{question}{arm}
    Which letter shows the \textit{arm} on the diagram?
    \AMCBoxOnly{ordered=true}{\wrongchoice[A]{}\correctchoice[B]{}%
        \wrongchoice[C]{}\wrongchoice[D]{}}
\end{question}

```

```

2046 \def\AMCbotextGoto{}
2047 \def\AMCbo@help{}
2048 \define@key{AMCBoxOnly}{help}{\def\AMCbo@help{\#1}}
2049 \define@boolkey{AMCBoxOnly}{ordered}[false]{}
2050 \setkeys{AMCBoxOnly}{ordered}
2051 \newcommand\AMCboOpts[1]{\setkeys{AMCBoxOnly}{#1}}
2052 \newcommand\AMCboShow[2]{%
2053   \ifAMC@ensemble\ifAMCformulaire@dedans%
2054     \AMC@amclog{AUTOQCM[Q=\the\AMCid@quest]^^J}%
2055   \fi\fi%
2056   {\setkeys{AMCBoxOnly}{#1}%
2057     \def\AMCbeginAnswer{} \def\AMCendAnswer{}%
2058     \def\AMCanswer##1##2{\hspace{\AMCformHSpace} \ifAMC@ensemble ##1\else%
2059       \ifAMC@inside@box ##1\else{\AMCboxOutsideLetter{##1}{##2}}\fi\fi%
2060     }%
2061     \ifAMC@ensemble\AMCbo@help\fi%
2062     \ifKV@AMCBoxOnly@ordered%
2063       \begin{choicescustom}[o]%
2064     \else%
2065       \begin{choicescustom}%
2066     \fi%
2067     #2
2068   \end{choicescustom}%
2069 }%
2070   \ifAMC@ensemble\ifAMCformulaire@dedans%
2071     \AMC@amclog{AUTOQCM[FQ]^^J}%
2072   \fi\fi%
2073 }
2074 \newcommand\AMCboHide[2]{%
2075   \AMCbotextGoto%
2076   \ifAMC@qbloc\else\vspace{1.5ex}\par\fi%
2077 }
2078 \def\AMCBoxOnly{%
2079   \AMC@if@separate@question{\AMC@mem@category{box}}%
2080   \AMCformatChoices{\AMCboShow}{\AMCboHide}%
2081 }

```

4.16 Page formatting

4.16.1 Watermark

\AMCw@termark These commands are used to print a grey “DRAFT” under each page, so as to prevent from printing old versions of the subject.

```

2082 \DeclareFontShape{OT1}{cmr}{b}{n}{<35->cmr17}{}
2083 \def\AMC@watertext{\AMC@loc@draft}
2084 \newcommand\AMCw@termark{%
2085   \setlength{\tempdimb}{.5\paperwidth}%
2086   \setlength{\tempdimc}{-.5\paperheight}%
2087   \put(\strip@pt\tempdimb,\strip@pt\tempdimc){%
2088     \makebox(0,0){\rotatebox{45}{\AMC@LR}}%

```

```

2089     \textcolor{gray}{0.8}{%
2090         \fontencoding{OT1}\fontfamily{cmr}
2091         \fontseries{b}\fontshape{n}
2092         \fontsize{90pt}{120pt}
2093         \selectfont
2094         \AMC@watertext}}}}}}
2095 \newcommand\AMCw@terprint[1]{%
2096   \setbox\@tempboxa\vbox to \z@{%
2097     \vbox{%
2098       \hbox to \z@{%
2099         #1\hss}\vss}
2100   \dp\@tempboxa\z@
2101   \box\@tempboxa}

```

4.16.2 Signs for scan analysis

The following code sets up all the signs to be printed on the pages so as to be able to recognize the position of the boxes on the scans. Four circles ● are printed on the corners (see \m@rqueCalage), and binary boxes show the student sheet number (see \AMCIDBoxesA), the page (see \AMCIDBoxesB) and a checking number (see \AMCIDBoxesC).

\AMC@intituleHead is the title to be printed at the beginning (used for corrected sheet, and empty on subject). \AMC@note is printed at the bottom of each page. You can change its value using \AMCsetFoot{\langle foot \rangle}.

```

2102 \def\AMCercle#1#2{%
2103   {\setlength{\unitlength}{1mm}%
2104    \begin{picture} (#1,#1)(-#2,-#2)\thinlines\circle*{#1}\end{picture}}}
2105 \def\m@rqueCalage{\AMCercle{3.6}{1.8}}
2106 \def\m@rque#1{\AMC@tracebox{1}{#1}{\m@rqueCalage}}
2107 \def\he@dtaille#1{\vbox to 1cm{#1}}
2108 \def\he@dbas#1{\he@dtaille{\vspace*{\fill}#1}}
2109 \def\he@dhaut#1{\he@dtaille{#1\vspace*{\fill}}}
2110 \def\AMC@intituleHead{\AMC@loc@corrected}
2111 \def\AMC@note{}
2112 \def\AMCsetFoot#1{\def\AMC@note{#1}}
2113 \newcommand\AMCStudentNumber{\the\AMCid@etud}
2114 \newcommand\AMCIDBoxesA{\AMCbin@begin{1}\AMC@binaryBoxes[\AMC@NCBetud]{\the\AMCid@etud}}
2115 \newcommand\AMCIDBoxesB{\AMCbin@begin{2}\AMC@binaryBoxes[\AMC@NCBpage]{\thepage}}
2116 \newcommand\AMCIDBoxesC{\AMCbin@begin{3}\AMC@binaryBoxes[\AMC@NCBcheck]{\the\AMCid@check}}
2117 \newcommand\AMCIDBoxesABC{%
2118   \hbox{\vbox{\noindent\AMCIDBoxesA\%
2119     \noindent\AMCIDBoxesB\AMCIDBoxesC}}\%
2120 }
2121 \AtBeginPage{\ifAMC@pagelayout\global\advance\AMCid@check\m@ne%
2122   \ifnum\AMCid@check<1\global\AMCid@check=\AMCid@checkmax\fi%
2123   \AMC@pagepos%
2124   \ifAMC@watermark\ifAMC@correchead\else\AMCw@terprint{\AMCw@termark}\%
2125   \fi\fi\fi}
2126 \fancypagestyle{AMCpageHeadOnly}{%
2127   \fancyhf{} \fancyhead[C]{\textsc{\AMC@intituleHead}}\%

```

```

2128 \renewcommand{\headrulewidth}{0pt}%
2129 \renewcommand{\footrulewidth}{0pt}%
2130 }
2131 \fancypagestyle{AMCpageFull}{%
2132 \fancyhf{}%
2133 \fancyhead[L]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHG}}}}}%
2134 \fancyhead[R]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHD}}}}}%
2135 \fancyfoot[L]{\AMC@LR{\leavevmode\m@rque{positionBG}}}}}%
2136 \fancyfoot[R]{\AMC@LR{\leavevmode\m@rque{positionBD}}}}}%
2137 \fancyhead[C]{\AMC@LR{\he@dhaus{%
2138 \begin{minipage}[b]{\AMC@CBtaille}\AMCboxColor{black}%
2139 \ifAMCids@top\vbox to \AMCids@height{\texttt{+\the\AMCid@etud/\thepage/\the\AMCid@check+}}\fi%
2140 \AMCIDBoxesABC
2141 \end{minipage}%
2142 \ifAMCids@side\hbox to \AMCids@width{\hspace*{\fill}%
2143 \texttt{+\the\AMCid@etud/\thepage/\the\AMCid@check+}}\fi%
2144 }}}}}}%
2145 \fancyhfoffset[EOLR]{5mm}%
2146 \fancyfoot[C]{\AMC@note}%
2147 \renewcommand{\headrulewidth}{0pt}%
2148 \renewcommand{\footrulewidth}{0pt}%
2149 }
2150 \newcommand\AMCsubjectPageTag{%
2151 \fbox{\texttt{\the\AMCid@etud:\thepage}}}%
2152 }
2153 \fancypagestyle{AMCpageNoMarks}{%
2154 \fancyhf{}%
2155 \fancyhead[R]{\AMCsubjectPageTag}}%
2156 \fancyfoot[C]{\AMC@note}%
2157 \renewcommand{\headrulewidth}{0pt}%
2158 \renewcommand{\footrulewidth}{0pt}%
2159 }
2160 \fancypagestyle{AMCpageEmpty}{%
2161 \fancyhf{}%
2162 \renewcommand{\headrulewidth}{0pt}%
2163 \renewcommand{\footrulewidth}{0pt}%
2164 }
2165 \AtBeginDocument{%
2166 \ifAMC@pagelayout%
2167 \ifAMC@correthead
2168 \pagestyle{AMCpageHeadOnly}
2169 \else
2170 \pagestyle{AMCpageFull}
2171 \fi
2172 \fi
2173 }

```

4.17 Defining a single exam copy content

\onecopy The command `\onecopy[⟨n⟩]{⟨code⟩}` generates ⟨n⟩ copies of the subject that is described in ⟨code⟩. The L^AT_EX code ⟨code⟩ that generates a single copy can be a little long, so that the environment `examcopy` is often preferred.

```

2174 \newcommand{\onecopy}[2]{%
2175   \ifx\AMCNOMBRECOPIES\undefined\AMCNUM@COPIES=#1%
2176   \else\AMCNUM@COPIES=\AMCNOMBRECOPIES\fi%
2177   \AMC@AMCLOG{AUTOCM[TOTAL=\the\AMCNUM@COPIES]^{J}}%
2178   \AMCID@ETUD=\AMCID@ETUDSTART%
2179   \ifnum\AMCID@ETUD=0\AMCID@ETUD=\AMC@PREMIERECP\fi%
2180   \AMCID@ETUDFIN=\AMCNUM@COPIES%
2181   \ADVANCE\AMCID@ETUDFIN\AMCID@ETUD\RELAX%
2182   \ifAMC@CORRECHEAD\AMCID@ETUDFIN=\AMC@PREMIERECP\fi%
2183   \ifAMC@PDFFORM\begin{Form}\fi%
2184   \loop%
2185     \ifAMC@CALIBRATION\PROTECTED@WRITE\AMC@XYFILE{}{%
2186       \STRING\rNGSTATE{\the\AMCID@ETUD}{\the\AMC@SR}%
2187     }\fi%
2188     \AMC@ZONEFORMULAIRE=false\SETCOUNTER{PAGE}{1}\SETCOUNTER{SECTION}{0}%
2189     \ifAMC@ENSEMBLE\ifAMC@AUTOMARKS\PAGESTYLE{AMC@PAGE NOMARKS}\fi\fi%
2190     \AMCNUMERO{1}%
2191     \ifAMC@CALIBRATION\AMC@AMCLOG{AUTOCM[ETU=\the\AMCID@ETUD]^{J}}\fi%
2192     \AMC@KEEPMEMORY=false%
2193     #2%
2194     \ifAMC@KEEPMEMORY\else\AMC@MEM@CLEAR\fi%
2195     \CLEARPAGE}%
2196     \ADVANCE\AMCID@ETUD\@ne\ifnum\AMCID@ETUD<\AMCID@ETUDFIN\REPEAT%
2197     \GLOBAL\AMCID@ETUDSTART=\AMCID@ETUD%
2198     \ifAMC@PDFFORM\END{Form}\fi%
2199 }
```

\AMCaddpages In some situations, one needs all question sheets to have the same number of pages. The command `\AMCaddpages{⟨n⟩}` adds enough (white) pages to get at least ⟨n⟩ pages in the current question sheet.

```

2200 \newcount\AMC@ADDPAGES
2201 \newcommand{\AMCaddpages}[1]{%
2202   \AMC@ADDPAGES=#1\ADVANCE\AMC@ADDPAGES\@ne%
2203   \CLEARPAGE%
2204   \WHILE{\NUMBER{\THEPAGE}<\AMC@ADDPAGES}\DO{%
2205     \ifAMC@AUTOMARKS\PAGESTYLE{AMC@PAGE EMPTY}\fi%
2206     \HBOX{}\CLEARPAGE%
2207   }%
2208 }
```

\AMCcleardoublepage If you want to print the subject all at one time in duplex mode, it is necessary to end each subject with an even number of pages. This can be achieved using `\AMCcleardoublepage` at the end of the copy definition. This command is also useful inserted before the separate answer sheet (if any).

```
2209 \def\AMCcleardoublepage{%
```

```

2210 \clearpage%
2211 \ifodd\thepage\else%
2212   \ifAMC@automarks\pagestyle{AMCpageEmpty}\fi%
2213   \hbox{}\clearpage%
2214 \fi%
2215 }

```

\exemplairepair To make some differences in the copies, checking if the student sheet number is odd, with \exemplairepair construct, can be useful.

```
2216 \def\exemplairepair{\ifodd\AMCid@etud}
```

\AMClabel Commands \AMClabel, \AMCref and \AMCpageref replaces L^AT_EX's \label, \ref and \pageref \AMCref to be able to use different labels for different sheets.

```

\AMCref 2217 \newcommand\AMCstudentlabel[1]{\the\AMCid@etud-\#1}
2218 \def\AMClabel#1{\expandafter\label{\AMCstudentlabel{#1}}}
2219 \def\AMCref#1{\expandafter\ref{\AMCstudentlabel{#1}}}
2220 \def\AMCpageref#1{\expandafter\pageref{\AMCstudentlabel{#1}}}

```

\AMCqlabel A label can be created for current question with \AMCqlabel{\label}. This label can be used with \AMCref and \AMCpageref. This command is defined for backward compatibility only, since \AMClabel can also be used.

```

2221 \newcommand{\AMCqlabel}[1]{%
2222   \AMClabel{\#1}%
2223 }
```

4.18 Pre-association

\AMCassociation Association between sheets and students can be made before the exam with the \AMCassociation[\filename]{\id} command. The optional argument \filename will be used when printing student sheets to files.

```

2224 \newcommand{\AMCassociation}[2][]{%
2225   \ifAMC@calibration%
2226     \immediate\write\AMC@XYFILE{\string\association{\the\AMCid@etud}{\#2}{\#1}}%
2227   \fi%
2228 }
```

\Cstudentslistfile You can also pass AMC the path to the CSV file with students, and the unique key that can be used, with \AMCstudentslistfile{\path}{\key}.

```

2229 \newcommand{\AMCstudentslistfile}[2]{%
2230   \ifAMC@calibration%
2231     \immediate\write\AMC@XYFILE{\string\with{studentslistfile=\#1}}%
2232     \immediate\write\AMC@XYFILE{\string\with{studentslistkey=\#2}}%
2233   \fi%
2234 }
```

4.19 Package options

See section 3.1 for the options descriptions.

```
2235 \def\AMC@lang@code{}
```

```

2236 \DeclareOptionX{noshuffle}{\AMC@ordretrue}
2237 \DeclareOptionX{noshufflegroups}{\AMC@shuffleGfalse}
2238 \DeclareOptionX{fullgroups}{\AMC@fullGroupstrue}
2239 \DeclareOptionX{answers}{\AMC@corretheadtrue\AMC@correcttrue}
2240 \DeclareOptionX{indivanswers}{\AMC@correcttrue}
2241 \DeclareOptionX{textpos}{\AMC@textPostrue}
2242 \DeclareOptionX{extractonly}{\AMC@extractOnlytrue\AMC@textPostrue\AMCboxStyle{shape=none}\AMCBoxedAnswers}
2243 \DeclareOptionX{box}{\AMC@qbloctrue}
2244 \DeclareOptionX{asbox}{\AMC@asqbloctrue}
2245 \DeclareOptionX{separateanswersheet}{\AMC@ensembletrue}
2246 \DeclareOptionX{digits}{\AMC@inside@digittrue}
2247 \DeclareOptionX{ordre}{\AMC@ordretrue}
2248 \DeclareOptionX{correc}{\AMC@corretheadtrue\AMC@correcttrue}
2249 \DeclareOptionX{modele}{\AMC@corretheadtrue\AMC@correcfalse\AMC@ordretrue}
2250 \DeclareOptionX{correcindiv}{\AMC@correcttrue}
2251 \DeclareOptionX{init}{\AMC@SR@time}
2252 \DeclareOptionX{bloc}{\AMC@qbloctrue}
2253 \DeclareOptionX{completmulti}{\AMC@complete@multittrue}
2254 \DeclareOptionX{insidebox}{\AMC@inside@boxtrue}
2255 \DeclareOptionX{ensemble}{\AMC@ensembletrue}
2256 \DeclareOptionX{chiffres}{\AMC@inside@digittrue}
2257 \DeclareOptionX{outsidebox}{\AMC@outside@boxtrue}
2258 \DeclareOptionX{calibration}{\AMC@calibrationtrue}
2259 \DeclareOptionX{nowatermark}{\AMC@watermarkfalse}
2260 \newcommand{\AMC@catalogMode}{%
2261   \AMC@catalogtrue%
2262   \AMC@watermarkfalse\AMC@corretheadtrue%
2263   \AMC@correcttrue\AMC@ordretrue\AMC@shuffleGfalse%
2264   \AMC@fullGroupstrue%
2265   \def\AMC@intituleHead{\AMC@loc@catalog}\AMC@affichekeystrue}
2266 \newcommand{\AMC@keys@next}{\AMC@keyslinfalse}
2267 \newcommand{\AMC@keys@line}{\AMC@keyslinetrue}
2268 \DeclareOptionX{catalog}{\AMC@catalogMode}
2269 \DeclareOptionX{keys}[next]{\csname AMC@keys@\#1\endcsname{}}
2270 \DeclareOptionX{francais}{\def\AMC@lang@code{FR}\AMC@loc@FR}
2271 \DeclareOptionX{lang}{\def\AMC@lang@code{\#1}\csname AMC@loc@\#1\endcsname}
2272 \DeclareOptionX{versionA}{%
2273   \def\AMC@id@checkmax{31}\def\AMC@NCBetud{9}\def\AMC@NCBpage{4}%
2274   \def\AMC@NCBcheck{5}\setlength{\AMC@CBtaille}{4cm}%
2275   \def\AMC@premierecopie{100}%
2276   \DeclareOptionX{plain}{\AMC@plaintrue}
2277   \DeclareOptionX{nopage}{\AMC@pagelayoutfalse}
2278   \DeclareOptionX{postcorrect}{\AMC@postcorrecttrue}
2279   \DeclareOptionX{automarks}{\AMC@automarkstrue}
2280   \newif\ifAMCneeds@storebox\AMCneeds@storeboxfalse
2281   \DeclareOptionX{storebox}{\AMCneeds@storeboxtrue}
2282   \DeclareOptionX{pdfform}{\AMC@pdfformtrue}
2283   \DeclareOptionX{codedigit}{\AMC@codeID@@{\#1}}
2284   \newif\ifAMC@survey\AMC@surveyfalse
2285   \DeclareOptionX{survey}{\AMC@surveytrue}

```

```

2286 \ProcessOptionsX
2287 \ifAMCneeds@storebox
2288   \RequirePackage{storebox}\AtBeginDocument{()}
2289 \fi
2290 \ifAMC@pdfform
2291   \AMC@amclog{AUTOQCM[VAR:project:pdfform=1]^^J}%
2292   \AMCboxStyle{shape=form}%
2293   \RequirePackage[pageanchor=false]{hyperref}%
2294 \else%
2295   \AMC@amclog{AUTOQCM[VAR:project:pdfform=0]^^J}%
2296 \fi
2297 \AtBeginDocument{%
2298   \ifAMCneeds@storebox%
2299     \let\AMC@new@savebox=\newstorebox%
2300     \let\AMC@save@box=\storebox%
2301     \let\AMC@use@box=\usestorebox%
2302   \fi%
2303   \AMC@new@savebox{\AMC@ovalbox@R}%
2304   \AMC@new@savebox{\AMC@ovalbox@RF}%
2305   \AMC@new@savebox{\AMC@ovalbox@O}%
2306   \AMC@new@savebox{\AMC@ovalbox@F}%
2307   \AMC@shapeprepare%
2308 }

```

4.20 Survey add-on

Some code and *tikz* settings to help handling surveys, see https://survey.codes/pdf/surveyamc_manual.pdf for more details. This survey add-on is originally written by Claudia Saalbach.

Questionnaires

```

auto 2309 \ifAMC@survey
question-auto 2310 \NewEnviron{Questionnaires}[1]{
  values 2311 \onecopy{#1}{}
values-auto 2312 \BODY
variable-auto 2313 }
\answer 2314 {
  2315 \NewEnviron{auto}[1]{
    2316 \csvreader[head to column names, separator=tab]{#1}{}{%
      2317 \BODY
      2318 }
      2319 }
  2320 \NewEnviron{question-auto}[3]{
    2321 \csvreader[head to column names, separator=tab]{#1}{}{%
      2322 \ifcsvstrcmp{#2}{#3}{\BODY \\}{}%
      2323 }
      2324 }
  2325 \newenvironment{values}{}{%
  2326 \NewEnviron{values-auto}[5]{
    2327 \csvreader[head to column names, separator=tab]{#1}{}{%
      2328 \ifcsvstrcmp{#2}{#3}{%

```

```

2329 \ifcsvstrcmp{#4}{#5}{\BODY \\
2330 }{}
2331 }{}
2332 }
2333 }
2334 \NewEnviron{variable-auto}[3]{
2335 \foreach \x in {#3}{
2336 \csvreader[head to column names, separator=tab]{#1}{}{%
2337 \ifcsvstrcmp{#2}{\x}{\BODY}{}
2338 }
2339 }
2340 }
2341 \newcommand{\answer}[5][]{\global\advance\AMCrep@count\@ne\relax%
2342 \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:B]^\J}\fi%
2343 \global\AMCune@bonnettrue%
2344 \AMCload@reponse{\une@rep{\ifAMC@correc\AMC@box{#1}{\AMC@checkbox}}%
2345 \else\AMC@box{#1}\fi\#2\#3\#4\#5}{\the\AMCrep@count}\ignorespaces}
2346 \RequirePackage{tikz}
2347 \usetikzlibrary{positioning, shapes, arrows, tikzmark, decorations.pathreplacing}
2348 \tikzset{
2349   checkbox-sc/.style={%
2350     right=of lab\thecsvrow
2351   },
2352   vallab-sc/.style={%
2353     text width=4cm,
2354     align=left,
2355   },
2356   checkbox-mc/.style={%
2357   },
2358   vallab-mc/.style={%
2359     above=of box\thecsvrow,
2360     text width=1.4cm,
2361     align=center,
2362   },
2363   varlab-mc/.style={%
2364     text width=4cm,
2365     align=left,
2366   },
2367   node distance= 0mm,
2368 }
2369 \fi

```

4.21 Package Errors

\AMC@error@explain Error to display if \explain command is used outside question like environments

```

2370 \def\AMC@error@explain{\PackageError{automultiplechoice}{%
2371   Command \protect\explain\space can only be used inside\MessageBreak question like environments}{Something}}
2372 }

```

4.22 Optional features

This package tries to see if optional packages `environ` and `etex` are loadable, and load them if possible. This behaviour can be cancelled by using `plain` option.

```
2373 \ifAMC@plain
2374 \else
2375   \IfFileExists{environ.sty}{\RequirePackage{environ}}{}
2376   \ifx\TeXversion\undefined
2377   \else
2378     \RequirePackage{etex}
2379   \fi
2380 \fi
```

`examcopy` Then, if `environ` package is loaded and defines command `\NewEnviron`, environment `examcopy` is defined.

Environment `\{examcopy\}[\langle n\rangle]` does the same as command `onecopy`: it encloses L^AT_EX code which makes *one* exam copy. Optional argument `\langle n\rangle` gives the number of desired copies – this can also be modified redefinig `\AMCNOMBRECOPIES`.

```
2381 \@ifpackageloaded{environ}{%
2382   \ifx\NewEnviron\undefined\PackageWarning{automultiplechoice}%
2383   {Package environ loaded but too old version:
2384     environnement examcopy/copieexamen will NOT be defined.}%
2385   \else\NewEnviron{examcopy}[1][5]{\onecopy{\#1}{\BODY}}\fi}%
2386 {\PackageWarning{automultiplechoice}%
2387 {Package environ not loaded: environnement
2388   examcopy/copieexamen will NOT be defined.}}
```

4.23 Use with recent LuaTeX versions

In recent LuaTeX versions, the commands `pdfsavepos`, `pdflastxpos` and `pdflastypos` has been renamed, stripping the `pdf` part. The following code tries to detect this situation and make the bindings between the old and new command names.

```
2389 \ExplSyntaxOn
2390
2391 \cs_if_exist:NTF \pdfsavepos { } {
2392   \cs_if_exist:NTF \savepos { \cs_new_eq:NN \pdfsavepos \savepos } { }
2393 }
2394 \cs_if_exist:NTF \pdflastxpos { } {
2395   \cs_if_exist:NTF \lastxpos { \cs_new_eq:NN \pdflastxpos \lastxpos } { }
2396 }
2397 \cs_if_exist:NTF \pdflastypos { } {
2398   \cs_if_exist:NTF \lastypos { \cs_new_eq:NN \pdflastypos \lastypos } { }
2399 }
2400
2401 \ExplSyntaxOff
```

4.24 External control

```
\SujetExterne Some of the package options can be controlled defining \xxxExterne commands. For example, the
\ScoringExterne following command will format the subject document, whatever options are used in the LATEX file:
\CorrigeExterne pdflatex '\nonstopmode\def\SujetExterne{1}\def\NoWatermarkExterne{1}\input{mcq.tex}'
\CorrigeIndivExterne
\NoWatermarkExterne 2402 \ifx\SujetExterne\undefined\else
2403 \message{***SUJET***^^J}
2404 \AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse
2405 \fi
2406 \ifx\ScoringExterne\undefined\else
2407 \message{***SCORING***^^J}
2408 \AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse\AMC@invisibltrue
2409 \fi
2410 \ifx\CorrigeExterne\undefined\else
2411 \message{***CORRIGE***^^J}
2412 \AMC@calibrationfalse\AMC@corretheadtrue\AMC@correcttrue\AMC@watermarkfalse
2413 \fi
2414 \ifx\CorrigeIndivExterne\undefined\else
2415 \message{***CORRIGE***^^J}
2416 \AMC@calibrationfalse\AMC@corretheadfalse\AMC@correcttrue\AMC@watermarkfalse
2417 \fi
2418 \ifx\CatalogExterne\undefined\else
2419 \message{***CATALOG***^^J}
2420 \AMC@catalogMode
2421 \fi
2422 \ifx\NoWatermarkExterne\undefined\else
2423 \AMC@watermarkfalse
2424 \fi
2425 \ifx\codeDigitExterne\undefined\else
2426 \AMC@codeID@@{\codeDigitExterne}
2427 \fi
```

4.25 Page layout

The following code sets the correct page layout to have room for signs for scan analysis, and prepares watermark printing:

```
2428 \@ifpackageloaded{geometry}{}{\usepackage{geometry}}
2429 \ifAMC@pagelayout
2430   \ifAMC@correthead
2431     \geometry{hmargin=3cm,vmargin={1cm,1cm},includeheadfoot,headheight=1cm,footskip=1cm}
2432   \else
2433     \geometry{hmargin=3cm,headheight=2cm,headsep=.3cm,footskip=1cm,top=3.5cm,bottom=2.5cm}
2434   \fi
2435 \ifAMC@watermark
2436   \ifAMC@correthead\else
2437     \def\AMC@note{\begin{minipage}{0.65\linewidth}
2438       \AMC@LR{\textcolor{blue}{\AMC@loc@message}}
2439     \end{minipage}}
2440   \fi
```

```

2441     \fi
2442   \fi
2443 \fi

```

4.26 Initialisation

Initialisation of the check counter:

```
2444 \AMC@cid@check=\AMC@cid@checkmax\advance\AMC@cid@check\@ne
```

Telling outside if separate answer sheet, and boxes labelling, are requested:

```

2445 \ifAMC@ensemble\AMC@amclog{AUTOQCM[VAR:ensemble=1]^^J}\fi
2446 \ifAMC@inside@box\AMC@amclog{AUTOQCM[VAR:insidebox=1]^^J}\fi
2447 \ifAMC@outside@box\AMC@amclog{AUTOQCM[VAR:outsidebox=1]^^J}\fi
2448 \ifAMC@postcorrect\AMC@amclog{AUTOQCM[VAR:postcorrect=1]^^J}\fi

```

Preparing writing to .xy file :

```

2449 \ifAMC@calibration
2450 \newwrite\AMC@XYFILE%
2451 \immediate\openout\AMC@XYFILE\jobname.xy%
2452 \immediate\write\AMC@XYFILE{\string\version{\AMC@VERSION}}
2453 \immediate\write\AMC@XYFILE{\string\with{codedigit=squarebrackets}}
2454 \immediate\write\AMC@XYFILE{\string\with{version=\AMC@VERSION}}
2455 \immediate\write\AMC@XYFILE{\string\with{ensemble=\ifAMC@ensemble yes\else no\fi}}
2456 \immediate\write\AMC@XYFILE{\string\with{insidebox=\ifAMC@inside@box yes\else no\fi}}
2457 \immediate\write\AMC@XYFILE{\string\with{outsidebox=\ifAMC@outside@box yes\else no\fi}}
2458 \immediate\write\AMC@XYFILE{\string\with{postcorrect=\ifAMC@postcorrect yes\else no\fi}}
2459 \immediate\write\AMC@XYFILE{\string\with{extractonly=\ifAMC@extractOnly yes\else no\fi}}
2460 \immediate\write\AMC@XYFILE{\string\with{lang=\AMC@lang@code}}
2461 \ifx\AMCNOMBRECopies\undefined%
2462 \immediate\write\AMC@XYFILE{\string\with{ncopies=default}}%
2463 \else%
2464 \immediate\write\AMC@XYFILE{\string\with{ncopies=\AMCNOMBRECopies}}%
2465 \fi%
2466 \fi

```

Preparing writing to .cs file :

```

2467 \ifAMC@catalog%
2468 \newwrite\AMC@CSFILE%
2469 \immediate\openout\AMC@CSFILE\jobname.cs%
2470 \fi%

```

4.27 French command names

For backward compatibility, a lot of commands have their french counterpart:

```

2471 \let\reponses=\choices\let\endreponses=\endchoices
2472 \let\reponseshoriz=\choiceshoriz\let\endreponseshoriz=\endchoiceshoriz
2473 \let\reponsesperso=\choicescustom\let\endreponsesperso=\endchoicescustom
2474 \let\bonne=\correctchoice
2475 \let\mauvaise=\wrongchoice
2476 \let\bareme=\scoring
2477 \let\baremeDefault=\scoringDefaultM

```

```

2478 \let\baremeDefautS=\scoringDefaultS
2479 \def\exemplaire{\AMC@loc@FR\onecopy}
2480 \@ifpackageloaded{environ}{%
2481   \let\copieexamen=\examcopy\let\endcopieexamen=\endexamcopy}{}%
2482 \let\melangegroupe=\shufflegroup
2483 \let\restituegroupe=\insertgroup
2484 \let\alafin=\lastchoices
2485 \let\formulaire=\AMCform
2486 \let\AMCdebutFormulaire=\AMCformBegin
2487 \let\champnom=\namefield
2488 \let\choixIntervalles=\AMCIntervals

```

5 Outputs

In the .xy file, $1/\langle n \rangle$ means student sheet number 1 (there is only one “student sheet” for this document as we did not use \onecopy) and page number $\langle n \rangle$ inside this student sheet. Then, each instance of the \tracepos command shows x and y positions as arguments #2 and #3 (unit is sp, such that 65536×72.27 sp is one inch). One has to take min and max of the x -values to determine the left and right position of the box, and min and max values of y -values to determine top and bottom position of the box.

5.1 namefield command

Lines in the .xy file from a \namefield command:

```

\tracepos{0/35:nom}{0sp}{26831454sp}{square}
\tracepos{0/35:nom}{6038827sp}{0sp}{square}
\tracepos{0/35:nom}{16026323sp}{0sp}{square}
\tracepos{0/35:nom}{0sp}{23846276sp}{square}

```

5.2 AMboxedchar command

Lines in the .xy file from a \AMboxedchar command:

```

\tracepos{0/35:test}{22597209sp}{10756930sp}{square}
\tracepos{0/35:test}{23302629sp}{10051510sp}{square}

```

5.3 AMCode command

Lines in the .xy file from a \AMCode command. Here, $\text{code}. \langle n \rangle : \langle q \rangle, \langle v \rangle$ relates to digit number $\langle n \rangle$ from the right ($\langle n \rangle=1$ for units, $\langle n \rangle=2$ for tens, $\langle n \rangle=3$ for hundreds and so on), question number $\langle q \rangle$ (\AMCode uses a fake question; this number can be ignored), and value $\langle v \rangle - 1$ (box number $\langle v \rangle$ for the digit).

```

\tracepos{0/59:case:code[5]:16,1}{25579605sp}{40511471sp}{square}
\tracepos{0/59:case:code[5]:16,1}{26285025sp}{39806051sp}{square}
\boxchar{0/59:case:code[5]:16,1}{A}
\tracepos{0/59:case:code[5]:16,2}{25579605sp}{39397359sp}{square}

```

```

\tracepos{0/59:case:code[5]:16,2}{26285025sp}{38691939sp}{square}
\boxchar{0/59:case:code[5]:16,2}{B}
\tracepos{0/59:case:code[5]:16,3}{25579605sp}{38283247sp}{square}
\tracepos{0/59:case:code[5]:16,3}{26285025sp}{37577827sp}{square}
\boxchar{0/59:case:code[5]:16,3}{C}
\tracepos{0/59:case:code[5]:16,4}{25579605sp}{37169135sp}{square}
\tracepos{0/59:case:code[5]:16,4}{26285025sp}{36463715sp}{square}
\boxchar{0/59:case:code[5]:16,4}{D}
\tracepos{0/59:case:code[4]:17,1}{27244404sp}{42739695sp}{square}
\tracepos{0/59:case:code[4]:17,1}{27949824sp}{42034275sp}{square}
\boxchar{0/59:case:code[4]:17,1}{0}
\tracepos{0/59:case:code[4]:17,2}{27244404sp}{41625583sp}{square}
\tracepos{0/59:case:code[4]:17,2}{27949824sp}{40920163sp}{square}
\boxchar{0/59:case:code[4]:17,2}{1}
\tracepos{0/59:case:code[4]:17,3}{27244404sp}{40511471sp}{square}
\tracepos{0/59:case:code[4]:17,3}{27949824sp}{39806051sp}{square}
\boxchar{0/59:case:code[4]:17,3}{2}
\tracepos{0/59:case:code[4]:17,4}{27244404sp}{39397359sp}{square}
\tracepos{0/59:case:code[4]:17,4}{27949824sp}{38691939sp}{square}
\boxchar{0/59:case:code[4]:17,4}{3}
\tracepos{0/59:case:code[4]:17,5}{27244404sp}{38283247sp}{square}
\tracepos{0/59:case:code[4]:17,5}{27949824sp}{37577827sp}{square}
\boxchar{0/59:case:code[4]:17,5}{4}
\tracepos{0/59:case:code[4]:17,6}{27244404sp}{37169135sp}{square}
\tracepos{0/59:case:code[4]:17,6}{27949824sp}{36463715sp}{square}
\boxchar{0/59:case:code[4]:17,6}{5}
\tracepos{0/59:case:code[3]:18,1}{28736261sp}{42739695sp}{square}
\tracepos{0/59:case:code[3]:18,1}{29441681sp}{42034275sp}{square}
\boxchar{0/59:case:code[3]:18,1}{0}
\tracepos{0/59:case:code[3]:18,2}{28736261sp}{41625583sp}{square}
\tracepos{0/59:case:code[3]:18,2}{29441681sp}{40920163sp}{square}
\boxchar{0/59:case:code[3]:18,2}{1}
\tracepos{0/59:case:code[3]:18,3}{28736261sp}{40511471sp}{square}
\tracepos{0/59:case:code[3]:18,3}{29441681sp}{39806051sp}{square}
\boxchar{0/59:case:code[3]:18,3}{2}
\tracepos{0/59:case:code[3]:18,4}{28736261sp}{39397359sp}{square}
\tracepos{0/59:case:code[3]:18,4}{29441681sp}{38691939sp}{square}
\boxchar{0/59:case:code[3]:18,4}{3}
\tracepos{0/59:case:code[3]:18,5}{28736261sp}{38283247sp}{square}
\tracepos{0/59:case:code[3]:18,5}{29441681sp}{37577827sp}{square}
\boxchar{0/59:case:code[3]:18,5}{4}
\tracepos{0/59:case:code[3]:18,6}{28736261sp}{37169135sp}{square}
\tracepos{0/59:case:code[3]:18,6}{29441681sp}{36463715sp}{square}
\boxchar{0/59:case:code[3]:18,6}{5}
\tracepos{0/59:case:code[2]:19,1}{30228118sp}{42739695sp}{square}
\tracepos{0/59:case:code[2]:19,1}{30933538sp}{42034275sp}{square}

```

```

\boxchar{0/59:case:code[2]:19,1}{0}
\tracepos{0/59:case:code[2]:19,2}{30228118sp}{41625583sp}{square}
\tracepos{0/59:case:code[2]:19,2}{30933538sp}{40920163sp}{square}
\boxchar{0/59:case:code[2]:19,2}{1}
\tracepos{0/59:case:code[2]:19,3}{30228118sp}{40511471sp}{square}
\tracepos{0/59:case:code[2]:19,3}{30933538sp}{39806051sp}{square}
\boxchar{0/59:case:code[2]:19,3}{2}
\tracepos{0/59:case:code[2]:19,4}{30228118sp}{39397359sp}{square}
\tracepos{0/59:case:code[2]:19,4}{30933538sp}{38691939sp}{square}
\boxchar{0/59:case:code[2]:19,4}{3}
\tracepos{0/59:case:code[2]:19,5}{30228118sp}{38283247sp}{square}
\tracepos{0/59:case:code[2]:19,5}{30933538sp}{37577827sp}{square}
\boxchar{0/59:case:code[2]:19,5}{4}
\tracepos{0/59:case:code[2]:19,6}{30228118sp}{37169135sp}{square}
\tracepos{0/59:case:code[2]:19,6}{30933538sp}{36463715sp}{square}
\boxchar{0/59:case:code[2]:19,6}{5}
\tracepos{0/59:case:code[1]:20,1}{31719975sp}{42739695sp}{square}
\tracepos{0/59:case:code[1]:20,1}{32425395sp}{42034275sp}{square}
\boxchar{0/59:case:code[1]:20,1}{0}
\tracepos{0/59:case:code[1]:20,2}{31719975sp}{41625583sp}{square}
\tracepos{0/59:case:code[1]:20,2}{32425395sp}{40920163sp}{square}
\boxchar{0/59:case:code[1]:20,2}{1}
\tracepos{0/59:case:code[1]:20,3}{31719975sp}{40511471sp}{square}
\tracepos{0/59:case:code[1]:20,3}{32425395sp}{39806051sp}{square}
\boxchar{0/59:case:code[1]:20,3}{2}
\tracepos{0/59:case:code[1]:20,4}{31719975sp}{39397359sp}{square}
\tracepos{0/59:case:code[1]:20,4}{32425395sp}{38691939sp}{square}
\boxchar{0/59:case:code[1]:20,4}{3}
\tracepos{0/59:case:code[1]:20,5}{31719975sp}{38283247sp}{square}
\tracepos{0/59:case:code[1]:20,5}{32425395sp}{37577827sp}{square}
\boxchar{0/59:case:code[1]:20,5}{4}
\tracepos{0/59:case:code[1]:20,6}{31719975sp}{37169135sp}{square}
\tracepos{0/59:case:code[1]:20,6}{32425395sp}{36463715sp}{square}
\boxchar{0/59:case:code[1]:20,6}{5}

```

Contents

1	Introduction	1
2	Samples	1
2.1	Standard layout	4
2.2	Separate answer sheet	5
2.3	Without markers	6
3	Usage	11
3.1	Package options	11
3.2	Questions and answers	12
3.3	Scoring	14
3.4	Groups of questions	14
3.5	Students identification	16
3.6	Separate answer sheet	17
3.7	Random computation questions	17
3.8	French command names	20
3.9	Customisation	20
3.9.1	Boxes	20
3.9.2	Codes	22
3.9.3	Answers	22
4	Implementation	22
4.1	Variables	23
4.2	Dimensions	25
4.3	Human readable sheet ID position	26
4.4	Localisation	27
4.4.1	English	27
4.4.2	Catalan	27
4.4.3	Dutch	28
4.4.4	French	28
4.4.5	German	28
4.4.6	Italian	29
4.4.7	Norwegian	29
4.4.8	Portuguese	29
4.4.9	Spanish	30
4.4.10	Japanese	30
4.4.11	Other languages	31
4.5	Interaction with other packages	31
4.5.1	cleveref	31
4.6	Random	31
4.6.1	Random pseudo-generator	31
4.6.2	Uniform random deviates	31
4.6.3	Tokens shuffling	32
4.7	Keys numbering	32
4.8	Boxes	33

4.8.1	Character logging	33
4.8.2	Position logging	33
4.8.3	Boxes to be checked by students	35
4.8.4	Scoring zones	41
4.8.5	Binary boxes	41
4.9	Checking Environment	42
4.10	Handling groups of questions	43
4.11	Questions	47
4.11.1	Managing answers	47
4.11.2	Separate answer sheet	48
4.11.3	Formatting answers	52
4.11.4	Score zones	53
4.11.5	Formatting questions	56
4.11.6	Explanations	58
4.12	Scoring	58
4.13	Numerical data	59
4.13.1	Codes	59
4.13.2	Numerical questions	62
4.13.3	Intervals	75
4.14	Open questions	76
4.15	Boxes with letters only	79
4.16	Page formatting	80
4.16.1	Watermark	80
4.16.2	Signs for scan analysis	81
4.17	Defining a single exam copy content	83
4.18	Pre-association	84
4.19	Package options	84
4.20	Survey add-on	86
4.21	Package Errors	87
4.22	Optional features	88
4.23	Use with recent LuaTeX versions	88
4.24	External control	89
4.25	Page layout	89
4.26	Initialisation	90
4.27	French command names	90
5	Outputs	91
5.1	<code>namefield</code> command	91
5.2	<code>AMCboxedchar</code> command	91
5.3	<code>AMCcode</code> command	91

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\\"	147, 153
\@aucune	804, 808, 809
\@firstoftwo	630
\@ifstar	968, 969
\@secondoftwo	632
\@skiphyperreffalse ..	1137
\@skiphyperreftrue ..	1133, 1137
\@tempboxa ..	2096, 2100, 2101
\@tempdimb	2085, 2087
\@tempdimc	2086, 2087
\~	188, 189, 194, 195
\u	1158
 A	
\aa	174
\alafin	21, 2484
\amc	831, 842, 844, 846, 847, 849, 852, 853, 855, 858, 859, 862–865, 867, 869, 870, 872, 874, 875, 877, 879, 880, 883, 884, 886, 887, 889, 890, 892, 893, 895, 896, 898, 901, 902, 904, 906, 910–913, 1215–1219, 1221, 1228, 1231, 1236, 1240, 1248, 1251–1253, 1258, 1260, 1262– 1265, 1267, 1272, 1274, 1276, 1284, 1289–1291, 1293, 1295, 1298–1301, 1303, 1305, 1308, 1309, 1311, 1312, 1314–1317, 1337, 1338, 1343– 1348, 1353, 1355– 1359, 1361, 1363– 1366, 1369, 1376– 1378, 1380, 1382, 1383, 1385, 1387, 1392, 1393, 1395, 1397–1399, 1401, 1407, 1412, 1424, 1458,
\AMC@addpages	2200, 2202, 2204
\AMC@affekte	<u>278</u> , 1150
\AMC@amclog	<u>17</u> , 279, 590, 957, 1016, 1021, 1168, 1200–1203, 1238, 1328, 1520, 1552, 1554, 1559, 1561, 1566, 1568, 1577, 1590, 1606, 1689, 1692, 1708, 1710, 1730, 1781, 1788, 1804,
\AMC@chiffres	1204
\AMC@crosschar	400, 503
\AMC@crossrule ..	422, 488, 504
\AMC@CSFILE ..	287, 2468, 2469
\AMC@definitnumero ..	279, 283
\AMC@draw@crossfalse ..	380
\AMC@draw@crosstrue ..	382

\AMC@error@explain 1195, 1197, 2370
 \AMC@fillcolor@ 378, 396, 397, 413, 418
 \AMC@fin@rep 791, 976, 980, 984, 987, 990
 \AMC@formBox 518
 \AMC@formBox@ 518
 \AMC@fullGroupsfalse 34
 \AMC@fullGroupstrue 2238, 2264
 \AMC@if@separate@question 842, 917, 922, 930, 936, 1322, 1899, 2043, 2079
 \AMC@imax 684, 696–698
 \AMC@intituleHead 2110, 2127, 2265
 \AMC@keepmemoryfalse .. 2192
 \AMC@keepmemorytrue 958
 \AMC@keyBox@ 547, 1239, 1523, 1526
 \AMC@keys@line 2267
 \AMC@keys@next 2266
 \AMC@lang@code 2235, 2270, 2271, 2460
 \AMC@loc@CA 104
 \AMC@loc@catalog 98, 111, 125, 138, 152, 166, 179, 191, 205, 217, 2265
 \AMC@loc@corrected ... 97, 110, 124, 137, 151, 165, 178, 190, 204, 216, 2110
 \AMC@loc@DE 145
 \AMC@loc@draft 92, 105, 119, 132, 146, 160, 173, 186, 199, 212, 2083
 \AMC@loc@ES 198
 \AMC@loc@explain 99, 112, 139, 153, 192, 218, 1195
 \AMC@loc@FR .. 131, 2270, 2479
 \AMC@loc@IT 159
 \AMC@loc@JA 211
 \AMC@loc@message 93, 106, 120, 133, 147, 161, 174, 187, 200, 213, 2438
 \AMC@loc@namesurname ... 103, 116, 129, 143, 157, 170, 183, 196, 209
 \AMC@loc@NLL 118
 \AMC@loc@NO 172

\AMC@loc@none 100, 113, 126, 140, 154, 167, 180, 193, 206, 219, 804
 \AMC@loc@PT 185
 \AMC@loc@q 96, 109, 123, 136, 150, 164, 177, 189, 203, 215, 1140
 \AMC@loc@qf 95, 108, 122, 135, 149, 163, 176, 188, 202, 214, 813
 \AMC@loc@question .. 101, 114, 127, 141, 155, 168, 181, 194, 207, 220, 226
 \AMC@loc@questions .. 102, 115, 128, 142, 156, 169, 182, 195, 208, 221, 226
 \AMC@logchar 286, 386
 \AMC@logfile 17–19
 \AMC@LR 21, 388, 2088, 2133–2137, 2438
 \AMC@makeovalbox 411, 430–433
 \AMC@mem@add 872, 918, 925, 932, 939, 1323
 \AMC@mem@add@ifneeded .. 829, 1164
 \AMC@mem@addsingle@ifneeded .. 921, 961, 963, 965, 967
 \AMC@mem@addvar 877
 \AMC@mem@aid 896, 931
 \AMC@mem@answer 928, 991, 998–1000, 1005, 1011
 \AMC@mem@category 890, 924, 1899, 2043, 2079
 \AMC@mem@clear 847, 2194
 \AMC@mem@next .. 867, 923, 937
 \AMC@mem@openQuestion .. 935, 1163
 \AMC@mem@qidaffname . 884, 938
 \AMC@mem@show .. 911, 948, 957
 \AMC@mem@show@filter 912, 952
 \AMC@mn@leftmargin 1028, 1036, 1039, 1045
 \AMC@mn@rightmargin 1029, 1037, 1040, 1043
 \AMC@mn@sep .. 1027, 1043, 1045
 \AMC@mn@test .. 1026, 1033, 1042
 \AMC@NCBcheck 594, 2116, 2274
 \AMC@NCBetud .. 594, 2114, 2273
 \AMC@NCBpage .. 594, 2115, 2273

\AMC@new@savebox 358, 2299, 2303–2306
 \AMC@note 2111, 2112, 2146, 2156, 2437
 \AMC@numeric@alsocorrect 1508, 1825, 1829, 1839, 1843
 \AMC@numeric@keepas 1506, 1818, 1819
 \AMC@numeric@scoreapprox 1498, 1785, 1795
 \AMC@numeric@scoreexact 1496, 1784, 1790
 \AMC@numeric@scorewrong 1500, 1792, 1795
 \AMC@numerotation 278, 282, 283
 \AMC@outside@sep ... 493, 499
 \AMC@oval@radius 418, 492, 509, 511
 \AMC@ovalbox@ . 432, 446, 2305
 \AMC@ovalbox@F 433, 444, 2306
 \AMC@ovalbox@R 429, 430, 452, 2303
 \AMC@ovalbox@RF 431, 450, 2304
 \AMC@pagepos 292, 2123
 \AMC@premierecopie 599, 2179, 2182, 2275
 \AMC@prepare ... 281, 284, 285
 \AMC@prepare@element ... 647, 655, 765
 \AMC@printformoutside@false 522
 \AMC@printformoutside@true 524, 525
 \AMC@printkeyoutside@false 539
 \AMC@printkeyoutside@true 541, 543
 \AMC@qaff 814, 1130, 1158, 1191
 \AMC@save@box .. 359, 414, 2300
 \AMC@setcolors@ 374, 395, 412, 437
 \AMC@shape@form 471
 \AMC@shape@form@base 458, 472
 \AMC@shape@form@ticked .. 460, 462, 465
 \AMC@shape@none 475
 \AMC@shape@oval 436
 \AMC@shape@square 393

\AMC@shapename
.. 292, 300, 309, 318, 494
\AMC@shapename@ 292, 389, 505
\AMC@shapeprepare
..... 505, 513, 2307
\AMC@shapeprepare@form . 457
\AMC@shapeprepare@none . 474
\AMC@shapeprepare@oval . 428
\AMC@shapeprepare@square 392
\AMC@shuffletoks
..... 259, 717, 720, 784
\AMC@smashbox 362, 365–369, 372
\AMC@smashboxheight
..... 363, 366–368, 371
\AMC@smashcentered
.. 364, 406, 407, 439, 440
\AMC@SR ... 228, 230, 233–
236, 238, 240, 241, 2186
\AMC@SR@count 233, 234, 236,
244, 248, 251, 254–257
\AMC@SR@time 245, 2251
\AMC@SRadvance . 231, 238, 239
\AMC@SRbit 238
\AMC@SRconst ... 229, 233, 236
\AMC@SRmax 244, 272
\AMC@SRnextByte 244
\AMC@SRnum .. 246, 247, 249,
250, 254, 257, 272, 273
\AMC@SRset . 230, 242, 243, 245
\AMC@SRtest 239, 250
\AMC@SRvalue 241
\AMC@stepQuestion
..... 1130, 1149, 1188
\AMC@sti 259, 267, 271, 274, 275
\AMC@stil 260, 268–270, 272, 276
\AMC@surveyfalse 2284
\AMC@surveytrue 2285
\AMC@sz@box 1049,
1051, 1053, 1056, 1099
\AMC@sz@callin
... 1061, 1066, 1074,
1076, 1141, 1159, 1160
\AMC@sz@callin@question 1051
\AMC@sz@callout 1060, 1065,
1069, 1071, 1153, 1154
\AMC@sz@callout@margin 1053
\AMC@sz@callout@margins 1056
\AMC@sz@depth 1049, 1059, 1064
\AMC@sz@height 1049, 1058, 1063
\AMC@sz@init@margins .. 1055

\AMC@sz@width 1049, 1057, 1062
\AMC@sza@box . 1084, 1092, 1095
\AMC@sza@callin 823, 824,
1106, 1111, 1119, 1121
\AMC@sza@callin@margin 1096
\AMC@sza@callin@margins 1100
\AMC@sza@callin@none .. 1088
\AMC@sza@callin@question 1092
\AMC@sza@callout 819, 820,
1105, 1110, 1114, 1116
\AMC@sza@callout@margin 1095
\AMC@sza@callout@margins 1099
\AMC@sza@callout@none . 1087
\AMC@sza@callout@question
..... 1091
\AMC@sza@depth 1084, 1104, 1109
\AMC@sza@height
..... 1084, 1103, 1108
\AMC@sza@init@margin .. 1094
\AMC@sza@init@margins . 1098
\AMC@sza@init@none 1086
\AMC@sza@init@question 1090
\AMC@sza@width 1084, 1102, 1107
\AMC@tempenv 628, 629
\AMC@tmpXY 340, 343, 345
\AMC@tracebox
... 292, 346, 438, 464,
582, 584, 587, 1007, 2106
\AMC@tracechar . 332, 535, 553
\AMC@tracepos .. 293, 403,
409, 993, 996, 1156, 1164
\AMC@traceposx 302, 322
\AMC@traceposy . 311, 321, 323
\AMC@unnumero 278
\AMC@use@box 360,
444, 446, 450, 452, 2301
\AMC@VERSION 2452, 2454
\AMC@watertext ... 2083, 2094
\AMC@XYFILE
... 295, 304, 313, 325,
329, 330, 334, 343–345,
2185, 2226, 2231, 2232,
2450–2460, 2462, 2464
\AMC@XYSpecial
... 339, 342, 344, 345
\AMCaddpghosto 2200
\AMCanswer
... 1011, 1012, 1997, 2058
\AMCassocation 2224

\AMCbeforeQuestion
..... 1139, 1152, 1223
\AMCbeginAnswer
... 983, 1012, 1996, 2057
\AMCbeginQuestion
..... 1139, 1158,
1171, 1177, 1191, 1222
\AMCbin@begin . 609, 2114–2116
\AMCbin@digit 604–609
\AMCbin@id . 603, 606, 608, 609
\AMCbin@ndigits
... 602, 612, 615, 621, 624
\AMCbin@number
... 601, 611, 614, 616, 618
\AMCbin@one 605, 616
\AMCbin@sequence ... 600,
611, 616, 617, 622, 623
\AMCbin@zero ... 607, 617, 622
\AMCbloc 1146
\AMCbo@help .. 2047, 2048, 2061
\AMCboHide 2074, 2080
\AMCboOpts 2051
\AMCboShow 2052, 2080
\AMCbotextGoto ... 2046, 2075
\AMCboxColor 516, 2138
\AMCboxDimensions .. 517, 611
\AMCBoxedAnswers .. 970, 2242
\AMCBoxOnly 2046
\AMCboxOutsideLetter ...
..... 518, 1998, 2059
\AMCboxStyle 20, 487, 2242, 2292
\AMCcercle 2102, 2105
\AMCchoiceLabel ... 476, 557
\AMCchoiceLabelFormat 390, 476
\AMCcleardoublepage . 17, 2209
\AMCcode 1316
\AMCcodeGrid 16, 1204
\AMCcodeGridInt .. 16, 1204
\AMCcodeH 1317
\AMCcodeHspace 1205, 1243, 1278
\AMCcodeID 1210, 1262
\AMCcodeID@00
... 1209, 1212, 2283, 2426
\AMCcodeID@dot 1208
\AMCcodeID@squarebrackets
..... 1207
\AMCcodeVspace
... 1206, 1241, 1277, 1280
\AMCcompleteMulti ... 13, 63
\AMCcurrentenv 626, 629, 1148

\AMCdebutFormulaire .	21, 2486	\AMClocalized	91
\AMCdecimalPoint	1446, 1616, 1648	\AMCloop@k	690, 696,
\AMCdefault@groupmode	644, 658, 659	700, 702, 723, 731, 740	
\AMCdontAnnotate	329, 2012	\AMCmarginNote .	1030, 1056, 1099
\AMCdontScan	329, 2011	\AMCmem@elt@cat .	887, 899, 903
\AMCdump@reponses	784, 798	\AMCmessage	17, 1151, 1164
\AMCEmptybox .	1024, 1049, 1084	\AMCncol@Background .	1456, 1851
\AMCendAnswer	984, 1012, 1996, 2057	\AMCncol@Border	1452, 1851
\AMCexponent .	1448, 1859, 1871	\AMCncol@BorderWidth	1454, 1850
\AMCform	17, 829, 2485	\AMCneeds@storeboxfalse .	2280
\AMCformAfterQuestion	812, 1164	\AMCneeds@storeboxtrue .	2281
\AMCformAnswer	811	\AMCnobloc	1145, 1227
\AMCformAnswerA	828, 932	\AMCnoCompleteMulti	13, 64, 1995
\AMCformatChoices	1320, 1900, 2044, 2080	\AMCNombreCopies	
\AMCformBeforeQuestion	811, 817	2175, 2176, 2461, 2464	
\AMCformBegin	17, 829, 2486	\AMCnoScoreZone	1129, 1224
\AMCformFilter	950	\AMCncontextGoto	1437, 1891
\AMCformHSpace	66, 827, 2058	\AMCncontextSign .	1444, 1667, 1668
\AMCformQuestion	811	\AMCncontextVHead	1438, 1620
\AMCformQuestionA	815, 939	\AMCnum@copies	
\AMCformQuestionN	814, 822	31, 2175–2177, 2180	
\AMCformS	829	\AMCnum@questions	785, 787
\AMCformVSpace	66, 811	\AMCnumeric@Hspace	
\AMCgroup@pre	713, 736	1439, 1451, 1578,	
\AMCgrouploop@next	738, 749, 764	1580, 1616, 1635, 1871	
\AMCgrouploop@prep	724, 747, 762	\AMCnumeric@Vspace	1440,
\AMCgrouppre@cyclic	707	1450, 1551, 1558, 1565,	
\AMCgrouppre@fixed	669	1592, 1608, 1622,	
\AMCgrouppre@withoutreplacement	685	1656, 1668, 1858, 1860	
\AMCgrouppre@withreplacement	676	\AMCnumericChoices	18, 1320
\AMChorizAnswerSep	1001, 1002, 1010	\AMCnumericChoicesPlain	
\AMChorizBoxSep	1003, 1004, 1007, 1009	1898, 1905	
\AMCid@check	27, 327, 2116, 2121,	\AMCnumericHide	1895, 1900
	2122, 2139, 2143, 2444	\AMCnumericOpts	1516
\AMCid@checkmax	594, 2122, 2273, 2444	\AMCnumericShow	1887, 1900
		\AMCnumero	1131, 2190
		\AMCocol@Background	
		1931, 1938, 2002	
		\AMCocol@BoxFrameRule	
		1932, 1956, 2002	
		\AMCocol@Foreground	
		1934, 1939,	
		2007, 2008, 2017, 2020	
		\AMCocol@FrameRule	
		1933, 1957, 2028	
		\AMCopen	1929
		\AMCopen@answer	
		1935, 1942, 1970, 1986	

\AMCopen@boxframerule	1954, 1955, 2001	\AMCrep@o	792, 794	B
\AMCopen@boxmargin	1952, 1953, 2000	\AMCrep@perso	982, <u>991</u>	\bareme 21, 2476
\AMCopen@contentcommand	1943, 2029	\AMCrep@r	796	\baremeDefaultM 21, 2477
\AMCopen@framerule	1958, 1959, 2027	\AMCrep@tikz	986, <u>991</u>	\baremeDefaultS 21, 2478
\AMCopen@Hspace	1944, 1945, 1999, 2004, 2015	\AMCrep@tikzmat	989, <u>991</u>	\bf 1447
\AMCopen@LineHeight	1948, 1949, 1969	\AMCrien@deux	<u>778</u> , 795	bloc (option) 21
\AMCopen@Lines	1950, 1951, 1974	\AMCscoreZone	<u>578</u> , <u>1024</u>	\bonne 21, 2474
\AMCopen@lines	1967	\AMCscoreZoneAnswerSheet	<u>1024</u>	\bool 905, 1218,
\AMCopen@lineuptext	1937, 1960, 1984, 1987, 1990	\AMCsection	<u>960</u>	1219, 1240, 1251, 1252,
\AMCopen@question 1936, 1941, 2003, 2004	\AMCsectionNumbered	<u>960</u> , <u>968</u>	1265, 1267, 1276, 1574,
\AMCopen@Width	1946, 1947, 1968	\AMCsectionStar	<u>964</u> , <u>968</u>	1585, 1600, 1619, 1624,
\AMCopenHide	2038, 2044	\AMCsetFoot	<u>2112</u>	1665, 1676, 1688, 1706,
\AMCopenOpts	1966	\AMCsetScoreZone	<u>1082</u> , 1083, 1129	1707, 1733, 1737, 1746,
\AMCopenShow	1977, 2044	\AMCsetScoreZoneAnswerSheet	<u>1127</u> – <u>1129</u>	1787, 1822, 1834, 1852
\AMCotextGoto	1929, 2039	\AMCshowSignificantDigits	<u>1385</u>	box (option) 11
\AMCotextReserved	1930, 1940, 2014, 2018, 2020	\AMCsignificantDigits	<u>1380</u>	\boxchar 335
\AMCoutsideLabelFormat	<u>518</u>	\AMCstudentlabel	<u>2217</u> – <u>2220</u>	
\AMCpageref	2220	\AMCStudentNumber	<u>2113</u>	
\AMCpostQquest	72, 2031	\AMCstudentslistfile	<u>2229</u>	
\AMCqlabel	<u>2221</u>	\AMCsubjectPageTag	<u>2150</u> , <u>2155</u>	
\AMCquestionaff	<u>1130</u>	\AMCsubsection	<u>960</u>	
\AMCquestionNumberfalse	1225	\AMCsubsectionNumbered	<u>962</u> , <u>969</u>	
\AMCquestionNumbertrue	45	\AMCsubsectionStar	<u>966</u> , <u>969</u>	
\AMCrandomseed	<u>242</u>	\AMCsw@p	<u>259</u>	
\AMCref	<u>2217</u>	\AMCsw@p@	<u>261</u> , <u>263</u> , <u>265</u>	
\AMCrep@@count	799, 801, 803	\AMCsz@loggedfalse	<u>578</u>	
\AMCrep@bloc	973, <u>991</u>	\AMCsz@loggedtrue	<u>591</u>	
\AMCrep@count	563, 566, 568, 572, 574, 772, 781, 801, 803, 807, 893, 931, 972, 978, 982, 986, 989, 993, 996, 1007, 1015, 1016, 1019–1022, 1233, 1237–1239, 1321, 1323, 1519, 1520, 1524, 1527, 2341, 2342, 2345	\AMCtext	<u>90</u>	
\AMCrep@fini	795, 798, 802, 810	\AMCtok@ik	<u>690</u> , 691, 693, 698–702, 722, 730, 743, 750, 766	
\AMCrep@init	<u>791</u> , 975, 978, 982, 986, 989	\AMCtok@k	<u>635</u> , 650–652, 656, 766	
\AMCrep@itemize	972, <u>991</u>	\AMCtok@max	<u>636</u>	
\AMCrep@ligne	978, <u>991</u>	\AMCtok@size	<u>637</u> , <u>725</u> – <u>728</u> , 736, 744, 751, 767	
		\AMCw@termark	<u>2082</u> , <u>2124</u>	
		\AMCw@terprint	<u>2082</u> , <u>2124</u>	
		amcxyfile (environment)	<u>339</u>	
		\answer	<u>288</u> , <u>1015</u> , <u>2309</u>	
		answers (option)	<u>11</u>	
		asbox (option)	<u>11</u>	
		\association	<u>2226</u>	
		auto (environment)	<u>2309</u>	
		automarks (option)	<u>12</u>	

\correcindiv (option)	21
\correctchoice	
14, 809, 1015, 1921, 2474	
\CorrigeExterne	2402
\CorrigeIndivExterne . . .	2402
\crefalias	225
\crefname	226
\cs	842, 846, 847, 849, 852, 855, 858, 862, 867, 869, 872, 874, 877, 879, 883, 884, 886, 889, 890, 892, 895, 896, 898, 901, 910–913, 1221, 1231, 1236, 1258, 1289, 1293, 1298, 1303, 1308, 1311, 1314–1317, 1335, 1343, 1353, 1356, 1361, 1365, 1377, 1380, 1382, 1385, 1387, 1393, 1407, 1412, 1424, 1512, 1516, 1518, 1532, 1547, 1572, 1583, 1598, 1612, 1642, 1663, 1684, 1728, 1887, 1889, 1895, 1904, 1907, 1908, 1916, 1926, 2391, 2392, 2394, 2395, 2397, 2398
\csvreader	
... 2316, 2321, 2327, 2336	
D	
\define@boolkey	
... 502, 1961–1964, 2049	
\define@choicekey	
... 77, 494, 1067, 1112	
digits (option)	11
\ding	466
\dontannotate	330
\dontscan	329
\dotfill	354, 1972, 1988
\draw	418, 422, 1043, 1045
E	
\element	15, 635
\endchoices	2471
\endchoicescustom	2473
\endchoiceshoriz	2472
\endcopieexamen	2481
\endexamcopy	2481
\endreponses	2471
\endresponseshoriz . . .	2472
\endresponsesperso . . .	2473
F	
\fancypagestyle	
... 2126, 2131, 2153, 2160	
\fbox	2151
\footrulewidth	
... 2129, 2148, 2158, 2163	
\foreach	2335
\formulaire	21, 2485
\fp	1347, 1355, 1357, 1359, 1363, 1368, 1370, 1372, 1376, 1383, 1388, 1395, 1413, 1416, 1717, 1718, 1742, 1743, 1752, 1780,
G	
\group	1339, 1351
H	
\he@dbas	2108, 2133, 2134
\he@dhaut	2109, 2137
\he@dtaille	2107–2109
\hfuzz	368
\ht	366, 1025
I	
\ifAMC@affichekeys	
... 36, 1157, 1158	
\ifAMC@asqbloc	42, 812, 818
\ifAMC@automarks	
60, 944, 2189, 2205, 2212	
\ifAMC@calibration	46, 294, 303, 312, 325, 329, 330, 333, 1016, 1021, 1151, 1167, 1200– 1203, 1238, 2185, 2191, 2225, 2230, 2342, 2449
\ifAMC@catalog	47, 385, 2467
\ifAMC@correc	38, 377, 1018, 1522, 1970, 1986, 2344
\ifAMC@correhead	
... 35, 1194, 2124, 2167, 2182, 2430, 2436	
\ifAMC@draw@cross	361, 400, 421
\ifAMC@ensemble	54, 523, 540, 561, 580, 832, 944, 947, 951, 956, 1158, 1326, 1729, 1880, 1881, 1978, 1983, 1997, 2003, 2034, 2053, 2058, 2061, 2070, 2189, 2445, 2455
\ifAMC@extractOnly	
... 40, 1848, 2459	
\ifAMC@fullGroups	34, 726
\ifAMC@inside@box	
... 52, 543, 571, 1998, 2059, 2446, 2456	
\ifAMC@inside@digit	55, 477
\ifAMC@invisible	61, 292
\ifAMC@keepmemory	954, 2194
\ifAMC@keysline	37, 1157, 1158

\ifAMC@ordre	32, 792	\ifKV@AMCdim@cross	
\ifAMC@outside@box 381, 396, 413	
. 53, 523, 541, 2447, 2457		\ifKV@AMCOpen@annotate 2012	
\ifAMC@pagelayout		\ifKV@AMCOpen@dots 1971	
... 58, 2121, 2166, 2429		\ifKV@AMCOpen@lineup ...	
\ifAMC@pdfform 1982, 2024	
62, 349, 2183, 2198, 2290		\ifKV@AMCOpen@scan 2011	
\ifAMC@plain	48, 2373	indivanswers (option) 7, 11	
\ifAMC@postcorrect		init (option) 11	
... 59, 809, 2448, 2458		\InputIfFileExists 15	
\ifAMC@printformoutside		\insertgroup 15, 716, 2483	
..... 521, 530		\insertgroupfrom 15, 716	
\ifAMC@printformoutside@		insidebox (option) 11	
..... 520, 527		\int 844, 846, 850, 856, 863,	
\ifAMC@printkeyoutside .		902, 1217, 1228, 1262,	
..... 538, 548		1284, 1348, 1364, 1392,	
\ifAMC@printkeyoutside@		1395, 1397–1399, 1401,	
..... 537, 545		1414, 1417, 1419, 1425,	
\ifAMC@qbloc	41,	1426, 1428, 1429, 1431,	
1139, 1156, 1164, 1190,		1530, 1533, 1535–	
1192, 1892, 2040, 2076		1537, 1539, 1548, 1573,	
\ifAMC@rbloc	43, 973, 976	1584, 1591, 1597, 1599,	
\ifAMC@shuffleG .	33, 717, 720	1601, 1607, 1613, 1615,	
\ifAMC@survey	2284, 2309	1620, 1626, 1630, 1634,	
\ifAMC@textPos	39,	1637, 1644, 1646, 1652,	
993, 996, 1006, 1156, 1164		1655, 1658, 1686, 1687,	
\ifAMC@watermark	51, 2124, 2435	1690, 1693, 1695, 1698,	
\ifAMC@zoneformulaire ..		1701, 1702, 1721–1723,	
..... 57, 525, 562, 833		1726, 1734, 1737, 1738,	
\ifAMCcomplete@multi	44, 806	1744, 1749, 1751, 1755,	
\ifAMCformulaire@dedans		1768, 1769, 1774, 1782,	
..... 56, 524,		1783, 1789, 1791, 1794,	
565, 581, 1729, 1881,		1801, 1808, 1809, 1813,	
1978, 2034, 2053, 2070		1814, 1816, 1829, 1836,	
\ifAMCids@side	74, 2142	1837, 1843, 1857, 1870	
\ifAMCids@top	73, 2139		
\ifAMCneeds@storebox ..		K	
..... 2280, 2287, 2298		\keys	1247, 1259,
\ifAMCquestionNumber	45, 1137		1443, 1513, 1732, 1890
\ifAMCsz@logged	578, 589	\keys (option)	11
\ifAMCtype@multi	50, 806		
\ifAMCune@bonne	49, 808	L	
\ifcase	78	\lastchoices	791, 2484
\ifcsname	1068, 1073,	\lastxpos	2395
1078, 1113, 1118, 1123		\lastypos	2398
\ifcsvstrcmp		\linebreak	1993
.. 2322, 2328, 2329, 2337			
\ifdim	1042	M	
\ifKV@AMCBoxOnly@ordered	2062	\m@rque	2106, 2133–2136
		\m@rqueCalage	2105, 2106
		\marginpar	1053, 1095
		N	
		\mauvaise	21, 2475
		\melangegroupe	21, 2482
		\MessageBreak	2371
		\multiSymbole 1139, 1166, 1184	
		O	
		\oddsidemargin ...	1036, 1040
		\onecopy 2174, 2311, 2385, 2479	
		options:	
		answers	11
		asbox	11
		automarks	12
		bloc	21
		box	11
		calibration	5, 11
		catalog	11
		chiffres	21
		completetmulti	11
		correc	21
		correcindiv	21
		digits	11
		ensemble	21
		francais	11
		fullgroups	12
		indivanswers	7, 11
		init	11
		insidebox	11
		keys	11
		nopage	6, 12
		noshuffle	11
		noshufflegroups	11
		nowatermark	5, 11
		ordre	21
		outsidebox	11

pdfform	12	reponseshoriz	(environment)	21	\textsf	503
plain	12	\reponsesperso	2473	\thecsvrow	998, 999, 2350, 2359	
postcorrect	12	reponsesperso	(environment)	21	tikz-multi	(environment) . 970
separateanswersheet	.	\restituegroupe	21, 2483	tikz-single	(environment) 970	
.....	5, 11, 17	\rngstate	2186	\tikzset	2348	
storebox	12			\times	1449	
\or	80, 82			\tl	864, 865, 870,	
ordre (option)	21			875, 904, 906, 1335,		
outsidebox (option)	11	S		1337, 1344, 1345, 1531,		
\ouverte@vs	1144	\savebox	359	1534, 1540, 1543, 1685,		
P		\savepos	2392	1696, 1697, 1700, 1704,		
\PackageError	\sbox	1025	1705, 1712, 1724, 1725		
.....	624, 662, 733, 2370	\scoring	\tracepos	296, 305, 314	
\pageref	2220	14, 1172, 1178, <u>1200</u> , 2476				
pdfform (option)	12	\scoringDefaultM	14, <u>1200</u> , 2477	U		
\pgfextractx	1033	\scoringDefaultS	14, <u>1200</u> , 2478	\une@rep	972, 973, 978, 982,	
\pgfpointanchor	1034	\ScoringExterne 2402	986, 989, 1018, 1022, 2344		
\pgfpointdiff	1033	\section 961, 965			
\pgfpointorigin	1033	separateanswersheet	(op-			
plain (option)	12	tion)			
postcorrect (option)	12	5, 11, 17				
\prg	831, 834,	\seq 1216, 1264,			
.....	836, 839, 1300, 1396, 1409	1272, 1338, 1346–1348				
Q		\setdefaultgroupmode	... 658			
\question	1144	\setgroupmode 644, <u>658</u>			
question (environment)	12, <u>1144</u>	\shuffle@it <u>784</u> , 798			
question-auto	(environ-	\shufflegroup			
ment) 2309 15, 682, 694, <u>716</u> , 2482				
\QuestionIndicative	\shufflegroupslice			
.....	14, <u>1200</u> , 1232 699, 702, 719				
questionmult (environment)	\smash 1970, 1986			
.....	12, <u>1144</u>	\space 2371			
Questionnaires	(environ-	\storebox 2300			
ment) 2309	storebox (option) 12			
questionouverte	(environ-	\str 899			
ment) 1144	\strut 1043, 1045			
R		\SujetExterne 2402			
\raisebox	1447	T				
\refstepcounter	1137	\tex 1341			
\reponses	2471	\textasciicircum 1449			
reponses (environment)	.. 21	\TextField 351			
\reponseshoriz	2472	\textit			
		99, 112, 139, 153, 192, 218				
		\textsc 2127			
X						
\x						